ARCADIS Design & Consultancy for natural and built assets


EYNESBURY TOWNSHIP

STAGE 22A CIVIL WORKS

MELTON CITY COUNCIL

DRAWING SCHEDULE	
DRAWING NUMBER	DRAWING TITLE
DRG-0001	COVER SHEET AND DRAWING SCHEDULE
DRG-0002	GENERAL NOTES
DRG-0010	SAFETY IN DESIGN SHEET 1
DRG-0011	SAFETY IN DESIGN SHEET 2
DRG-0012	SAFETY IN DESIGN SHEET 3
DRG-0100	EARTHWORKS LAYOUT PLAN SHEET 1
DRG-0101	EARTHWORKS LAYOUT PLAN SHEET 2
DRG-0200	SETOUT PLAN SHEET 1
DRG-0201	SETOUT PLAN SHEET 2
DRG-0220	ROADWORKS AND DRAINAGE LAYOUT PLAN SHEET 1
DRG-0221	ROADWORKS AND DRAINAGE LAYOUT PLAN SHEET 2
DRG-0240	GYMBOWEN AVENUE (MC04) LONGITUDINAL SECTION
DRG-0241	GYMBOWEN AVENUE (MC04) CROSS SECTIONS SHEET 1
DRG-0242	GYMBOWEN AVENUE (MC04) CROSS SECTIONS SHEET 2
DRG-0243	GYMBOWEN AVENUE (MC04) CROSS SECTIONS SHEET 3
DRG-0244	CHERRYPOOL CRESCENT (MC05) LONGITUDINAL SECTION
DRG-0245	CHERRYPOOL CRESCENT (MC05) CROSS SECTIONS SHEET 1
DRG-0246	CHERRYPOOL CRESCENT (MC05) CROSS SECTIONS SHEET 2
~~DRG-0247~~	~~CHERRYPOOL CRESCENT (MC05) CROSS SECTIONS SHEET 3~~ REMOVED FROM SET
DRG-0248	OZENKADNOOK WAY (MC07) LONGITUDINAL SECTION & CROSS SECTIONS
DRG-0249	GOROKE STREET (MC09) LONGITUDINAL SECTION & CROSS SECTIONS
DRG-0250	GOROKE STREET (MC09) CROSS SECTIONS
DRG-0251	KARNAK LANE (MC10) LONGITUDINAL SECTION & CROSS SECTIONS
DRG-0252	KARNAK LANE (MC11) LONGITUDINAL SECTION & CROSS SECTIONS
DRG-0253	KARNAK LANE (MC12) LONGITUDINAL SECTION & CROSS SECTIONS
DRG-0254	KARNAK LANE (MC12) CROSS SECTIONS
DRG-0260	INTERSECTION DETAIL PLAN SHEET 1
DRG-0261	INTERSECTION DETAIL PLAN SHEET 2
DRG-0262	INTERSECTION DETAIL PLAN SHEET 3
DRG-0263	INTERSECTION DETAIL PLAN SHEET 4
~~DRG-0264~~	~~INTERSECTION DETAIL PLAN SHEET 5~~ REMOVED FROM SET
~~DRG-0265~~	~~INTERSECTION DETAIL PLAN SHEET 6~~ REMOVED FROM SET
DRG-0280	TYPICAL DETAILS
DRG-0281	PAVEMENT PLAN SHEET 1
DRG-0282	PAVEMENT PLAN SHEET 2
DRG-0290	SIGNAGE AND LINEMARKING PLAN SHEET 1
DRG-0291	SIGNAGE AND LINEMARKING PLAN SHEET 2
DRG-0300	STORMWATER DRAINAGE LONGITUDINAL SECTIONS SHEET 1
DRG-0301	STORMWATER DRAINAGE LONGITUDINAL SECTIONS SHEET 2
DRG-0302	STORMWATER DRAINAGE LONGITUDINAL SECTIONS SHEET 3
DRG-0303	STORMWATER DRAINAGE LONGITUDINAL SECTIONS SHEET 4
DRG-0304	STORMWATER DRAINAGE LONGITUDINAL SECTIONS SHEET 5
DRG-0305	STORMWATER DRAINAGE LONGITUDINAL SECTIONS SHEET 6
DRG-0320	STORMWATER DRAINAGE PIT SCHEDULE

DRAWING SCHEDULE	
DRAWING NUMBER	DRAWING TITLE
DRG-0350	STORMWATER DRAINAGE 20% AEP CATCHMENT PLAN SHEET 1
DRG-0351	STORMWATER DRAINAGE 20% AEP CATCHMENT PLAN SHEET 2
DRG-0352	STORMWATER DRAINAGE 1% AEP CATCHMENT PLAN SHEET 1
DRG-0353	STORMWATER DRAINAGE 1% AEP CATCHMENT PLAN SHEET 2
DRG-0354	STORMWATER DRAINAGE 20% AEP OVERALL CATCHMENT PLAN
DRG-0356	STORMWATER DRAINAGE 1% AEP OVERALL CATCHMENT PLAN
DRG-0360	STORMWATER DRAINAGE CALCULATION TABLES SHEET 1
DRG-0361	STORMWATER DRAINAGE CALCULATION TABLES SHEET 2
DRG-0700	PASSIVE IRRIGATION LAYOUT SHEET 1
DRG-0701	PASSIVE IRRIGATION LAYOUT SHEET 2
DRG-0702	PASSIVE IRRIGATION DETAILS



LOCALITY PLAN
N.T.S
MELWAY REF 226 B2

LEVEL DATUM	
TBM	TDS8001
E	283462.24
N	5814502.34
RL	97.28

REAL PROPERTY DESCRIPTION
LOT S181 ON PS543210K
PARISH OF MOORADORANOOK
LOCAL AUTHORITY - MELTON CITY COUNCIL

nearmap.com IMAGERY EXTRACTED FROM nearmap.com

DISCLAIMER

THIS MAP HAS BEEN PREPARED USING nearmap.com IMAGERY. THIS DATA IS NOT GUARANTEED TO BE FREE FROM ERROR OR OMISSION. THEREFORE ARCADIS AND ITS EMPLOYEES DISCLAIM LIABILITY OF ANY ACT DONE OR OMISSION MADE ON THE INFORMATION CONTAINED IN THIS DATA AND ANY CONSEQUENCES OF SUCH ACTS OR OMISSIONS. THIS DRAWING IS PROVIDED FOR THE INFORMATION OF THE PERSON OR ORGANISATION TO WHOM ARCADIS PROVIDES IT. IT MAY NOT BE PROVIDED TO, OR USED BY, ANY OTHER PERSON WITHOUT ARCADIS' PRIOR WRITTEN CONSENT.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
03	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures

Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: COVER SHEET AND DRAWING SCHEDULE

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0001	04

100mm on Original

GENERAL NOTES

1. ALL DIMENSIONS ON THE DRAWINGS ARE IN METRES UNLESS SHOWN OTHERWISE.
2. ALL WORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH THE GENERAL CONDITIONS OF CONTRACT, AS AMENDED.
3. THE CONTRACTOR SHALL PROVIDE A MINIMUM SEVEN (7) BUSINESS DAYS NOTIFICATION PERIOD TO COUNCIL AND ALL SERVICES PRIOR TO COMMENCEMENT OF WORKS, UNLESS NOTED OTHERWISE.
4. ALL WORK SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE RELEVANT AUTHORITY SPECIFICATIONS AND STANDARD DRAWINGS AS APPROVED BY THE RELEVANT AUTHORITY. IN THE CASE OF DISPUTE THE SPECIFICATIONS TAKE PRECEDENCE.
5. ALL WORKS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AUTHORITY APPROVED ARCADIS PROJECT DRAWINGS AND CONTRACT SPECIFICATIONS.
6. PRIOR TO COMMENCEMENT OF WORKS ON SITE, THE CONTRACTOR MUST ENSURE THAT ALL MATTERS RELATING TO OCCUPATIONAL HEALTH AND SAFETY, HAVE BEEN ADDRESSED. ALL REQUIRED NOTIFICATIONS TO BE SUBMITTED AND COMPLY WITH THE VICTORIAN WORKCOVER AUTHORITY. DETAILS OF THE CONTRACTORS OCCUPATIONAL HEALTH & SAFETY PROCEDURES TO BE LODGED WITH THE SITE ENGINEER PRIOR TO COMMENCEMENT OF WORKS.
7. ALL WORKS SHALL COMPLY WITH THE REQUIREMENTS OF THE MINES ACT 1958, THE MINES (TRENCHES) REGULATIONS 1982, THE OCCUPATIONAL HEALTH AND SAFETY ACT 2004, THE OCCUPATIONAL HEALTH AND SAFETY (MINES) REGULATIONS 2002, WORKSAFE AND ANY OTHER LEGISLATION APPLICABLE AT THE TIME OF COMMENCEMENT OF WORKS.
8. THE CONTRACTOR SHALL UNDERTAKE SERVICE PROVING OF ALL EXISTING SERVICES PRIOR TO COMMENCEMENT OF WORKS AND ADVISE THE CONSTRUCTION SUPERINTENDENT OF ANY DISCREPANCY WITH THE INFORMATION PROVIDED ON THE CONTRACT DRAWINGS.
9. THE DRAWINGS SHALL BE READ IN CONJUNCTION WITH OTHER CONSULTANTS PLANS, SPECIFICATIONS & OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED BY THE SUPERINTENDENT DURING THE COURSE OF THE CONTRACT.
10. NO BLASTING WORKS SHALL BE UNDERTAKEN WITHIN 4.5m OF EXISTING UTILITIES OR 15m OF ANY COMPLETED PART OF THE WORKS WITHOUT PRIOR CONSENT FROM THE SITE ENGINEER/CONSTRUCTION SUPERINTENDENT. THE CONTRACTOR SHALL OBTAIN ALL RELEVANT AUTHORITY PERMITS PRIOR TO COMMENCEMENT OF ANY BLASTING WORKS.
11. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE FOR ANY DAMAGE INCURRED TO EXISTING UTILITY SERVICES AS A RESULT OF THE EXECUTION OF WORK UNDER THE CONTRACT.
12. NO WORK SHALL BE CARRIED OUT WITHIN 3 METRES OF ANY EXISTING SERVICES WITHOUT PRIOR RECORDED CONSULTATION WITH THE RELEVANT AUTHORITY.
13. ALL EXISTING SERVICES & STRUCTURES ARE TO BE MAINTAINED IN GOOD ORDER FOR THE DURATION OF THE CONTRACT & WHERE RELOCATION IS REQUIRED, REFER SPECIFICATION.
14. COUNCIL AND SUPERINTENDENT TO BE NOTIFIED SEVEN (7) BUSINESS DAYS PRIOR TO COMMENCEMENT OF WORKS.
15. CONTRACTOR SHALL MEET THE REQUIREMENTS OF THE CULTURAL MANAGEMENT PLAN FOR THIS STAGE.
16. ALL AREAS DISTURBED AS RESULT OF CONNECTION TO EXISTING UTILITY SERVICES, ROADWAYS AND ADJOINING PROPERTIES SHALL BE REINSTATED AS PART OF THE WORKS.
17. ALL NEW WORKS SHALL MATCH NEATLY TO EXISTING AND TO THE SATISFACTION OF COUNCIL AND THE SUPERINTENDENT.

SURVEY NOTES

1. THE EXISTING SITE CONDITIONS AND UTILITY SERVICES INFORMATION SHOWN HAS BEEN COMPILED FROM SURVEY INFORMATION SUPPLIED BY OTHERS. THE INFORMATION IS SHOWN TO PROVIDE A BASIS FOR DESIGN. ARCADIS DOES NOT GUARANTEE THE ACCURACY OR COMPLETENESS OF THE SURVEY BASE OR ITS SUITABILITY AS A BASIS FOR CONSTRUCTION DRAWINGS.
2. THE INFORMATION IS NOT INTENDED TO PROVIDE THE CONTRACTOR WITH COMPLETE OR ACCURATE INFORMATION CONCERNING THE LOCATION & EXTENT OF UTILITY SERVICES.
3. THE CONTRACTOR SHALL VERIFY THE LOCATION, DEPTH & EXTENT OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF WORK.
4. ALL EXISTING SURFACE LEVELS SHOWN ON THE ENGINEERING DRAWINGS HAVE BEEN INTERPOLATED FROM A DIGITAL TERRAIN MODEL. THESE LEVELS HAVE BEEN USED AS THE BASIS FOR ALL ENGINEERING DESIGN.
5. SHOULD DISCREPANCIES BE ENCOUNTERED DURING CONSTRUCTION BETWEEN THE SURVEY DATA AND ACTUAL FIELD DATA, THE CONTRACTOR SHALL CONTACT THE CONSTRUCTION SUPERINTENDENT.
6. ALL HIGH STABILITY PSM'S ARE TO BE TO MGA COORDINATES & LEVELLED BY A LICENSED SURVEYOR WITH RESULTS FORWARDED TO COUNCIL.
7. ALL LEVELS ARE TO AUSTRALIAN HEIGHT DATUM AND ALL COORDINATES ARE TO MAP GRID OF AUSTRALIA (MGA) ZONE 55 UNLESS NOTED OTHERWISE.
8. TBM'S TO BE RE-ESTABLISHED BY THE LICENSED SURVEYOR IF FOUND TO BE MISSING AT THE COMMENCEMENT OF CONSTRUCTION.
9. SHOULD ANY MARKS BE DISTURBED, THE CONTRACTOR WILL IMMEDIATELY NOTIFY THE DEVELOPER'S CONSULTANT TO ARRANGE RE-INSTATEMENT AT THE CONTRACTORS EXPENSE.
10. THE CONTRACTOR MUST COMPLETE A LEVEL CHECK BETWEEN ALL TBM'S TO VERIFY LEVEL VALUES BEFORE COMMENCEMENT OF WORKS.

WORKING IN CLOSE PROXIMITY TO OVERHEAD ELECTRICAL POWERLINES NOTES

1. THE CONTRACTOR SHALL TAKE CARE WHEN UNDERTAKING WORKS WITHIN CLOSE PROXIMITY TO OVERHEAD POWERLINES AND SHALL CONDUCT WORKS IN ACCORDANCE WITH AUTHORITY REQUIREMENTS.
2. THE CONTRACTOR SHALL PROVIDE A MINIMUM TEN (10) BUSINESS DAYS NOTIFICATION PERIOD TO THE AUTHORITY PRIOR TO COMMENCEMENT OF WORKS.
3. THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS PRIOR TO COMMENCEMENT OF WORKS WITH ANY ADDITIONAL SAFETY PRECAUTIONS INCLUDED WITHIN THE CONTRACTORS SAFE WORK METHOD STATEMENT FOR THE WORKS AND COMMUNICATED TO THE CONSTRUCTION SUPERINTENDENT.
4. ALL WORKS WITHIN CLOSE PROXIMITY TO EXISTING POWERLINES SHALL BE UNDERTAKEN IN ACCORDANCE WITH THE AUTHORITIES NO GO ZONE REQUIREMENTS AND THAT THE CONTRACTOR AND SUB-CONTRACTORS HAVE MET THIS REQUIREMENTS INCLUDING PROVISION OF A SPOTTER IF REQUIRED.
5. ANY VEHICLES OR EQUIPMENT EXCEEDING 3.0m MAXIMUM OPERATING HEIGHT ARE NOT PERMITTED TO UNDERTAKE WORKS UNDER POWERLINES UNLESS WRITTEN APPROVAL IS OBTAINED FROM THE AUTHORITY FOR A GREATER OPERATING HEIGHT LIMIT. AN INCREASE TO THE OPERATING HEIGHT LIMIT IS SUBJECT TO ACHIEVING ADEQUATE CLEARANCE TO CONDUCTORS.
6. THE FOLLOWING ARE NOT PERMITTED UNDER EXISTING POWERLINES:
   - MAINTENANCE OR REFUELING OF VEHICLES AND EQUIPMENT
   - STORAGE AND HANDLING OF FLAMMABLE LIQUIDS OR GASES
   - STOCKPILING OF EXCAVATED MATERIAL IS NOT PERMITTED UNDER POWERLINES
   - CONTRACTOR SITE COMPOUND, STORAGE AREAS AND VEHICLE CAR PARKING POWERLINES.
7. ALL STORMWATER PITS, REINFORCED CONCRETE PIPES, REINFORCED CONCRETE BOX CULVERTS AND ANY OTHER EXPOSED STEEL SHALL BE COMPLETELY SECTIONALISED AND ISOLATED AS DIRECTED BY THE CONSTRUCTION SUPERINTENDENT FOR WORKS WITHIN 30m OF AN EXISTING OR PROPOSED ELECTRICAL TOWER
8. REINFORCED CONCRETED PIPES AND BOX CULVERTS THAT HAVE BEEN CUT AND HAVE EXPOSED STEEL ARE ONLY PERMISSIBLE WITHIN STORMWATER PITS WITH ALL EXPOSED STEEL TO BE COMPLETELY SECTIONALISED AND ISOLATED

WORKING IN CLOSE PROXIMITY TO GAS TRANSMISSION PIPELINES NOTES

1. THE CONTRACTOR SHALL TAKE CARE WHEN UNDERTAKING WORKS WITHIN CLOSE PROXIMITY TO GAS TRANSMISSION PIPELINES AND SHALL CONDUCT WORKS IN ACCORDANCE WITH AUTHORITY REQUIREMENTS.
2. THE CONTRACTOR SHALL PROVIDE A MINIMUM FORTY-EIGHT (48) HOURS NOTIFICATION PERIOD TO THE AUTHORITY PRIOR TO COMMENCEMENT OF PROVING AND / OR CONSTRUCTION TO ALLOW ARRANGEMENTS FOR A CORPORATION INSPECTOR TO ATTEND SITE DURING THE WORKS.
3. PROVING SHALL BE UNDERTAKEN BY HAND AND UNDER THE SUPERVISION OF A CORPORATION INSPECTOR.
4. UPON COMPLETION OF SERVICE PROVING THE CONTRACTOR SHALL SUPPLY PROVING INFORMATION TO THE CONSTRUCTION SUPERINTENDENT FOR REVIEW AND CONFIRMATION IN ACHIEVING THE FOLLOWING MINIMUM CLEARANCES;
   - 300mm TOP OF PIPELINE TO UNDERSIDE OF ROAD PAVEMENT BOXING
   - 1.2m TOP OF PIPELINE TO FINISHED SURFACE LEVELS
   - 300mm BETWEEN PIPELINE AND INSTALLATION OF EQUIPMENT $\leq$ 1.5m WIDE CROSSING PERPENDICULAR TO THE PIPELINE
   - 500mm BETWEEN PIPELINE AND INSTALLATION OF EQUIPMENT > 1.5m WIDE CROSSING PERPENDICULAR TO THE PIPELINE
   - 500mm BETWEEN PIPELINE AND INSTALLATION OF EQUIPMENT PARALLEL TO THE PIPELINE
4. THE CONTRACTOR SHALL ENSURE THAT THE MINIMUM CLEARANCES ARE ACHIEVED ONSITE.
5. NO MECHANICAL EQUIPMENT SHALL BE USED WITHIN 1.0m OF THE PIPELINE AT ALL TIMES EXCEPT FOR BORING OPERATIONS.
6. WHEN UNDERTAKING BORING OPERATIONS, HAND EXCAVATION ADJACENT TO THE PIPELINE IS REQUIRED 1.0m FROM THE SIDE FROM THE PIPELINE FROM WHICH THE BORE WILL APPROACH. THE AUGER IS TO BE CHECKED WHEN IT REACHES THIS EXCAVATION TO ENSURE THAT THE REQUIRED MINIMUM CLEARANCE IS MAINTAINED BETWEEN THE BORE AND THE PIPELINE.
7. EXTREME CAUTION IS REQUIRED FOR ANY BLASTING BEING CARRIED OUT WITHIN CLOSE PROXIMITY TO THE PIPELINE AND SHALL BE UNDERTAKEN UNDER SUPERVISION OF A CORPORATION INSPECTOR. BLASTING RESTRICTIONS MUST BE IN ACCORDANCE WITH SAA EXPLOSIVES CODE 2187, AND ONLY MODIFIED AFTER EXPLICIT AGREEMENT WITH A CORPORATION ENGINEER.

SITE DEMOLITION & CLEARING NOTES

1. CONTRACTOR SHALL CONFIRM WITH THE CONSTRUCTION SUPERINTENDENT OF ANY REQUIREMENTS FOR AN AUTHORISED SPOTTER-CATCHER OR ARBORIST TO BE ON SITE PRIOR TO THE COMMENCEMENT OF & DURING THE CLEARING WORK.
2. ANY CLEARING REQUIRED TO BE UNDERTAKEN BY THE CONTRACTOR IS TO BE STRICTLY IN ACCORDANCE WITH THE APPROVED ENVIRONMENTAL MANAGEMENT PLAN.
3. THE CONTRACTOR SHALL COMPLY WITH THE REQUIREMENTS AS OUTLINED WITHIN THE ENVIRONMENTAL PROTECTION AUTHORITY VICTORIA PUBLICATION 'CONSTRUCTION TECHNIQUES FOR SEDIMENT POLLUTION CONTROL' DURING ALL PHASES OF CONSTRUCTION.
4. EROSION & SEDIMENT CONTROL MEASURES ARE TO BE INSTALLED PRIOR TO COMMENCEMENT OF CLEARING & GRUBBING WORKS.
5. CONTRACTOR TO PROVIDE ADEQUATE PROTECTION AGAINST SILT RUNOFF FROM THE SITE AS PART OF THEIR ENVIRONMENTAL MANAGEMENT PLAN (EMP).
6. A TEMPORARY 1.5M HIGH POST & WIRE FENCE SHALL BE ERECTED AND MAINTAINED AROUND EXISTING TREES, NOMINATED TO BE RETAINED AS PER A TREE PROTECTION ZONE (TPZ) CONDITION, AT ALL TIMES DURING CONSTRUCTION. UNDER NO CIRCUMSTANCES SHALL SITE SHEDS, VEHICLES, MACHINERY AND EQUIPMENT BE STORED OR PLACED WITHIN FENCED ZONE OF THESE TREES. FENCE TO BE INSTALLED PRIOR TO THE PRE START MEETING WITH COUNCIL.
7. NO NATIVE VEGETATION SHALL BE DESTROYED, FELLED, LOPPED RING BARKED OR UPROOTED WITHOUT THE CONSENT OF THE MUNICIPAL ENGINEER OR HIS REPRESENTATIVE.
8. THE AREA WITHIN THE LIMITS OF CLEARING SHALL BE CLEARED OF ALL VEGETATION, ALL MINOR MAN-MADE STRUCTURES (SUCH AS FENCES, BUILDING MATERIAL & EXISTING DRIVEWAYS), ALL RUBBISH & OTHER MATERIALS WHICH, IN THE OPINION OF THE SUPERINTENDENT, ARE UNSUITABLE FOR USE IN THE WORKS WITH THE EXCEPTION OF CERTAIN TREES MARKED FOR PRESERVATION.
9. PRIOR TO REMOVAL, TREES ARE TO BE MARKED BY CONTRACTOR AND APPROVED BY THE CONSTRUCTION SUPERINTENDENT AND COUNCIL REPRESENTATIVE.
10. TREES ARE TO BE MULCHED & STOCKPILED ON SITE FOR USE IN LANDSCAPING.
11. WHERE PARTS OF TREES CANNOT BE MULCHED, THEY ARE TO BE DISPOSED OF OFF-SITE AT AN APPROVED FACILITY.
12. ON COMPLETION THE CONTRACTOR IS RESPONSIBLE FOR THE REMOVAL OF ALL BUILDING WASTE, RUBBISH AND SPOIL FROM THE SITE. NO SURPLUS TREES, VEGETATION OR OTHER MATERIALS IS TO BE BURNT ON SITE.

EARTHWORKS NOTES

1. ALL WORK SHOULD BE UNDERTAKEN IN ACCORDANCE WITH AS 3798-2007 GUIDELINES ON EARTHWORKS FOR COMMERCIAL AND RESIDENTIAL DEVELOPMENTS AND UNDER LEVEL 1 SUPERVISION.
2. THE CONTRACTOR IS TO FENCE LIMIT PRIOR TO PRE START MEETING WITH COUNCIL.
3. EROSION & SEDIMENT CONTROL MEASURES ARE TO BE MAINTAINED DURING EARTHWORKS.
4. TOPSOIL SHOULD BE STRIPPED AND STOCKPILED FROM ALL AREAS WHERE EARTHWORKS ARE TO BE CONDUCTED. BEFORE COMPLETING THE SITE WORKS, TOPSOIL SHOULD BE PLACED AND REHABILITATED TO REPLICATE THE PREDEVELOPMENT DEPTHS AS APPROPRIATE.
5. DESIGN LEVELS GIVEN ARE FINISHED SURFACE LEVELS INCLUSIVE OF TOPSOIL.
6. REFER TO ROAD CROSS SECTIONS FOR BATTER GRADES. BATTER GRADES OF MAXIMUM 1 IN 6 SHALL BE ADOPTED WHERE GRADES ARE NOT SPECIFIED.
7. NOTWITHSTANDING THE LIMITS OF CUTTING & FILLING SHOWN ON THE DRAWINGS, THE ACTUAL LIMITS SHALL BE DETERMINED ON SITE BY THE CONSTRUCTION SUPERINTENDENT DURING CONSTRUCTION. FINISHED SURFACE CONTOURS MAY BE ADJUSTED BY WRITTEN DIRECTION OF THE ENGINEER DURING CONSTRUCTION.
8. WHERE FILL EXCEEDS 300mm THE FILL SHALL BE COMPACTED IN ACCORDANCE WITH THE REQUIREMENTS OF TABLE 204.131 COMPACTION REQUIREMENTS SCALE C OF VICROADS SPECIFICATION AND TRIMMED AND SHAPED TO MATCH EXISTING SITE LEVELS, EXCEPT IN AREAS NOMINATED FOR SOFT LANDSCAPING. GEOTECHNICAL TEST RESULTS AND LEVEL 1 SUPERVISION CERTIFICATION TO BE SUBMITTED TO COUNCIL'S ENGINEERING DEPARTMENT FOR APPROVAL.
9. ALL FILL PLACED ON THE SITE IS TO COMPRISE OF ONLY NATURAL EARTH & ROCK & IS TO BE FREE OF ALL CONTAMINANTS (REFER TO THE ENVIRONMENTAL PROTECTION ACT 1994 SECTION 11). NO DEMOLITION MATERIAL SHALL BE USED UNLESS NOTED ON THE DRAWINGS AND PROJECT SPECIFICATION OR APPROVED BY THE CONSTRUCTION SUPERINTENDENT AND COUNCIL.
10. ALL RETAINING WALL SUBSURFACE DRAINAGE SHALL ACHIEVE LEGAL POINT OF DISCHARGE TO STORMWATER DRAINAGE INFRASTRUCTURE.
11. THE CONTRACTOR SHALL OBTAIN COUNCIL APPROVAL FOR THE REMOVAL AND DISPOSAL OF ANY EXCAVATED MATERIAL OR TOPSOIL NOT BEING RETAINED ONSITE.
12. ALL ALLOTMENTS AND RESERVES SHALL BE SMOOTHED, GRADED AND SHAPED TO AN EVEN SURFACE AND BE FREE DRAINING.
13. ALL AREAS DISTURBED AS PART OF THE WORKS SHALL BE RESURFACED WITH A MINIMUM 100mm THICK LAYER OF TOPSOIL UNLESS NOTED OTHERWISE AND ADEQUATELY STABILISED IN ACCORDANCE WITH THE LANDSCAPE DRAWINGS. IN THE ABSENCE OF A NOMINATED METHOD, TURF SHALL BE ADOPTED.

ROADWORKS NOTES

1. CHAINAGES TO ROADWAYS AND DRAINAGE CHANNELS ARE MEASURED ALONG THE CONTROL LINE / CENTRELINE UNLESS NOTED OTHERWISE.
2. CHAINAGES AND RADII TO CUL-DE-SAC HEADS AND KERB RETURNS ARE TO LIP OF KERB UNLESS NOTED OTHERWISE.
3. THE CONTRACTOR SHALL OBTAIN ANY ROAD OPENING PERMIT PRIOR TO UNDERTAKING ANY WORKS WITHIN AN EXISTING ROADWAY INCLUSIVE OF ANY REQUIRED TRAFFIC MANAGEMENT PLANS.
4. THE CONTRACTOR SHALL ERECT TRAFFIC CONTROL DEVICES IN ACCORDANCE WITH THE APPROVED TRAFFIC MANAGEMENT PLAN.
5. THE ROAD PAVEMENT ADOPTED WILL BE DETERMINED BY THE GEOTECHNICAL ENGINEER AND APPROVED BY COUNCIL. THIS PAVEMENT SHALL BE BASED ON SOIL TEST TAKEN AT SUBGRADE LEVEL. ANY VARIATIONS TO THE NOMINAL PAVEMENT THICKNESS WILL BE PAID AT THE RATES SHOWN IN THE TENDER SCHEDULE.
6. SUBGRADE SHALL BE COMPACTED 97% DRY DENSITY OF THE MAXIMUM FOUND IN STANDARD COMPACTION TEST IN AREAS OF CUT TO A DEPTH OF 150mm AND IN AREAS OF FILL TO A DEPTH OF 450mm.
7. RELATIVE COMPACTION OF CRUSHED ROCK WITHIN PAVEMENTS SHALL BE UNDERTAKEN AT THE OPTIMUM MOISTURE CONTENT TO A DRY DENSITY (BASED ON THE PERCENTAGE OF THE MAXIMUM DRY DENSITY OBTAINED IN THE MODIFIED COMPACTION TEST) AS FOLLOWS;
   - 0-100mm BELOW TOP OF BASE, RELATIVE COMPACTION OF 100%
   - 100-300mm BELOW TOP OF BASE, RELATIVE COMPACTION OF 98%
   - >300mm BELOW TOP OF BASE, RELATIVE COMPACTION OF 97%.
8. THE NATURE STRIPS AND CUT OR FILLED AREAS ARE TO BE TOPSOILED WITH 100mm OF APPROVED MATERIAL.
9. THE CONTRACTOR SHALL COORDINATE WITH ALL SUBCONTRACTORS AND AUTHORITIES ENSURE THAT ALL SERVICES ARE INSTALLED PRIOR TO INSTALLATION OF THE FINAL PAVEMENT COURSE.
10. SUBSOIL DRAINS SHALL BE PROVIDED UNDER ALL KERBS IN ACCORDANCE WITH AUTHORITY STANDARDS.
11. SUBSOIL DRAIN LOCATION & EXTENTS SHALL BE DETERMINED ON SITE BY THE SITE ENGINEER / SUPERINTENDENT.
12. ROAD CROSSING CONDUITS LOCATIONS ARE SUBJECT TO CHANGE. THE CONTRACTOR SHALL SEEK WRITTEN CLARIFICATION FROM THE CONSTRUCTION SUPERINTENDENT REGARDING ANY CHANGES TO THE ROAD CROSSING CONDUITS PRIOR TO INSTALLATION.
13. ALL ROAD CROSSING CONDUITS SHALL BE INSTALLED TO THE RELEVANT AUTHORITY STANDARDS.
14. KERB MARKERS ARE TO BE INSTALLED TO THE KERB FACE ABOVE UTILITY CONDUIT LOCATIONS AND UNDERGROUND STORMWATER CONNECTIONS IN ACCORDANCE WITH AUTHORITY REQUIREMENTS.
15. BACKFILL TO ALL UTILITY SERVICING TRENCHES WITHIN ROAD RESERVE SHALL BE 20mm CLASS 3 CRUSHED ROCK COMPACTED TO A DRY DENSITY NOT LESS THAN 97% OF THE MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING;
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE CROSS PAVEMENT
   - ADJACENT TO THE KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE.
19. ALL FOOTPATHS SHALL BE MINIMUM 1.50m WIDE UNLESS NOTED OTHERWISE AND CONSTRUCTED IN ACCORDANCE WITH AUTHORITY STANDARDS INCLUDING A MINIMUM OF 50mm MECHANICALLY COMPACTED 20mm CLASS 3 CRUSHED ROCK OR CLASS 3 CRUSHED CONCRETE . FOR AREAS IN FILL, CRUSHED ROCK SHALL EXTEND DOWN TO THE EXISTING NATURAL SURFACE IN ACCORDANCE WITH AUTHORITY STANDARDS.
20. ALL DRIVEWAYS TO BE CONSTRUCTED IN ACCORDANCE WITH AUTHORITY STANDARDS AND SHALL BE OFFSET 0.75m FROM SIDE BOUNDARY OR EASEMENT UNLESS NOTED OTHERWISE.
21. ALL DRIVEWAYS AND PRAM RAMPS SHALL BE LOCATED A MINIMUM 1.0m FROM STORMWATER PITS.
22. ALL PRAM RAMPS SHALL BE LOCATED A MINIMUM OF 2.0m FROM DRIVEWAYS.

STORMWATER DRAINAGE NOTES

1. ALL REINFORCED CONCRETE DRAINAGE PIPES SHALL BE CLASS 2 UNLESS NOTED OTHERWISE. PIPE CLASSIFICATION TO INCREASE WHERE LESS THAN 600mm COVER IS ACHIEVED TO PAVEMENT SUBGRADE LEVEL. CONTRACTOR TO CONFIRM PIPE CLASS DURING TENDER.
2. ALL DRAINAGE PIPES SHALL BE RUBBER RING BELLED SOCKET JOINTS (RRJ) UNLESS NOTED OTHERWISE.
3. ALL DRAINAGE TRENCHES TO BE BACKFILLED AND COMPACTED IN ACCORDANCE WITH AUTHORITY STANDARDS.
4. EXPOSURE CLASSIFICATION FOR ALL REINFORCED CONCRETE BOX CULVERTS SHALL MEET THE EXPECTED ENVIRONMENTAL CONDITIONS AS OUTLINED WITHIN AS3600 TABLE 4.3. CONTRACTOR TO CONFIRM EXPOSURE CLASSIFICATION DURING TENDER.
5. CAST INSITU BASE SLABS SHALL BE USED FOR ALL REINFORCED CONCRETE BOX CULVERTS UNLESS NOTED OTHERWISE. CONTRACTOR TO CONFIRM ALLOWANCE FOR CAST INSITU BASE SLABS DURING TENDER.
6. STORMWATER DRAINAGE PIPES SHALL NOT BE SUBJECTED TO CONSTRUCTION TRAFFIC LOADING DURING CONSTRUCTION UNLESS THE PIPE STRENGTH CHARACTERISTICS HAVE BEEN ASSESSED IN ACCORDANCE WITH AS.3725-2007, LOADS ON BURIED PIPES.
7. CONCRETE PIPES DAMAGED DUE TO CONSTRUCTION LOADS SHALL BE REPLACED AT THE CONTRACTOR'S COST.
8. DRAINAGE PITS SHALL BE CAST MONOLITHICALLY WITH CEMENT RENDER ONLY USED FOR DEFECT REPAIRS.
9. WHERE THE DROP THROUGH A STORMWATER PIT IS LESS THAN 50mm THE CONTRACTOR SHALL PROVIDE HALF HEIGHT CONCRETE BENCHING IN ACCORDANCE WITH AUTHORITY STANDARDS.
10. CONTRACTOR IS TO VERIFY ALL FINISHED SURFACE LEVELS OF PROPOSED STORMWATER PITS BEFORE CONSTRUCTING TO FINISHED LEVELS.
11. ALL STORMWATER PIT COVERS AND GRATES SHALL BE IN ACCORDANCE WITH AUTHORITY STANDARDS.
12. ALL PROPERTY INLET CONNECTIONS TO DRAINAGE INFRASTRUCTURE WITHIN COUNCIL ROAD RESERVE SHALL BE CONSTRUCTED IN ACCORDANCE WITH AUTHORITY STANDARDS
13. ALL PROPERTY INLET CONNECTIONS WITHIN PRIVATE PROPERTY SHALL BE LOCATED 1.0m FROM THE LOW SIDE BOUNDARY UNLESS NOTED OTHERWISE AND INSTALLED AT A MINIMUM DEPTH OF 400mm OR AS SPECIFIED WITHIN AUTHORITY STANDARDS.

SIGNAGE & LINEMARKING NOTES

1. THE CONTRACTOR SHALL CONFIRM THE ROAD NAMES WITH THE CONSTRUCTION SUPERINTENDENT PRIOR TO ORDERING OF STREET NAME SIGNAGE.
2. THE CONTRACTOR SHALL INSTALL AND MAINTAIN ANY NECESSARY TEMPORARY SIGNAGE AND LINE MARKING IN ACCORDANCE WITH THE APPROVED TRAFFIC MANAGEMENT INCLUDING REINSTATEMENT AT THE COMPLETION OF THE WORKS.
3. ALL SIGNAGE, LINEMARKING & REFLECTORISED PAVEMENT MARKERS ARE TO BE IN ACCORDANCE WITH AS1742 PARTS 1-15 AND THE VICROADS TRAFFIC ENGINEERING MANUAL VOLUMES 1 AND 2.
4. ALL TRAFFIC SIGNS TO BE SIZE 'B' UNLESS NOTED OTHERWISE.
5. THE CONTRACTOR SHALL SUPPLY AND ERECT ALL STREET SIGNAGE IN ACCORDANCE WITH THE AUTHORITY STANDARDS.
6. ALL SIGNAGE TO BE MADE REDUNDANT ARE TO BE REMOVED FROM SITE OR RELOCATED AS SHOWN ON THE DRAWINGS.
7. FINAL SIGN LOCATIONS TO BE DETERMINED ON SITE BY THE SUPERINTENDENT AND COUNCIL REPRESENTATIVE.
8. EXISTING LINEMARKING MADE REDUNDANT BY NEW LINEMARKING IS TO BE REMOVED BY HIGH PRESSURE WATER BLASTING OR OTHER METHOD APPROVED BY THE AUTHORITY.
9. ALL LINEMARKING TO BE LONG LIFE THERMOPLASTIC REFLECTORISED WHITE PAINT UNLESS NOTED OTHERWISE.
10. GUIDEPOSTS TO BE INSTALL IN ACCORDANCE WITH AUTHORITY STANDARDS.
11. ALL TACTILE GROUND SURFACE INDICATORS SHALL BE INSTALLED IN ACCORDANT WITH AS1428.4.1.

Issue	Description	DR	CH	VE	Date
02	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

GENERAL NOTES

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0002	02

100mm on Original

SAFETY IN DESIGN REGISTER

PROJECT	Eynesbury Township Pty Ltd
LOCATION	Eynesbury Township
PROJECT NUMBER	10029435
PROJECT DESCRIPTION	xxxx

Risk ID No.	Design Phase	Discipline	Phase of Project	Hazard/ Aspect	Risks/ Opportunities/ Impacts	Risk					Proposed Controls (to mitigate or avoid - include reference to any standards or code used)	Mitigated Risk / Opportunity					Likely Risk Entity	Comment
						Probability/ Likelihood		Consequence/ Benefit/ Impact		Level		Probability/ Likelihood		Consequence/ Benefit/ Impact		Level		
DD1	Detailed Design	Civil	Construction	Construction within the vicinity of live traffic, abutting exisiting stages	Discruptions or accident involving live traffic	1	Rare	5	Catostrophic	Medium	Provide safety barriers, traffic controls and implementation of Traffic Management Plan. TCP provided within contract.	1	Rare	3	Moderate	Low	Contractor	
DD2	Detailed Design	Civil	Construction	Moving vehicles / Physical harm from being hit by moving vehicles or vehicle strike to infrastructure	Physical harm from being hit by moving vehicles or vehicle strike to infrastructure / Fatality	2	Unlikely	3	Moderate	Medium	Approved or designated areas for pedestrians. High visibility clothing to be provided and worn on all site visits. Visitors to adhere to designated pedestrian areas. Specify trenchless construction techniques (where possible) for existing road crossings. Specify on drawings the requirement for the Contractor to prepare a traffic management plan in accordance with AS1742.3.	1	Rare	3	Moderate	Low	Contractor	
DD3	Detailed Design	Civil	Construction	Vehicle movement conflicts with utilities / clear zones / pits	Injury or vehicle accident	2	Unlikely	3	Moderate	Medium	Sequence works, Traffic control (TCP), temporary fencing or barriers to be installed. TCP provided within contract.	1	Rare	3	Moderate	Low	Contractor	
DD4	Detailed Design	Civil	Construction	Working plant (fixed or mobile)/ Physical harm from moving machinery	Physical harm from moving machinery / Fatality	2	Unlikely	4	Major	Medium	Be aware of any rules put in place by the site operator for visitors (warning signs, etc). Visitors to ensure that they are accompanied at all times while on site and that they adhere to any rules that the site operator has in place.	1	Rare	4	Major	Low	Contractor	
DD5	Detailed Design	Civil	Construction	Trench collapse / asphyxiation, crushed	Asphyxiation, crushed / fatality	2	Unlikely	4	Major	Medium	Ensure WH&S requirements for trenching / shoring are placed on the construction drawings. Minimise trench depth. Backfill to authorities requirment. Ensure contractor installs cut off drains and berms adjacent to trench to prevent storm water runoff entering the trench. Undertake works in accordance with Geotechnical report recommendations.	1	Rare	4	Major	Low	Contractor	
DD6	Detailed Design	Civil	Construction	Open trench left opened during night.	Falling from heights / Major injury	1	Rare	5	Catostrophic	Medium	Trench is backfilled each day before contractor leaves site. Contractor provides man-proof fencing around open trench areas with adequate warning of deep excavation as well as covering open trench with boards.	1	Rare	4	Major	Low	Contractor	
DD7	Detailed Design	Civil	Maintenance	Maintenance of Batters / batter is too steep to safely maintain (mower may roll) in adjacent parks	Driver of vehicle is injured (i.e. slasher rolls) / Physical injury or death and property damage.	2	Unlikely	3	Moderate	Medium	Batter complies with local government minimum standards. Batter at 1 in 6 minimum mowable. Batter steeper than 1 in 6 to be planted or landscaped. Landscaping to be low maintenance variety where possible. Maintenance Entity shall undertake works in accordance with their site specific safe work method statement.	1	Rare	3	Moderate	Low	Authority / Property Owners	
DD8	Detailed Design	Civil	Construction	Works adjacent to existing services (electricity, optic fibre, water, etc) / Damage to services, electrocution.	Existing service is struck / property damage, private property without services, physical injury or death (i.e. electrocution).	3	Possible	3	Moderate	High	Design considers clearances to mains as required by asset holders and has been approved by asset holders. The Principal Contractor shall located all existing services and ensure they are marked and protected appropriately onsite in accordance with requirements of the respective asset holder and ensure safe work method statements are undertaken and approved by any asset holders as required.	1	Rare	3	Moderate	Low	Contractor	
DD9	Detailed Design	Civil	Construction	Unstable stockpiles (including working next to dam) / Physical harm caused by moving piles of aggregate, etc	As denoted / Major injury	2	Unlikely	3	Moderate	Medium	Warning signs. Site rules. Visitors to remain within the site's designated areas at all times and to refrain from climbing onto stockpiles. Contractor to monitor water levels and sins of failure in adjacent and/or upstream dams.	1	Rare	3	Moderate	Low	Contractor	
DD10	Detailed Design	Civil	Construction	Stormwater Runoff / Sediment and Erosion of earthwork areas	Sedimentation of stormwater infrastructure and creeks as well as erosion of batters / environmental harm, conveyance of stormwater infrastructure compromised	3	Possible	2	Minor	Medium	Principal Contractor shall implement and maintain erosion and sediment control in accordance with current guidelines prior to, during and after construction.	1	Rare	1	Insignificant	Low	Contractor	
DD11	Detailed Design	Civil	Construction	Raw sewage / Construction personnel in contact with raw sewage	Infection / Major injury	2	Unlikely	3	Moderate	Medium	Ensure live sewer connection works are accurately planned and performed in accordance with relevant standards. Ensure sufficient time is available to perform "live connection" works. Visitors to remain outside of designated live works area.	1	Rare	3	Moderate	Low	Contractor	
Retaining Walls																		
DD13	Detailed Design	Civil	Construction	Height and fall hazards during construction / comissioning involving Retaining walls, alignment	Injury falling from a height	2	Unlikely	3	Moderate	Medium	Temporary / permanent fencing or barriers to be installed at the top of the retaining wall. Provide fencing (at heights) during design process.	1	Rare	3	Moderate	Low	Contractor	
DD14	Detailed Design	Civil	Operations	Height / Fall hazards involving Retaining walls	Injury falling from a height	2	Unlikely	3	Moderate	Medium	Temporary / permanent fencing or barriers to be installed at the top of the retaining wall.	1	Rare	3	Moderate	Low	Property Owner	
DD15	Detailed Design	Civil	Construction	Batter and adjacent retaining wall Stability / Batters collapse	Batter or retaining wall fails / death	2	Unlikely	3	Moderate	Medium	Design and geotechnical reporting has been undertaken in accordance with Council requirements. The constrictor shall implement a safe work method statement, design, undertake works with the required level of supervision from a geotechnical engineer and provide certifications as required.	1	Rare	3	Moderate	Low	Contractor	
Drainage																		
DD16	Detailed Design	Civil	Maintenance	Stormwater Runoff in overland flow path	Drowning / Death	2	Unlikely	3	Moderate	Medium	Overland flow calculation is accordance with authority requirement. Storm water infrastructure to be maintained by Authority to sure the designed storm water system operate as per design intent.	1	Rare	2	Minor	Low	Authority	

Issue	Description	DR	CH	VE	Date
02	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: SAFETY IN DESIGN
SHEET 1

Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone / Stage	Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD		CV	DRG	0010	02

100mm on Original

Date Plotted: 28 Jul 2023 - 10:54am File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0010-SID.dwg V1

SAFETY IN DESIGN REGISTER

PROJECT	Eynesbury Township Pty Ltd
LOCATION	Eynesbury Township
PROJECT NUMBER	10029435
PROJECT DESCRIPTION	xxxx

Risk ID No.	Design Phase	Discipline	Phase of Project	Hazard/ Aspect	Risks/ Opportunities/ Impacts	Risk					Proposed Controls (to mitigate or avoid - include reference to any standards or code used)	Mitigated Risk / Opportunity					Likely Risk Entity	Comment
						Probability/ Likelihood		Consequence/ Benefit/ Impact		Level		Probability/ Likelihood		Consequence/ Benefit/ Impact		Level		
DD17	Detailed Design	Civil	Operations	Trip / falls hazards related to grated pits	Injury falling from hazard	2	Possible	2	Minor	Low	Drainage grates provided in accordance with manufacturers standards and authorities. Drainage grates bike and pedestrian friendly.	1	Possible	2	Minor	Low	Authority	
DD18	Detailed Design	Civil	Operations	Potential pit failure design that is non standard	Potential risk of vehicle or maintenance crew accident	1	Rare	3	Moderate	Low	Pits are constructed in accordance to Authority standards. Any not standard pit to be designed by qualitied structural engineer.	1	Rare	2	Minor	Low	Authority	
DD19	Detailed Design	Civil	Operations	Height / Fall hazards involving culvert endwall / headwalls / pipe	Potential risk of an accident	2	Unlikely	3	Moderate	Medium	Temporary fencing or barriers/guardrails to be installed around culverts / headwalls in accordance with authority standards, and relevant design principles. Allow for fencing in Design Process.	1	Rare	3	Moderate	Low	Authority	
DD20	Detailed Design	Civil	Operations	Hazard for children playing inside / around Culvert endwall / headwalls outlets	Potential risk of an accident	1	Rare	3	Moderate	Low	Provide grating in accordance with manufacturers standards and authorities.	1	Rare	3	Moderate	Low	Authority	
DD21	Detailed Design	Civil	Maintenance	Unsafe access for maintenace to access pits	Potential risk to maintenance crew	1	Rare	2	Minor	Low	Provide safe access arrangements and working conditions for maintenance crew, and pits design in accordance with relevant authority standards and design principles. Where possible design pit in location for easy access and outside of permanent water bodies. Locations of pits to be agreed with relevant authorities.	1	Rare	3	Moderate	Low	Authority	
DD22	Detailed Design	Civil	Maintenance	Unsafe access for maintenance to drains / culverts	Potential risk and accident involving maintenance crew	1	Rare	2	Minor	Low	Provide safe access arrangements and working conditions for maintenance crew, and pits design location in accordance with relevant authority standards and design principles.	1	Rare	3	Moderate	Low	Authority	
Sewer																		
DD23	Detailed Design	Civil	Maintenance	Unsafe access for maintenance to manholes	Potential risk and accident involving maintenance crew	2	Unlikely	3	Moderate	Medium	Provide safe access arrangements and working conditions for maintenance crew, and manhole locations in compliance with authority standards and design principles. Where possible design manhole in location for easy access.	1	Rare	3	Moderate	Low	Authority	
DD24	Detailed Design	Civil	Maintenance	Deep Sewer propety connection	Potential trench collapse during deep plumbing connection	2	Unlikely	3	Moderate	Medium	All propety connections are designed to approximate 1.3m maximum deep which allowed construction tollalance to reach maximum of 1.5m safe trench depth.	1	Rare	3	Moderate	Low	Authority	
DD25	Detailed Design	Civil	Construction	Sewer reticulation main	Potential trench collapse during construction with deep sewer	2	Unlikely	4	Major	Medium	All sewer reticulation mains are designed to main depth whenever possible. Cotractor must carry out safe trench construction method when construsting deep sewer as per industry safety requirment. Trenches must be backfilled to authorities backfiall specifications.	1	Rare	2	Minor	Low	Contractor	
Electricity																		
DD26	Detailed Design	Civil	Operations	Unsafe location of assets within clear zones	Potential risk of an accident	2	Unlikely	2	Minor	Low	Pits to be below ground and where above ground, sufficient offset from clear zones. Temporary barrier protection to be installed.Subconsultancy design has appropriate accreditations and in accordance with authority standards.	1	Rare	3	Moderate	Low	Authority	
DD27	Detailed Design	Civil	Construction	Existing services strike / electrocution / drowning	Electrocution / drowning / fatality	2	Unlikely	4	Major	Medium	Ensure all existing services are accurately shown on construction drawings. Ensure separation distances between services are in accordance with relevant standards. Contractor to verify existing survives location on site prior construction start	1	Rare	3	Moderate	Low	Contractor	
NBN																		
DD28	Detailed Design	Civil	Operations	Unsafe location of NBN design assests	Potential risk of an accident / trap hazard	2	Unlikely	2	Minor	Low	Pits to be located outside of traffic able area and located out of footpath. Authority should have traffic management plan in place to maintain asset if they are located within traffic able area. Subconsultancy design has appropriate accreditations and in accordance with authority standards.	1	Rare	3	Moderate	Low	Authority	
Water																		
DD29	Detailed Design	Civil	Operations	Unsafe location of Water assests. Ie. Within road carriageway	Potential risk of an accident during maintenance	2	Unlikely	3	Moderate	Medium	Valves & Hydrants are located outside of traffic able area to provide safe access during operations / maintenance. Authority should have traffic management plan in place to operate valves / hydrants if they are located within traffic able area . Water pits designed in accordance with authority standards.	1	Rare	3	Moderate	Low	Contractor	
Gas																		
DD30	Detailed Design	Civil	Maintenance	Unsafe location / cover of Gas and clearacne to other services	Potential risk of damage to gas main or other services	2	Unlikely	4	Major	Medium	Gas main to be designed and installed accordance to authority standards. Only approved contractor to carry out manintence works and must identify exsiting services surrounding the gas main pror any excavation.	1	Rare	4	Major	Low	Authority	

Issue	Description	DR	CH	VE	Date
02	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: SAFETY IN DESIGN
SHEET 2

Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0011	02

100mm on Original

Date Plotted: 10 Jul 2023 - 02:48pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0010-SID.dwg V1

Likelihood	Consequence				
	1 **Insignificant** << $1,000 Damage	2 **Minor** << $10,000 Damage	3 **Moderate** << $100,000 Damage	4 **Major** << $1,000,000 Damage	5 **Catastrophic** >> $1,000,000 Damage
1 **Rare - (0.001%)**	**1 (Low)**	**2 (Low)**	**3 (Low)**	**4 (Low)**	**5 (Medium)**
2 **Unlikely - (0.1%)**	**2 (Low)**	**4 (Low)**	**6 (Medium)**	**8 (Medium)**	**10 (High)**
3 **Possible - (1%)**	**3 (Low)**	**6 (Medium)**	**9 (High)**	**12 (High)**	**15 (High)**
4 **Likely - (10%)**	**4 (Low)**	**8 (Medium)**	**12 (High)**	**16 (Extreme)**	**20 (Extreme)**
5 **Almost Certain - (90%)**	**5 (Medium)**	**10 (High)**	**15 (High)**	**20 (Extreme)**	**25 (Extreme)**

SAFETY AND ENVIRONMENTAL HAZARD IDENTIFICATION/RISK ASSESSMENT

LIKELIHOOD		
1	Rare	The event could occur, but it is rare / only in exceptional circumstances.
2	Unlikely	The event is unlikely to occur (though it could occur during similar work activities).
3	Possible	The event is possible to / might occur during some projects.
4	Likely	The event will probably / is likely to occur at least once during most projects.
5	Almost Certain	The event is a common occurrence on all projects.

Consequence		
1.000	Insignificant	The event could result in injury or illness not resulting in a lost work day.
2.000	Minor	The event could result in injury or illness not resulting in one or more lost work days.
3.000	Moderate	The event could result in partial disability, injuries or illness that may require hospitalisation.
4.000	Major	The event could result in permanent total disability.
5.000	Catostrophic	The event could result in fatality.

PROJECT RISK RATINGS	
1 - 4	Low
5 - 8	Medium
9 - 15	High
16-25	Extreme

Issue	Description	DR	CH	VE	Date
02	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

SAFETY IN DESIGN
SHEET 3

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0012	02

100mm on Original

Date Plotted: 10 Jul 2023 - 02:47pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0010-SID.dwg V1

REFER TO DRG-0101 FOR CONTINUATION

FUTURE STAGE 22B

FUTURE STAGE 26

EXISTING STAGE 18C

EXISTING STAGE 18B

STAGE 22A

GOROKE STREET

CHERRYPOOL CRESCENT

KARNAK LANE

OZENKADNOOK WAY

MOUNT MARY ROAD

MOYREISK CLOSE

MURTOA CRESCENT

GYMBOWEN AVENUE

ZUMSTEINS WALK

KARNAK LANE

SUPERLOT S193

SUPERLOT S194

SUPERLOT S195

RESERVE NO.145

RESERVE NO. 146

RESERVE NO.147

RESERVE NO.148

RESERVE NO.149

RESERVE NO. 114

RESERVE NO. 115

RESERVE NO. 112

FUTURE NATURE RESERVE

STONE PITCHED RETAINING WALL
REFER LANDSCAPE ARCHITECTS
DRAWINGS FOR DETAILS

LEGEND

- EXISTING SURFACE CONTOURS
- PROPOSED SURFACE CONTOURS
- PROPOSED KERB & CHANNEL
- STAGE BOUNDARY
- PROPOSED RIDGE LINE
- PROPOSED RETAINING WALL
- MUNICIPAL BOUNDARY
- EXISTING TREES TO BE RETAINED
- EXISTING TREES TO BE REMOVED

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. CUT-FILL HATCH SHOWN FROM EXISTING SURFACE TO FINISHED SURFACE.

CUT FILL DEPTH RANGE

Lower_value		Upper_value	Colour
-1.4	to	-1.3	m
-1.3	to	-1.2	m
-1.2	to	-1.1	m
-1.1	to	-1	m
-1	to	-.9	m
-.9	to	-.8	m
-.8	to	-.7	m
-.7	to	-.6	m
-.6	to	-.5	m
-.5	to	-.4	m
-.4	to	-.3	m
-.3	to	-.2	m
-.2	to	-.1	m
-.1	to	0.0	m
0.0	to	.1	m
.1	to	.2	m
.2	to	.3	m
.3	to	.4	m
.4	to	.5	m
.5	to	.6	m
.6	to	.7	m
.7	to	.8	m
.8	to	.9	m
.9	to	1	m
1	to	1.1	m
1.1	to	1.2	m
1.2	to	1.3	m
1.3	to	1.4	m

Issue	Description	DR	CH	VE	Date
03	RESPONSE TO COUNCIL RFI	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

EARTHWORKS LAYOUT PLAN
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0100	03

100mm on Original

Date Plotted: 17 Jul 2023 - 04:50pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0100-Earthworks.dwg V1

INSET - A

REFER INSET - A

FUTURE STAGE 22E

FUTURE WETLAND RESERVE

FUTURE STAGE 22B

STAGE 22A

EXISTING STAGE 18D

MOUNT MARY ROAD

CHERRYPOOL CRESCENT

GOROKE STREET

KARNAK LANE

BUNGALALLY WALK

CALLAWADDA DRIVE

EXTENDED DRIVEWAY

BALQUHIDDER

SUPERLOT S196

RESERVE NO.151

RESERVE NO. 117

RESERVE NO. 114

SUPERLOT S193

REFER TO DRG-0100 FOR CONTINUATION

LEGEND

- EXISTING SURFACE CONTOURS
- PROPOSED SURFACE CONTOURS
- PROPOSED KERB & CHANNEL
- STAGE BOUNDARY
- PROPOSED RIDGE LINE
- EXISTING TREES TO BE RETAINED
- EXISTING TREES TO BE REMOVED

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. CUT-FILL HATCH SHOWN FROM EXISTING SURFACE TO FINISHED SURFACE

CUT FILL DEPTH RANGE

Lower_value		Upper_value	Colour
-1.4	to	-1.3	m
-1.3	to	-1.2	m
-1.2	to	-1.1	m
-1.1	to	-1	m
-1	to	-.9	m
-.9	to	-.8	m
-.8	to	-.7	m
-.7	to	-.6	m
-.6	to	-.5	m
-.5	to	-.4	m
-.4	to	-.3	m
-.3	to	-.2	m
-.2	to	-.1	m
-.1	to	0.0	m
0.0	to	.1	m
.1	to	.2	m
.2	to	.3	m
.3	to	.4	m
.4	to	.5	m
.5	to	.6	m
.6	to	.7	m
.7	to	.8	m
.8	to	.9	m
.9	to	1	m
1	to	1.1	m
1.1	to	1.2	m
1.2	to	1.3	m
1.3	to	1.4	m

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

100mm on Original

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

EARTHWORKS LAYOUT PLAN
SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0101	04

Date Plotted: 17 Jul 2023 - 04:42pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0100-Earthworks.dwg V1

REFER TO DRAWING DRG-0201 FOR CONTINUATION

FUTURE STAGE 22B

FUTURE STAGE 26

STAGE 22A

EXISTING STAGE 18C

GOROKE STREET (MC09)

CHERRYPOOL CRESCENT (MC05)

OZENKADNOOK WAY (MC07)

KARNAK LANE (MC12)

KARNAK LANE (MC11)

GYMBOWEN AVENUE (MC04)

ZUMSTEINS WALK

MOUNT MARY ROAD

MOYREISK CLOSE

MURTOA CRESCENT

RESERVE NO.145

RESERVE NO. 146

RESERVE NO.147

RESERVE NO.148

RESERVE NO.149

RESERVE NO. 115

RESERVE NO. 112

SUPERLOT S193

SUPERLOT S194

SUPERLOT S195

LEGEND

- PROPOSED KERB & CHANNEL
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- STAGE BOUNDARY

NOTE:

FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.

CONTROL LINE SETOUT - GYMBOWEN AVENUE (MC04)

PT	CHAINAGE	EASTING	NORTHING	BEARING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	-6.600	283229.499	5814603.124	274e01'47.25"			
IP 2	0.000	283222.916	5814603.588				
TC	29.566	283193.746	5814608.412	279e23'24.44"			
IP 3	41.230	283182.024	5814610.350		R = 50.000	23.329	26e44'00.56"
CT	52.895	283172.428	5814617.355	306e07'25.00"			
TC	551.150	282769.964	5814911.090	306e07'25.00"			
IP 4	563.757	282759.559	5814918.684		R = -50.000	25.214	28e53'35.63"
CT	576.364	282746.780	5814920.305	277e13'49.37"			
IP 5	660.462	282663.350	5814930.890	277e13'49.37"			

CONTROL LINE SETOUT - CHERRYPOOL CRESCENT (MC05)

PT	CHAINAGE	EASTING	NORTHING	BEARING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	282969.585	5814765.398	36e07'25.00"			
TC	41.296	282993.930	5814798.754	36e07'25.00"			
IP 2	49.698	282999.017	5814805.724		R = -30.000	16.804	32e05'37.73"
CT	58.100	282999.624	5814814.332	4e01'47.27"			
TC	170.285	283007.508	5814926.240	4e01'47.27"			
IP 3	180.052	283008.546	5814941.006		R = 10.000	19.533	111e55'05.57"
IP 4	189.819	283021.858	5814934.529				
IP 5	209.774	283040.021	5814925.691		R = -105.000	39.911	21e46'42.20"
IP 6	229.730	283060.167	5814924.222				
TC	315.083	283145.295	5814918.016	94e10'10.65"			
IP 7	322.925	283155.244	5814917.291		R = 10.000	15.684	89e51'36.65"
CT	330.767	283154.543	5814907.340	184e01'47.30"			
TC	524.996	283140.893	5814713.591	184e01'47.30"			
IP 8	533.398	283140.287	5814704.983		R = 30.000	16.804	32e05'37.70"
CT	541.800	283135.200	5814698.013	216e07'25.00"			
IP 9	585.005	283109.729	5814663.115	216e07'25.00"			

CONTROL LINE SETOUT - OZENKADNOOK WAY (MC07)

PT	CHAINAGE	EASTING	NORTHING	BEARING
IP 1	0.000	283145.462	5814778.445	94e01'47.25"
IP 2	44.850	283190.201	5814775.293	94e01'47.25"

CONTROL LINE SETOUT - GOROKE STREET (MC09)

PT	CHAINAGE	EASTING	NORTHING	BEARING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283041.636	5814712.812	36e07'25.00"			
TC	37.779	283063.908	5814743.328	36e07'25.00"			
IP 2	46.181	283068.995	5814750.298		R = -30.000	16.804	32e05'37.66"
CT	54.584	283069.602	5814758.906	4e01'47.34"			
IP 3	218.777	283081.140	5814922.693	4e01'47.34"			

CONTROL LINE SETOUT - KARNAK LANE (MC11)

PT	CHAINAGE	EASTING	NORTHING	BEARING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283139.075	5814705.212	107e06'42.75"			
IP 2	8.176	283146.889	5814702.807				
IP 3	10.153	283148.789	5814702.222		R = 15.000	3.953	15e05'56.88"
IP 4	12.129	283150.471	5814701.162				
TC	52.519	283184.645	5814679.633	122e12'39.62"			
IP 5	54.978	283186.768	5814678.295		R = -10.000	4.919	28e10'52.37"
CT	57.437	283189.272	5814678.118	94e01'47.25"			
IP 6	84.535	283216.303	5814676.214	94e01'47.25"			

CONTROL LINE SETOUT - KARNAK LANE (MC12)

PT	CHAINAGE	EASTING	NORTHING	BEARING
IP 1	0.000	283180.705	5814682.114	32e18'41.94"
IP 2	6.172	283184.005	5814687.331	
IP 3	202.353	283197.791	5814883.026	4e01'47.25"

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

100mm on Original

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON


Title

SETOUT PLAN
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0200	04

Date Plotted: 27 Jul 2023 - 03:14pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0200-Setout.dwg V1



REFER TO DRAWING DRG-0200 FOR CONTINUATION

LEGEND

- PROPOSED KERB & CHANNEL
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- STAGE BOUNDARY

NOTE:

FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.

CONTROL LINE SETOUT - CHERRYPOOL CRESCENT (MC05)

PT	CHAINAGE	EASTING	NORTHING	BEARING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	282969.585	5814765.398	36é07'25.00"			
TC	41.296	282993.930	5814798.754	36é07'25.00"			
IP 2	49.698	282999.017	5814805.724		R = -30.000	16.804	32é05'37.73"
CT	58.100	282999.624	5814814.332	4é01'47.27"			
TC	170.285	283007.508	5814926.240	4é01'47.27"			
IP 3	180.052	283008.548	5814941.006		R = 10.000	19.533	111é55'05.57"
IP 4	189.819	283021.858	5814934.529				
IP 5	209.774	283040.021	5814925.691		R = -105.000	39.911	21é46'42.20"
IP 6	229.730	283060.167	5814924.222				
TC	315.083	283145.295	5814918.016	94é10'10.65"			
IP 7	322.925	283155.244	5814917.291		R = 10.000	15.684	89é51'36.65"
CT	330.767	283154.543	5814907.340	184é01'47.30"			
TC	524.996	283140.893	5814713.591	184é01'47.30"			
IP 8	533.398	283140.287	5814704.983		R = 30.000	16.804	32é05'37.70"
CT	541.800	283135.200	5814698.013	216é07'25.00"			
IP 9	585.005	283109.729	5814663.115	216é07'25.00"			

CONTROL LINE SETOUT - OZENKADNOOK WAY (MC07)

PT	CHAINAGE	EASTING	NORTHING	BEARING
IP 1	0.000	283145.462	5814778.445	94é01'47.25"
IP 2	44.850	283190.201	5814775.293	94é01'47.25"

CONTROL LINE SETOUT - GOROKE STREET (MC09)

PT	CHAINAGE	EASTING	NORTHING	BEARING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283041.636	5814712.812	36é07'25.00"			
TC	37.779	283063.908	5814743.328	36é07'25.00"			
IP 2	46.181	283068.995	5814750.298		R = -30.000	16.804	32é05'37.66"
CT	54.584	283069.602	5814758.906	4é01'47.34"			
IP 3	218.777	283081.140	5814922.693	4é01'47.34"			

CONTROL LINE SETOUT - KARNAK LANE (MC10)

PT	CHAINAGE	EASTING	NORTHING	BEARING
IP 1	0.000	283153.052	5814886.178	94é01'47.25"
IP 2	77.850	283230.710	5814880.707	94é01'47.25"

CONTROL LINE SETOUT - KARNAK LANE (MC12)

PT	CHAINAGE	EASTING	NORTHING	BEARING
IP 1	0.000	283180.705	5814682.114	32é18'41.94"
IP 2	6.172	283184.005	5814687.331	
IP 3	202.353	283197.791	5814883.026	4é01'47.25"

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

SETOUT PLAN
SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0201	04

100mm on Original

REFER TO DRAWING-0801 FOR CONTINUATION

FUTURE STAGE 22B
22073

STAGE 22A

FUTURE STAGE 26

EXISTING STAGE 18C

EXISTING STAGE 18B

RESERVE NO.145

RESERVE NO. 146

RESERVE NO.147

RESERVE NO.149

RESERVE NO. 114

RESERVE NO. 115

RESERVE NO. 112

GOROKE STREET

CHERRYPOOL CRESCENT

OZENKADNOOK WAY

KARNAK LANE

KARNAK LANE

GYMBOWEN AVENUE

FUTURE NATURE RESERVE

FUTURE NATURE RESERVE

ZUMSTEINS WALK
RESERVE NO.148

MOUNT MARY ROAD

MURTOA CRESCENT

MOYREISK CLOSE

SUPERLOT S193

SUPERLOT S194

SUPERLOT S195

PROPOSED ELECTRICAL KIOSK TO HAVE 1.8m HIGH TIMBER FENCE WITH RAILING FACING INWARDS

CONSTRUCT TEMPORARY GRAVEL TURN AROUND (R=10.5m), "NO ROAD" SIGN & EDGE STRIP IF FUTURE STAGE WORKS HAVE NOT COMMENCED

STONE PITCHED RETAINING WALL AND SAFETY BARRIER. REFER LANDSCAPE ARCHITECT DRAWING FRO DETAILS

PRINCIPAL SURVEYOR TO INSTALL PSM

RAISED PAVEMENT. REFER DRAWING DRG-0280 FOR DETAIL

PROVIDE ENDPIPE WITH BLOCK OUT FOR FUTURE CONNECTION MINIMUM 1m BEYOND STAGE BOUNDARY

PRINCIPAL SURVEYOR TO INSTALL PSM

ELECTRICAL AND COMMS CROSSING OVER DRAIN

PROVIDE ENDPIPE WITH BLOCK OUT FOR FUTURE CONNECTION MINIMUM 1m BEYOND STAGE BOUNDARY

CONTRACTOR TO MAKE EVERY EFFORT TO ENSURE TREES #170, #171, #173A AND #173B ARE RETAINED ONSITE. LOCALISED BATTER STEEPENING AS REQUIRED AROUND TRUNK ZONE.

SUBSURFACE DRAIN TO BE INSTALLED UNDER INVERT CHANNELS FOR ALL PARKING BAYS ALONG GYMBOWEN AVENUE

CONNECT TO MOUNT MARY ROAD STAGE 3 DRAINAGE PIPE

REMOVE EXISTING CONCRETE EDGE STRIP, "NO ROAD" SIGN AND MATCH NEATLY TO EXISTING CONSTRUCTION

CONNECT TO MOUNT MARY ROAD WATER AND GAS MAIN

REFER TO MOUNT MARY ROAD STAGE 3 DESIGN PACKAGES FOR SUPERLOT S193 GAS, WATER AND DRAINAGE CONNECTIONS

PALING FENCE TO BE INSTALLED ALONG RESERVE BOUNDARY

BOLLARDS TO BE INSTALLED BY LANDSCAPE CONSTRACTOR AT 1.5m SPACING TO COUNCIL SATISFACTION

REFER TO LANDSCAPE PACKAGE FOR FOOTPATH ALIGNMENT DETAILS

PALING FENCE TO BE INSTALLED ALONG RESERVE BOUNDARY

REFER TO MOUNT MARY ROAD STAGE 3 DESIGN PACKAGES FOR SUPERLOT S194 FOR GAS, WATER AND DRAINAGE CONNECTIONS

PROVIDE CONNECTION TO MOUNT MARY ROAD STAGE 3 DRAINAGE PIPE

PATH CONNECTION TO MOUNT MARY ROAD FOOTPATH

BOLLARDS TO BE INSTALLED BY LANDSCAPE CONSTRACTOR AT 1.5m SPACING TO COUNCIL SATISFACTION

REFER TO GAS AND WATER DESIGN PACKAGES FOR CONNECTION TO MOUNT MARY ROAD GAS AND WATER SERVICES.

ARIELTON CITY COUNCIL / WYNDHAM CITY COUNCIL

MELTON CITY COUNCIL / WYNDHAM CITY COUNCIL

ROAD LAYOUT TABLE

ROAD NAME	ROAD CLASSIFICATION	RESERVE WIDTH (m)	ROAD WIDTH			KERB TYPE		VERGE WIDTH (m)	
			LIP TO LIP	INV TO INV	BACK TO BACK	NTH/WEST	STH/EAST	NTH/WEST	STH/EAST
GYMBOWEN AVENUE	CS1	20.00	10.70m	11.60m	11.90m	B3/IC	B3/IC	4.20	4.20
CHERRYPOOL CRESCENT	AS1	16.00	6.40m	7.30m	7.60m	B2	B2	4.50	4.20
GOROKE STREET	AS1	16.00	6.40m	7.30m	7.60m	B2	B2	4.20	4.50
OZENKADNOOK WAY	AL	10.00	6.00m	-	-	-	-	2.00	2.00
KARNAK LANE (LOT 22028-22110)	AL	10.00	6.00m	-	-	-	-	2.00	2.00
KARNAK LANE (SUPERLOT S195 & S196)	AL	8.00	6.00m	-	-	-	-	1.00	1.00
ZUMSTEINS WALK / BUNGALALLY WALK	WALK WAY	5.00	-	-	-	-	-	-	-

SERVICES OFFSET TABLE

ROAD NAME	GAS		WATER		RECYCLED WATER		ELECTRICITY		COMMUNICATIONS	
	SIDE	OFFSET (m)	SIDE	OFFSET (m)	SIDE	OFFSET (m)	SIDE	OFFSET (m)	SIDE	OFFSET (m)
GYMBOWEN AVENUE	SOUTH	2.10	SOUTH	3.50	SOUTH	2.70	NORTH	2.60	NORTH	1.80
CHERRYPOOL CRESCENT	WEST	2.10	WEST	3.10	WEST	2.60	EAST	2.60	EAST	1.80
GOROKE STREET	EAST	2.10	EAST	3.10	EAST	2.60	WEST	2.60	WEST	1.80
ZUMSTEINS WALK	NORTH	1.80	NORTH	2.80	NORTH	2.30	NORTH	3.80	NORTH	3.30
BUNGALALLY WALK	SOUTH	1.80	SOUTH	2.80	SOUTH	2.30	SOUTH	3.80	SOUTH	3.30
KARNAK LANE (S195 & S196)	-	-	-	-	-	-	NORTH	0.50	-	-
KARNAK LANE (LOTS 22028 - 22110)	-	-	-	-	-	-	EAST	1.00	-	-

LEGEND

- PROPOSED STAGE BOUNDARY
- 5.0 — PROPOSED DESIGN CONTOURS
- PROPOSED KERB & CHANNEL
- FALL OF ALLOTMENT
- DIRECTION OF OVERLAND FLOW
- A-1 — PROPOSED STORMWATER DRAINAGE
- PROPOSED PIT LABEL
- S — PROPOSED SEWERAGE RETICULATION
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- PROPOSED DRAINAGE INLET
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- PROPOSED ROAD PAVEMENT
- GWR — PROPOSED GAS / CLASS A / POTABLE WATER HOUSE CONNECTION
- BOLLARD
- FS98.86 — FINISHED RIDGE LEVEL
- FS97.14 — FINISHED SURFACE LEVEL
- 93.750 — EXISTING SURFACE LEVEL
- PROPOSED RIDGE LINE
- PROPOSED RETAINING WALL
- CUT (> 0.3m)
- FILL (> 0.3m)
- EXISTING STAGE BOUNDARY
- 5.0 — EXISTING SURFACE CONTOURS
- EXISTING STORMWATER DRAINAGE
- s — EXISTING SEWER RETICULATION
- w — EXISTING WATER RETICULATION
- r — EXISTING RECYCLED WATER RETICULATION
- e — EXISTING ELECTRICITY UNDER GROUND
- c — EXISTING COMMUNICATIONS
- g — EXISTING GAS RETICULATION
- EXISTING SWALE
- FUTSWD — FUTURE STORMWATER DRAINAGE
- FUTS — FUTURE SEWER RETICULATION
- FUTW — FUTURE WATER RETICULATION
- FUTR — FUTURE RECYCLED WATER RETICULATION
- FUTC — FUTURE COMMUNICATIONS
- FUTE — FUTURE ELECTRICAL UNDER GROUND
- FUTG — FUTURE GAS RETICULATION
- EXISTING TREES TO BE RETAINED
- EXISTING TREES TO BE REMOVED
- TEMPORARY FENCE
- TEMPORARY SWALE
- MUNICIPAL BOUNDARY
- PALING FENCE

NOTES:

1. FUTURE SUPERLOT BOUNDARIES SHOWN FOR SERVICE LOCATIONS ONLY. TO BE CONFIRMED UNDER SEPARATE CONTRACT.
2. STAGE 22A TO BE CONSTRUCTED CONCURRENTLY WITH STAGE 22B, D, E & MMR03.
3. UNLESS NOTED OTHERWISE, ALL SERVICES WILL CROSS OVER DRAINAGE PIPE EXCEPT SEWER PIPE. REFER TO RELEVANT UTILITYDESIGN PACKAGES FOR DETAILS.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

ROADWORKS AND DRAINAGE LAYOUT PLAN
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0220	04

100mm on Original

Date Plotted: 27 Jul 2023 - 03:28pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0220-Roadworks.dwg V1

INSET - A

PEDESTRAIN SAFETY FENCE INCL. REQUIRED GATE/S, TO THE FULL PERIMETER OF THE TEMPORARY OUTLET CHANNEL

EXISTING STAGE 18D

REFER STAGE 22D DESIGN PACKAGE FOR PROPOSED WATERWAY FUNCTIONAL PLAN AND DESIGN

TEMPORARY OUTLET CHANNEL TO BE GRADED THROUGH FUTURE SEDIMENT POND, WETLAND AND WATERWAY @ 1in500. BATTERS AND BASE TO BE HYDROSEEDED

FUTURE STAGE 22E

FUTURE WETLAND RESERVE

REFER STAGE 22E DESIGN PACKAGE FOR PROPOSED WETLAND FUNCTIONAL PLAN AND DESIGN

FUTURE 4.0m WIDE SHARED PATH TO BE CONSTRUCTED AS PART OF THE FUTURE WETLAND PACKAGE. EXACT ALIGNMNET IS SUBJECT TO FINAL LANDSCAPE DESIGN

REFER TO GAS AND WATER DESIGN PACKAGES FOR CONNECTION TO MOUNT MARY ROAD GAS AND WATER SERVICES.

8m RADIUS PIPE BANDAGE JOINT. REFER TO MELBOURNE WATER STANDARD DRAWING 7251/08/420 FOR JOINT DETAIL

CONSTRUCT TEMPORARY GRAVEL TURN AROUND (R=10.5m), "NO ROAD" SIGN & EDGE STRIP IF FUTURE STAGE WORKS HAVE NOT COMMENCED

BUNGALALLY WALK

PATH CONNECTION TO MOUNT MARY ROAD FOOTPATH

MOUNT MARY ROAD

CHERRYPOOL CRESCENT

GOROKE STREET

KARNAK LANE

CALLAWADDA DRIVE

EXTENDED DRIVEWAY

BALQUHIDDER

SUPERLOT S196

RESERVE NO.151

SUPERLOT S193

RESERVE NO. 117

RESERVE NO. 114

DRAINAGE CROSSING UNDER SEWER. REFER SEWER DESIGN PACKAGE FOR DETAIL

BOLLARDS TO BE INSTALLED BY LANDSCAPE CONSTRACTOR AT 1.5m SPACING TO COUNCIL SATISFACTION

PROVIDE CONNECTION TO MOUNT MARY ROAD STAGE 3 DRAINAGE PIPE

REFER TO MOUNT MARY ROAD STAGE 3 DESIGN PACKAGES FOR SUPERLOT S197 GAS, WATER AND DRAINAGE CONNECTIONS

CONSTRUCT TEMPORARY GRAVEL TURN AROUND (R=10.5m), "NO ROAD" SIGN & EDGE STRIP IF FUTURE STAGE WORKS HAVE NOT COMMENCED

STAGE 22A

FUTURE STAGE 22B

EXISTING STAGE 18D

REFER INSET - A

REFER TO DRAWING-0221 FOR CONTINUATION

LEGEND

- PROPOSED STAGE BOUNDARY
- PROPOSED DESIGN CONTOURS
- PROPOSED KERB & CHANNEL
- FALL OF ALLOTMENT
- DIRECTION OF OVERLAND FLOW
- PROPOSED STORMWATER DRAINAGE
- PROPOSED PIT LABEL
- PROPOSED SEWERAGE RETICULATION
- PROPOSED WATER RETICULATION
- PROPOSED RECYCLED WATER RETICULATION
- PROPOSED ELECTRICITY UNDER GROUND
- PROPOSED COMMUNICATIONS
- PROPOSED GAS RETICULATION
- PROPOSED DRAINAGE INLET
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- PROPOSED ROAD PAVEMENT
- PROPOSED GAS / CLASS A / POTABLE WATER HOUSE CONNECTION
- BOLLARD
- FINISHED RIDGE LEVEL
- FINISHED SURFACE LEVEL
- EXISTING SURFACE LEVEL
- PROPOSED RIDGE LINE
- PROPOSED RETAINING WALL
- CUT (> 0.3m)
- FILL (> 0.3m)
- EXISTING STAGE BOUNDARY
- EXISTING SURFACE CONTOURS
- EXISTING STORMWATER DRAINAGE
- EXISTING SEWER RETICULATION
- EXISTING WATER RETICULATION
- EXISTING RECYCLED WATER RETICULATION
- EXISTING ELECTRICITY UNDER GROUND
- EXISTING COMMUNICATIONS
- EXISTING GAS RETICULATION
- EXISTING SWALE
- FUTURE STORMWATER DRAINAGE
- FUTURE SEWER RETICULATION
- FUTURE WATER RETICULATION
- FUTURE RECYCLED WATER RETICULATION
- FUTURE COMMUNICATIONS
- FUTURE ELECTRICAL UNDER GROUND
- FUTURE GAS RETICULATION
- EXISTING TREES TO BE RETAINED
- EXISTING TREES TO BE REMOVED
- TEMPORARY FENCE
- TEMPORARY SWALE
- MUNICIPAL BOUNDARY
- PALING FENCE

NOTES:

1. FUTURE SUPERLOT BOUNDARIES SHOWN FOR SERVICE LOCATIONS ONLY. TO BE CONFIRMED UNDER SEPARATE CONTRACT.
2. STAGE 22A TO BE CONSTRUCTED CONCURRENTLY WITH STAGE 22B, D, E & MMR03.
3. UNLESS NOTED OTHERWISE, ALL SERVICES WILL CROSS OVER DRAINAGE PIPE EXCEPT SEWER PIPE. REFER TO RELEVANT UTILITYDESIGN PACKAGES FOR DETAILS.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

ROADWORKS AND DRAINAGE LAYOUT PLAN SHEET 2


ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0221	04

100mm on Original

Date Plotted: 27 Jul 2023 - 03:30pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0220-Roadworks.dwg V1

NOTE:
1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.



Vertical Curve Length (m)
Vertical Curve Radius (m)

Vertical Grade (%)
Vertical Grade (1 in ...)

Horizontal Curve Radius

DATUM RL 95.0


| | | |

LEGEND

STRUCTURAL FILL

NOTE:


1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.



DATUM RL 97.00

PROPOSED LEVEL		99.870	99.869	99.839	99.777	99.627	99.612	99.560	99.520	99.560	99.662	99.560	99.520	99.560	99.612	99.627	99.777	99.839	99.869	99.870	99.806
EXISTING LEVEL		99.958	99.958	99.947	99.928	99.927	99.924	99.912	99.910	99.907	99.884	99.861	99.858	99.856	99.844	99.841	99.840	99.821	99.810	99.810	99.806
OFFSET	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	10.510	


CH 39.996



DATUM RL 97.00

PROPOSED LEVEL		100.118	100.186	100.185	100.155	100.093	100.093	99.943	99.928	99.876	99.836	99.876	99.836	99.876	99.876	99.928	100.093	100.155	100.185	100.186	99.922
EXISTING LEVEL		100.118	100.116	100.116	100.103	100.083	100.082	99.943	99.928	99.876	99.836	99.876	99.836	99.876	99.876	99.928	99.962	99.958	99.943	100.053	99.922
OFFSET	-10.270	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	12.110


CH 62.422



DATUM RL 98.00

PROPOSED LEVEL		100.224	100.325	100.324	100.294	100.174	100.024	100.064	100.166	100.064	100.024	100.183	100.136	100.106	100.105	100.063					
EXISTING LEVEL		100.224	100.222	100.222	100.214	100.185	100.183	100.180	100.158	100.129	100.125	100.123	100.073	100.057	100.057	100.053					
OFFSET	-10.400	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.650	8.450	9.950	10.000	10.330					


CH 75.753



DATUM RL 98.00

PROPOSED LEVEL		100.339	100.476	100.475	100.445	100.383	100.233	100.218	100.300	100.166	100.126	100.166	100.268	100.215	100.166	100.126	100.276	100.156	100.126	100.125	100.135
EXISTING LEVEL		100.339	100.335	100.335	100.326	100.312	100.311	100.308	100.300	100.299	100.297	100.297	100.282	100.215	100.207	100.204		100.148	100.139	100.139	100.122
OFFSET	-10.550	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.650				8.450	9.950	10.000	12.830	


CH 111.076



DATUM RL 97.00

PROPOSED LEVEL		99.748	99.747	99.717		99.597	99.447	99.487	99.588	99.487	99.447	99.597		99.717	99.747	99.748	99.767				
EXISTING LEVEL		99.894	99.894	99.884		99.854	99.853	99.850	99.831	99.811	99.809	99.808		99.777	99.768	99.767	99.767				
OFFSET	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.650		8.450	9.950	10.000	10.110					


CH 34.782



DATUM RL 97.00

PROPOSED LEVEL		100.105	100.152	100.151	100.121	100.069	99.909	99.894	99.842	99.802	99.944	99.842	99.802	99.842	99.842	99.894	100.059	100.121	100.151	100.152	99.919
EXISTING LEVEL		100.105	100.103	100.103	100.090	100.069	100.068	100.064	100.051	100.045	100.019	99.994	99.990	99.987	99.974	99.970	99.969	99.948	99.935	99.935	99.919
OFFSET	-10.190	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	11.860


CH 60.000



DATUM RL 98.00

PROPOSED LEVEL		100.224	100.325	100.324	100.294	100.174	100.024	100.064	100.166	100.064	100.024	100.183	100.136	100.106	100.105	100.063					
EXISTING LEVEL		100.224	100.222	100.222	100.214	100.185	100.183	100.180	100.158	100.129	100.125	100.123	100.073	100.057	100.057	100.053					
OFFSET	-10.400	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.650	8.450	9.950	10.000	10.330					


CH 75.753



DATUM RL 98.00

PROPOSED LEVEL		100.322	100.529	100.528	100.498	100.436	100.286	100.271	100.219	100.179	100.286	100.219	100.321	100.176	100.173	100.179	100.329	100.209	100.179	100.178	100.111
EXISTING LEVEL		100.322	100.317	100.317	100.307	100.290	100.289	100.286	100.276	100.274	100.271	100.271	100.251	100.176	100.173	100.172		100.142	100.133	100.133	100.112
OFFSET	-10.830	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.650				8.450	9.950	10.000	13.340	


CH 100.000



DATUM RL 97.00

PROPOSED LEVEL		99.675	99.673	99.643		99.523	99.382	99.413	99.515	99.413	99.373	99.523		99.643	99.673	99.674	99.735				
EXISTING LEVEL		99.851	99.850	99.835		99.793	99.792	99.790	99.774	99.758	99.756	99.755		99.730	99.734	99.735	99.735				
OFFSET	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.650		8.450	9.950	10.000	10.360					


CH 29.566



DATUM RL 97.00

PROPOSED LEVEL		100.067	100.052	100.051	100.021	99.959	99.794	99.702	99.742	99.844	99.742	99.702	99.742	99.809	99.959	100.021	100.051	100.052	99.888		
EXISTING LEVEL		100.067	100.066	100.066	100.053	100.032	99.959	99.809	99.742	99.702	99.742	99.995	99.975	99.973	99.971	99.957	99.956	99.926	99.906	99.906	99.888
OFFSET	-10.090	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	11.310


CH 52.895



DATUM RL 98.00

PROPOSED LEVEL		100.194	100.264	100.263	100.233	100.113	99.963	100.003	100.105	100.003	99.963	100.003	100.055	100.070	100.220	100.195	100.165	100.164	100.021	100.151	
EXISTING LEVEL		100.194	100.192	100.191	100.181	100.146	100.145	100.142	100.120	100.090	100.086	100.083	100.068	100.064	100.062	100.038	100.023	100.022	100.021	100.100	
OFFSET	-10.280	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	10.000	10.100	

CH 71.422



DATUM RL 98.00

PROPOSED LEVEL		100.316	100.531	100.530	100.500	100.438	100.288	100.273	100.221	100.181	100.221	100.323	100.221	100.181	100.331	100.211	100.181	100.180	100.107		
EXISTING LEVEL		100.316	100.310	100.310	100.300	100.283	100.282	100.279	100.267	100.264	100.243	100.176	100.173	100.172		100.142	100.133	100.132	100.111		
OFFSET	-10.860	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.650		8.450	9.950	10.000	13.360		

CH 97.424

DATUM RL 97.00

PROPOSED LEVEL		99.666	99.665	99.635		99.515	99.365	99.405	99.507	99.405	99.365	99.515		99.635	99.665	99.666	99.696				
EXISTING LEVEL		99.847	99.847	99.832		99.787	99.786	99.784	99.768	99.752	99.749	99.749		99.725	99.730	99.730	99.730				
OFFSET	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.650		8.450	9.950	10.000	10.120					

CH 28.994

DATUM RL 97.00

PROPOSED LEVEL		99.870	99.869	99.839	99.777	99.627	99.612	99.560	99.521	99.560	99.662	99.560	99.520	99.560	99.612	99.627	99.777	99.839	99.869	99.870	99.806
EXISTING LEVEL		99.958	99.958	99.947	99.928	99.927	99.924	99.912	99.910	99.907	99.884	99.861	99.858	99.856	99.844	99.841	99.840	99.821	99.810	99.810	99.806
OFFSET	-10.000	-9.950	-8.450	-5.950	-5.800	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	10.510	

CH 40.000

DATUM RL 98.00

PROPOSED LEVEL		100.155	100.204	100.203	100.173	100.053	99.903	99.943	100.044	99.943	99.903	99.943	100.009	100.159	100.149	100.130	100.129	100.098			
EXISTING LEVEL		100.155	100.154	100.153	100.143	100.108	100.107	100.104	100.082	100.052	100.048	100.045	100.030	99.994	99.995	99.985	99.985	99.982			
OFFSET	-10.190	-10.000	-9.950	-8.450		-3.650	-3.500	-3.050	0.000	3.050	3.500	3.800	5.350	5.800	5.950	8.450	9.950	10.000	10.250		

CH 67.145

DATUM RL 98.00

PROPOSED LEVEL		100.251	100.435	100.434	100.404	100.342	100.192	100.177	100.125	100.085	100.213	100.085	100.227	100.166	100.162	100.160	100.235	100.132	100.102	100.101	100.073
EXISTING LEVEL		100.251	100.248	100.247	100.240	100.227	100.227	100.224	100.215	100.213	100.196	100.176	100.173	100.172		100.111	100.095	100.095	100.095	100.073	
OFFSET	-10.740	-10.000	-9.950	-8.450	-5.950	-5.350	-3.800	-3.500	-3.050	0.000	3.050	3.500	3.650			8.450	9.950	10.000	12.110		

CH 80.476

GYMBOWEN AVENUE (MC04) - CROSS SECTIONS

SCALE 1:200 HORI.
1:100 VERT.

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 5 10 15 20m
1 : 200

0 2 4 6 8 10m
1 : 100

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title


GYMBOWEN AVENUE (MC04)
CROSS SECTIONS
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0241	03

NOTE:
1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

LEGEND
STRUCTURAL FILL



DATUM RL 98.00


| | | |

LEGEND

STRUCTURAL FILL

NOTE:


1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.
3. REFER TO LANDSCAPE DETAIL DRAWINGS FOR RETAINING WALL AND SAFETY BARRIER DETAILS



DATUM RL 99.00

| | | |

NOTE:
1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.




| | | |

LEGEND

STRUCTURAL FILL

NOTE:


1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.



DATUM RL 97.50

PROPOSED LEVEL		98.881	98.880	98.850	98.707	98.557	98.597	98.704	98.597	98.557	98.707	98.765	98.845	98.832
EXISTING LEVEL		98.147	98.148	98.177	98.225	98.228	98.237	98.299	98.361	98.370	98.373	98.413	98.439	98.439
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.340	8.390


CH 333.011



DATUM RL 98.00

PROPOSED LEVEL		98.992	98.991	98.961	98.899	98.748	98.788	98.895	98.788	98.749	98.899	98.998	99.000
EXISTING LEVEL		98.716	98.717	98.731	98.754	98.756	98.760	98.790	98.820	98.825	98.826	98.864	98.864
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 371.271



DATUM RL 98.00

PROPOSED LEVEL		99.136	99.135	99.105	99.042	98.882	98.932	99.039	98.932	98.882	99.042	99.142	99.143
EXISTING LEVEL		99.030	99.031	99.046	99.071	99.073	99.077	99.110	99.142	99.147	99.148	99.182	99.182
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 400.000



DATUM RL 98.50

PROPOSED LEVEL		99.414	99.413	99.383	99.321	99.171	99.211	99.318	99.211	99.171	99.321	99.391	99.421	99.422
EXISTING LEVEL		99.560	99.561	99.568	99.581	99.582	99.584	99.600	99.615	99.617	99.617	99.625	99.629	99.629
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 455.771



DATUM RL 97.70

PROPOSED LEVEL		98.726	98.496	98.603	98.496	98.456	98.606	98.810	98.840	98.842			
EXISTING LEVEL		98.389	98.413	98.455	98.468	98.469	98.470	98.482	98.487	98.487			
OFFSET		-5.000	-3.200	0.000	3.200	3.650	3.800	7.950	9.450	9.500			


CH 312.839



DATUM RL 98.00

PROPOSED LEVEL		98.936	98.935	98.905	98.842	98.692	98.732	98.839	98.732	98.692	98.842	98.912	98.942	98.943
EXISTING LEVEL		98.564	98.565	98.579	98.600	98.601	98.604	98.627	98.649	98.653	98.654	98.674	98.684	98.685
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 360.000



DATUM RL 98.00

PROPOSED LEVEL		99.130	99.129	99.099	99.036	98.886	98.926	99.033	98.926	98.886	99.036	99.106	99.136	99.137
EXISTING LEVEL		99.018	99.018	99.033	99.058	99.059	99.064	99.095	99.127	99.132	99.133	99.161	99.171	99.172
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 398.771



DATUM RL 98.30

PROPOSED LEVEL		99.349	99.348	99.318	99.256	99.106	99.146	99.253	99.146	99.106	99.256	99.326	99.356	99.357
EXISTING LEVEL		99.453	99.454	99.462	99.477	99.478	99.480	99.510	99.543	99.545	99.546	99.562	99.570	99.570
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 442.771



DATUM RL 97.70

PROPOSED LEVEL		98.726	98.496	98.603	98.496	98.456	98.606	98.814	98.844	98.845			
EXISTING LEVEL		98.409	98.432	98.469	98.460	98.461	98.462	98.494	98.499	98.499			
OFFSET		-5.000	-3.200	0.000	3.200	3.650	3.800	7.950	9.450	9.500			


CH 311.965



DATUM RL 98.00

PROPOSED LEVEL		98.919	98.918	98.888	98.826	98.676	98.716	98.823	98.716	98.676	98.826	98.896	98.926	98.927
EXISTING LEVEL		98.519	98.520	98.530	98.548	98.549	98.552	98.575	98.598	98.601	98.602	98.622	98.633	98.633
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 356.771



DATUM RL 98.00

PROPOSED LEVEL		99.057	99.056	99.026	98.964	98.813	98.853	98.960	98.853	98.814	98.964	99.033	99.063	99.065
EXISTING LEVEL		98.873	98.874	98.887	98.909	98.910	98.914	98.943	98.972	98.976	98.977	99.002	99.015	99.016
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 384.271



DATUM RL 98.30

PROPOSED LEVEL		99.236	99.235	99.205	99.142	98.992	99.032	99.139	99.032	98.992	99.142	99.212	99.242	99.243
EXISTING LEVEL		99.273	99.274	99.289	99.306	99.307	99.310	99.331	99.351	99.354	99.355	99.369	99.374	99.374
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 420.000

DATUM RL 97.70

PROPOSED LEVEL		98.730	98.500	98.606	98.500	98.460	98.610	98.817	98.847	98.848			
EXISTING LEVEL		98.453	98.474	98.503	98.522	98.523	98.523	98.536	98.540	98.541			
OFFSET		-5.000	-3.200	0.000	3.200	3.650	3.800	7.950	9.450	9.500			

CH 308.932

DATUM RL 97.70

PROPOSED LEVEL		98.881	98.880	98.850	98.742	98.592	98.632	98.739	98.632	98.592	98.742	98.812	98.842	98.843
EXISTING LEVEL		98.224	98.225	98.233	98.271	98.274	98.283	98.339	98.385	98.392	98.394	98.435	98.456	98.457
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 340.000

DATUM RL 98.00

PROPOSED LEVEL		99.036	99.035	99.005	98.942	98.792	98.832	98.939	98.832	98.792	98.942	99.012	99.042	99.043
EXISTING LEVEL		98.826	98.826	98.840	98.862	98.863	98.867	98.896	98.924	98.928	98.930	98.955	98.968	98.969
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 380.000

DATUM RL 98.00

PROPOSED LEVEL		99.194	99.193	99.163	99.101	98.951	98.991	99.097	98.991	98.951	99.101	99.171	99.201	99.202
EXISTING LEVEL		99.173	99.174	99.189	99.214	99.216	99.220	99.249	99.270	99.273	99.274	99.290	99.295	99.295
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 411.771

CHERRYPOOL CRESCENT (MC05) - CROSS SECTIONS

SCALE 1:200 HORI.
1:100 VERT.

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	MR	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 5 10 15 20m
1 : 200

0 2 4 6 8 10m
1 : 100

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: CHERRYPOOL CRESCENT (MC05)
CROSS SECTIONS
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com


Project No.	Originator	Zone / Stage	Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD		CV	DRG	0245	03

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

LEGEND


STRUCTURAL FILL



DATUM RL 98.50

PROPOSED LEVEL		99.552	99.551	99.521	99.459	99.308	99.348	99.455	99.348	99.308	99.459	99.528	99.558	99.559
EXISTING LEVEL		99.744	99.745	99.751	99.762	99.762	99.764	99.778	99.794	99.797	99.797	99.807	99.812	99.812
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 483.271



DATUM RL 98.70

PROPOSED LEVEL		99.707	99.706	99.676	99.614	99.463	99.503	99.610	99.503	99.463	99.614	99.683	99.713	99.714
EXISTING LEVEL		99.913	99.913	99.922	99.937	99.938	99.941	99.960	99.979	99.982	99.983	99.998	100.004	100.004
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 514.271



DATUM RL 98.80

PROPOSED LEVEL		99.851	99.850	99.820	99.757	99.607	99.647	99.754	99.647	99.607	99.757	99.857	99.858	
EXISTING LEVEL		100.037	100.037	100.042	100.051	100.052	100.053	100.064	100.075	100.075	100.076	100.085	100.085	
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	8.100	8.150	


CH 540.000



DATUM RL 99.00

PROPOSED LEVEL		100.098	100.097	100.017	99.955	99.805	99.844	99.951	99.845	99.805	99.955	100.123	100.220	100.221
EXISTING LEVEL		100.151	100.151	100.160	100.170	100.170	100.172	100.184	100.175	100.174	100.174	100.184	100.195	100.196
OFFSET		-8.730	-8.680	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.980	9.030


CH 572.905



DATUM RL 98.50

PROPOSED LEVEL		99.536	99.535	99.505	99.442	99.292	99.332	99.439	99.332	99.292	99.442	99.512	99.542	99.543
EXISTING LEVEL		99.724	99.724	99.730	99.741	99.742	99.744	99.760	99.776	99.778	99.779	99.789	99.794	99.794
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 480.000



DATUM RL 98.70

PROPOSED LEVEL		99.636	99.635	99.605	99.542	99.392	99.432	99.539	99.432	99.392	99.542	99.612	99.642	99.643
EXISTING LEVEL		99.830	99.831	99.837	99.852	99.853	99.856	99.875	99.894	99.896	99.897	99.909	99.914	99.914
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 500.000



DATUM RL 98.80

PROPOSED LEVEL		99.761	99.760	99.730	99.667	99.517	99.557	99.664	99.557	99.517	99.667	99.737	99.767	99.768
EXISTING LEVEL		99.948	99.949	99.957	99.972	99.973	99.976	99.995	100.014	100.017	100.018	100.033	100.040	100.040
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 524.996



DATUM RL 99.00

PROPOSED LEVEL		99.971	99.970	99.940	99.877	99.727	99.767	99.874	99.767	99.727	99.877	99.947	99.977	99.976
EXISTING LEVEL		100.185	100.185	100.187	100.190	100.190	100.191	100.190	100.189	100.188	100.188	100.187	100.187	100.187
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 560.000



DATUM RL 98.50

PROPOSED LEVEL		99.487	99.486	99.456	99.394	99.243	99.283	99.390	99.283	99.243	99.394	99.463	99.493	99.494
EXISTING LEVEL		99.666	99.666	99.674	99.687	99.687	99.690	99.706	99.722	99.724	99.725	99.737	99.741	99.742
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 470.271



DATUM RL 98.70

PROPOSED LEVEL		99.624	99.623	99.593	99.531	99.381	99.421	99.528	99.421	99.381	99.531	99.601	99.631	99.632
EXISTING LEVEL		99.820	99.820	99.826	99.838	99.839	99.842	99.861	99.880	99.883	99.884	99.895	99.900	99.900
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150


CH 497.771



DATUM RL 98.80

PROPOSED LEVEL		99.736	99.735	99.705	99.642	99.492	99.532	99.639	99.532	99.492	99.642	99.712	99.742	99.743
EXISTING LEVEL		99.932	99.932	99.941	99.956	99.957	99.959	99.979	99.998	100.000	100.001	100.017	100.023	100.024
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 520.000



DATUM RL 98.80

PROPOSED LEVEL		99.861	99.860	99.830	99.768	99.618	99.658	99.765	99.658	99.618	99.768	99.838	99.868	99.869
EXISTING LEVEL		100.049	100.049	100.054	100.063	100.063	100.065	100.077	100.085	100.085	100.085	100.089	100.092	100.092
OFFSET		-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150

CH 541.800

CHERRYPOOL CRESCENT (MC05) - CROSS SECTIONS

SCALE 1:200 HORI.
1:100 VERT.

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	MR	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 5 10 15 20m
1 : 200

0 2 4 6 8 10m
1 : 100

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

CHERRYPOOL CRESCENT (MC05)
CROSS SECTIONS
SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0246	03

100mm on Original

DRAWING REMOVED FROM SET

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	MR	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 5 10 15 20m

1 : 200

0 2 4 6 8 10m

1 : 100

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON


Title

CHERRYPOOL CRESCENT (MC05)
CROSS SECTIONS
SHEET 3

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0247	03

Date Plotted: 14 Mar 2023 - 02:58pm File Name: C:\Users\reyesm1531\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0240-RoadLS-XS.dwg V2



INTERSECTION CHERRYPOOL CRESCENT (MC05)
CH 0.000
HI CH 14.330
EXISTING SURFACE
PROPOSED SURFACE
IP RL 99.435
IP RL 99.537
IP RL 98.893
REFER DRAWINGS
DRG-0260 TO DRG-0265
FOR KERB RETURN LEVELS
DRIVEWAY CROSSOVER
REFER MCC STD DWG MCC 504
15 VC
R 379
1.0%
1:100
-3.0%
-1:34
-2.5%
-1:40

| | | |

NOTE:
1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

LEGEND

STRUCTURAL FILL




| | | |

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

LEGEND


STRUCTURAL FILL



DATUM RL 99.50

PROPOSED LEVEL		100.604	100.404	100.403	100.373	100.310	100.160	100.200	100.307	100.200	100.160	100.310	100.380	100.410	100.411	100.745
EXISTING LEVEL		100.051	100.034	100.033	100.020	99.998	99.997	99.993	99.965	99.937	99.933	99.932	99.907	99.895	99.895	99.881
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150


CH 96.616



DATUM RL 99.50

PROPOSED LEVEL		100.790	100.547	100.546	100.516	100.453	100.303	100.343	100.450	100.343	100.303	100.453	100.523	100.553	100.554	100.888
EXISTING LEVEL		100.167	100.150	100.150	100.137	100.115	100.114	100.110	100.083	100.057	100.054	100.052	100.030	100.018	100.017	100.001
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150


CH 83.616



DATUM RL 99.00

PROPOSED LEVEL		100.347	100.147	100.146	100.116	100.053	99.903	99.943	100.050	99.943	99.903	100.053	100.123	100.153	100.154	100.487
EXISTING LEVEL		99.992	99.972	99.972	99.957	99.933	99.931	99.927	99.895	99.864	99.859	99.858	99.830	99.816	99.815	99.795
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150


CH 120.000



DATUM RL 99.50

PROPOSED LEVEL		100.859	100.587	100.586	100.556	100.493	100.343	100.383	100.490	100.383	100.343	100.493	100.563	100.593	100.594	100.927
EXISTING LEVEL		100.199	100.162	100.162	100.169	100.148	100.147	100.143	100.117	100.091	100.088	100.086	100.064	100.052	100.051	100.035
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150


CH 80.000



DATUM RL 99.00

PROPOSED LEVEL		100.444	100.244	100.243	100.213	100.151	100.001	100.041	100.147	100.041	100.001	100.151	100.221	100.251	100.252	100.585
EXISTING LEVEL		100.001	99.987	99.986	99.976	99.958	99.957	99.953	99.922	99.891	99.886	99.885	99.857	99.842	99.842	99.822
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150


CH 111.116



DATUM RL 99.50

PROPOSED LEVEL		101.040	100.706	100.705	100.675	100.613	100.463	100.503	100.609	100.503	100.463	100.613	100.683	100.713	100.714	101.047
EXISTING LEVEL		100.244	100.225	100.225	100.211	100.190	100.189	100.185	100.161	100.136	100.132	100.131	100.110	100.098	100.098	100.082
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150


CH 69.116



DATUM RL 99.00

PROPOSED LEVEL		100.567	100.367	100.366	100.336	100.273	100.123	100.163	100.270	100.163	100.123	100.273	100.343	100.373	100.374	100.707
EXISTING LEVEL		100.020	100.003	100.003	99.990	99.966	99.966	99.963	99.940	99.917	99.914	99.913	99.891	99.876	99.875	99.863
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150

CH 100.000



DATUM RL 99.00

PROPOSED LEVEL		100.263	100.063	100.062	100.032	99.969	99.819	99.839	99.966	99.859	99.819	99.969	100.039	100.069	100.070	100.404
EXISTING LEVEL		99.973	99.953	99.952	99.937	99.913	99.911	99.907	99.875	99.843	99.839	99.837	99.809	99.794	99.794	99.774
OFFSET		-9.850	-7.850	-7.800	-6.300	-3.800	-3.650	-3.200	0.000	3.200	3.650	3.800	6.600	8.100	8.150	10.150

CH 127.616

GOROKE STREET (MC09) - CROSS SECTIONS

SCALE 1:200 HORI.
1:100 VERT.

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	MR	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 5 10 15 20m

1 : 200

0 2 4 6 8 10m

1 : 100

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project


EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

GOROKE STREET (MC09)
CROSS SECTIONS

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0250	03




Vertical Curve Length (m)
Vertical Curve Radius (m)

Vertical Grade (%)
Vertical Grade (1 in ...)

Horizontal Curve Radius


DATUM RL 93.0

| | | |



KARNAK LANE (MC11) - LONGITUDINAL SECTION


SCALE 1:500 HORI.
1:50 VERT.



DATUM RL 99.00

PROPOSED LEVEL	99.694	99.669	99.594	99.669	99.694
EXISTING LEVEL	99.817	99.827	99.856	99.884	99.891
OFFSET	-4.000	-3.000	0.000	3.000	4.000


CH 40.000



DATUM RL 98.50

PROPOSED LEVEL	99.486	99.236	99.211	99.136	99.211	99.236
EXISTING LEVEL	99.606	99.615	99.619	99.632	99.645	99.649
OFFSET	-6.000	-4.000	-3.000	0.000	3.000	4.000


CH 76.031



DATUM RL 99.00

PROPOSED LEVEL	99.951	99.926	99.851	99.926	99.951
EXISTING LEVEL	99.927	99.932	99.948	99.964	99.970
OFFSET	-4.000	-3.000	0.000	3.000	4.000


CH 20.000



DATUM RL 98.50

PROPOSED LEVEL	99.550	99.435	99.410	99.335	99.410	99.435
EXISTING LEVEL	99.709	99.721	99.727	99.745	99.764	99.770
OFFSET	-6.000	-4.000	-3.000	0.000	3.000	4.000


CH 60.000



DATUM RL 99.00

PROPOSED LEVEL	99.962	99.937	99.862	99.937	99.962
EXISTING LEVEL	99.939	99.944	99.961	99.978	99.983
OFFSET	-4.000	-3.000	0.000	3.000	4.000


CH 16.332



DATUM RL 98.50

PROPOSED LEVEL	99.566	99.453	99.428	99.353	99.428	99.453
EXISTING LEVEL	99.720	99.732	99.738	99.756	99.775	99.781
OFFSET	-6.000	-4.000	-3.000	0.000	3.000	4.000


CH 58.535



DATUM RL 98.00

PROPOSED LEVEL	99.257	99.047	99.022	98.947	99.022	99.047
EXISTING LEVEL	99.530	99.538	99.543	99.556	99.568	99.573
OFFSET	-6.000	-4.000	-3.000	0.000	3.000	4.000


CH 82.535



DATUM RL 99.00

PROPOSED LEVEL	99.949	99.924	99.849	99.924	99.949
EXISTING LEVEL	99.952	99.958	99.976	99.992	99.998
OFFSET	-4.000	-3.000	0.000	3.000	4.000


CH 12.129



DATUM RL 99.00

PROPOSED LEVEL	99.675	99.650	99.575	99.650	99.675
EXISTING LEVEL	99.810	99.819	99.848	99.877	99.885
OFFSET	-4.000	-3.000	0.000	3.000	4.000

CH 41.365



DATUM RL 98.00

PROPOSED LEVEL	99.470	99.187	99.162	99.087	99.162	99.187
EXISTING LEVEL	99.560	99.568	99.572	99.585	99.598	99.602
OFFSET	-6.000	-4.000	-3.000	0.000	3.000	4.000

CH 80.000

KARNAK LANE (MC11) - CROSS SECTIONS

SCALE 1:200 HORI.
1:100 VERT.

NOTE:
1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	MR	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales
0 10 20 30 40 50m
1 : 500
0 5 10 15 20m
1 : 200
0 2 4 6 8 10m
1 : 100
0 1 2 3 4 5m
1 : 50

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: KARNAK LANE (MC11)
LONGITUDINAL SECTION &
CROSS SECTIONS

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com


Project No.	Originator	Zone	Stage	Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD			CV	DRG	0252	03

100mm on Original

NOTE:
1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

LEGEND

STRUCTURAL FILL



REFER DRAWINGS DRG-0260 TO DRG-0265 FOR KERB RETURN LEVELS

Vertical Curve Length (m)
Vertical Curve Radius (m)
Vertical Grade (%)
Vertical Grade (1 in ...)
Horizontal Curve Radius

DATUM RL 93.0


| | | |

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. STRUCTURAL FILL IS REQUIRED WHERE FOOTPATH OR PAVEMENT IS CONSTRUCTED ABOVE EXISTING SURFACE.

LEGEND


STRUCTURAL FILL



DATUM RL 97.50

PROPOSED LEVEL		99.056	98.856	98.806	98.731	98.806	98.856
EXISTING LEVEL		99.322	99.307	99.291	99.260	99.228	99.207
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 101.353



DATUM RL 97.50

PROPOSED LEVEL		98.893	98.693	98.643	98.568	98.643	98.693
EXISTING LEVEL		98.995	98.975	98.954	98.921	98.888	98.866
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 132.353



DATUM RL 97.00

PROPOSED LEVEL		98.748	98.548	98.498	98.423	98.498	98.548
EXISTING LEVEL		98.640	98.618	98.595	98.556	98.504	98.470
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 160.000



DATUM RL 97.00

PROPOSED LEVEL		98.604	98.404	98.354	98.279	98.354	98.404
EXISTING LEVEL		98.286	98.262	98.238	98.187	98.132	98.096
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 187.353



DATUM RL 97.50

PROPOSED LEVEL		99.263	98.929	98.879	98.804	98.879	98.929
EXISTING LEVEL		99.399	99.384	99.369	99.346	99.307	99.288
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 87.353



DATUM RL 97.50

PROPOSED LEVEL		98.951	98.751	98.701	98.626	98.701	98.751
EXISTING LEVEL		99.153	99.131	99.109	99.076	99.037	99.011
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 121.353



DATUM RL 97.50

PROPOSED LEVEL		98.778	98.578	98.528	98.453	98.528	98.578
EXISTING LEVEL		98.703	98.680	98.658	98.621	98.569	98.534
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 154.353



DATUM RL 97.00

PROPOSED LEVEL		98.643	98.443	98.393	98.318	98.393	98.443
EXISTING LEVEL		98.403	98.379	98.354	98.307	98.252	98.215
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 180.000



DATUM RL 97.50

PROPOSED LEVEL		99.301	98.968	98.918	98.843	98.918	98.968
EXISTING LEVEL		99.451	99.436	99.421	99.398	99.360	99.318
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 80.000



DATUM RL 97.50

PROPOSED LEVEL		98.958	98.758	98.708	98.633	98.708	98.758
EXISTING LEVEL		99.172	99.150	99.128	99.091	99.052	99.027
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 120.000



DATUM RL 97.50

PROPOSED LEVEL		98.835	98.635	98.585	98.510	98.585	98.635
EXISTING LEVEL		98.837	98.817	98.797	98.765	98.728	98.699
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 143.353



DATUM RL 97.00

PROPOSED LEVEL		98.662	98.462	98.412	98.337	98.412	98.462
EXISTING LEVEL		98.461	98.437	98.412	98.366	98.310	98.273
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 176.353



DATUM RL 97.50

PROPOSED LEVEL		99.310	98.977	98.927	98.852	98.927	98.977
EXISTING LEVEL		99.463	99.448	99.432	99.410	99.371	99.330
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 78.353



DATUM RL 97.50

PROPOSED LEVEL		99.009	98.809	98.759	98.684	98.759	98.809
EXISTING LEVEL		99.275	99.254	99.233	99.202	99.164	99.138
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 110.353



DATUM RL 97.50

PROPOSED LEVEL		98.853	98.653	98.603	98.528	98.603	98.653
EXISTING LEVEL		98.885	98.865	98.845	98.813	98.779	98.750
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000


CH 140.000



DATUM RL 97.00

PROPOSED LEVEL		98.720	98.520	98.470	98.395	98.470	98.520
EXISTING LEVEL		98.581	98.558	98.536	98.495	98.443	98.409
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000

CH 165.353



DATUM RL 97.00

PROPOSED LEVEL		98.556	98.357	98.307	98.232	98.307	98.357
EXISTING LEVEL		98.143	98.119	98.094	98.040	97.986	97.949
OFFSET		-7.000	-5.000	-3.000	0.000	3.000	5.000

CH 196.353

KARNAK LANE (MC12) - CROSS SECTIONS

SCALE 1:200 HORI.
1:100 VERT.

Issue	Description	DR	CH	VE	Date
03	UPDATED FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	MR	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 5 10 15 20m
1 : 200
0 2 4 6 8 10m
1 : 100

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		


Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: KARNAK LANE (MC12)
CROSS SECTIONS

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com


Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0254	03

Date Plotted: 9 Nov 2022 - 11:46am File Name: C:\Users\menezc4027\ACCDocs\Arcadis\a-au-10029435-eynesbury Estate\project Files\01_work In Progress\01_civil_cv\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0240-RoadLS-XS.dwg V2




GYMBOWEN AVENUE INDENTED PARKING DETAIL - CH 75.753

SCALE 1:200



GYMBOWEN AVENUE INDENTED PARKING DETAIL - CH 34.782

SCALE 1:200



MKCP05 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

MKCP06 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

CONTROL LINE SETOUT - MKCP05

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283152.166	5814628.366			
IP 2	1.563	283150.809	5814629.356	R = -3.450	3.127	51°55'28.78"
IP 3	3.127	283149.193	5814628.899			
IP 4	4.282	283147.998	5814628.561	R = 2.550	2.311	51°55'38.89"
IP 5	5.438	283146.995	5814629.293			

CONTROL LINE SETOUT - MKCP06

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283122.278	5814647.332			
IP 2	1.156	283121.275	5814648.064	R = 2.550	2.311	51°55'33.75"
IP 3	2.311	283121.233	5814649.305			
IP 4	3.874	283121.176	5814650.984	R = -3.450	3.127	51°55'34.83"
IP 5	5.438	283119.819	5814651.975			

MKCP01 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

MKCP02 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

MKCP03 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

MKCP04 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

CONTROL LINE SETOUT - MKCP01

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283187.725	5814606.622			
IP 2	1.490	283186.193	5814607.047	R = -3.450	2.980	49°29'27.71"
IP 3	2.980	283184.874	5814606.158			
IP 4	4.192	283183.787	5814605.425	R = 2.550	2.423	54°26'50.66"
IP 5	5.403	283182.558	5814605.883			

CONTROL LINE SETOUT - MKCP03

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283185.654	5814616.154			
IP 2	1.090	283186.737	5814615.731	R = 2.550	2.181	49°00'01.20"
IP 3	2.181	283187.127	5814614.637			
IP 4	3.836	283187.731	5814612.946	R = -3.450	3.310	54°58'32.10"
IP 5	5.491	283189.462	5814612.471			

CONTROL LINE SETOUT - MKCP02

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283161.578	5814618.649			
IP 2	1.156	283160.575	5814619.381	R = 2.550	2.311	51°55'37.80"
IP 3	2.311	283160.533	5814620.622			
IP 4	3.874	283160.476	5814622.301	R = -3.450	3.127	51°55'29.40"
IP 5	5.438	283159.119	5814623.292			

CONTROL LINE SETOUT - MKCP04

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283155.445	5814633.525			
IP 2	1.563	283156.802	5814632.534	R = -3.450	3.127	51°55'33.08"
IP 3	3.127	283158.419	5814632.992			
IP 4	4.282	283159.614	5814633.330	R = 2.550	2.311	51°55'36.76"
IP 5	5.438	283160.617	5814632.598			

LEGEND

- 5.0 — PROPOSED SURFACE CONTOURS
- 5.0 — EXISTING SURFACE CONTOURS
- PROPOSED KERB & CHANNEL
- PROPOSED STORMWATER DRAINAGE
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- FUTS — FUTURE SEWER RETICULATION
- FUTW — FUTURE WATER RETICULATION
- FUTR — FUTURE RECYCLED WATER RETICULATION
- FUTC — FUTURE COMMUNICATIONS
- FUTE — FUTURE ELECTRICAL UNDER GROUND
- FUTG — FUTURE GAS RETICULATION

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. ALL KERB SETOUT DATA AND LONG SECTION PROFILE SHOWN ON THE LIP OF KERB UNLESS NOTED OTHERWISE.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

N

0 5 10 15 20m

1 : 200

0 1 2 3 4m

1 : 40

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project


EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

INTERSECTION DETAIL PLAN
SHEET 1


ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0260	04



GYMBOWEN AVENUE - CHERRYPOOL CRESCENT INTERSECTION DETAIL


SCALE 1:200



MK01 LONGITUDINAL SECTION

SCALE 1:200 HORI.

1:40 VERT.



MK02 LONGITUDINAL SECTION

SCALE 1:200 HORI.


1:40 VERT.

CONTROL LINE SETOUT - MK01

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283119.447	5814671.002			
IP 2	7.108	283114.112	5814663.692	R = -9.050	14.216	90d00'00.00"
IP 3	14.216	283121.422	5814658.356			


CONTROL LINE SETOUT - MK02

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283101.632	5814672.800			
IP 2	7.108	283108.943	5814667.465	R = -9.050	14.216	90d00'00.00"
IP 3	14.216	283114.278	5814674.775			



GYMBOWEN AVENUE - GOROKE STREET INTERSECTION DETAIL


SCALE 1:200



MK03 LONGITUDINAL SECTION

SCALE 1:200 HORI.

1:40 VERT.



MK04 LONGITUDINAL SECTION

SCALE 1:200 HORI.

1:40 VERT.

CONTROL LINE SETOUT - MK03

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283051.354	5814720.699			
IP 2	7.108	283046.019	5814713.389	R = -9.050	14.216	90d00'00.00"
IP 3	14.216	283053.329	5814708.054			

CONTROL LINE SETOUT - MK04

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283033.539	5814722.497			
IP 2	7.108	283040.849	5814717.162	R = -9.050	14.216	90d00'00.00"
IP 3	14.216	283046.185	5814724.472			

LEGEND

- PROPOSED SURFACE CONTOURS (5.0)
- EXISTING SURFACE CONTOURS (5.0)
- PROPOSED KERB & CHANNEL
- PROPOSED STORMWATER DRAINAGE
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- FUTS — FUTURE SEWER RETICULATION
- FUTW — FUTURE WATER RETICULATION
- FUTR — FUTURE RECYCLED WATER RETICULATION
- FUTC — FUTURE COMMUNICATIONS
- FUTE — FUTURE ELECTRICAL UNDER GROUND
- FUTG — FUTURE GAS RETICULATION

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. ALL KERB SETOUT DATA AND LONG SECTION PROFILE SHOWN ON THE LIP OF KERB UNLESS NOTED OTHERWISE.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

1 : 200

1 : 40

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved


Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: INTERSECTION DETAIL PLAN
SHEET 2


ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone	Stage	Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD			CV	DRG	0261	04




GYMBOWEN AVENUE INDENTED PARKING DETAIL - CH 130.061

SCALE 1:200



MKCP09 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.



MKCP10 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

LEGEND

- PROPOSED SURFACE CONTOURS (5.0)
- EXISTING SURFACE CONTOURS (5.0)
- PROPOSED KERB & CHANNEL
- PROPOSED STORMWATER DRAINAGE
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- FUTS — FUTURE SEWER RETICULATION
- FUTW — FUTURE WATER RETICULATION
- FUTR — FUTURE RECYCLED WATER RETICULATION
- FUTC — FUTURE COMMUNICATIONS
- FUTE — FUTURE ELECTRICAL UNDER GROUND
- FUTG — FUTURE GAS RETICULATION

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. ALL KERB SETOUT DATA AND LONG SECTION PROFILE SHOWN ON THE LIP OF KERB UNLESS NOTED OTHERWISE.

CONTROL LINE SETOUT - MKCP09

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283108.299	5814660.383			
IP 2	1.563	283106.942	5814661.373	R = -3.450	3.127	51d55'33.08"
IP 3	3.127	283105.326	5814660.915			
IP 4	4.282	283104.131	5814660.577	R = 2.550	2.311	51d55'36.76"
IP 5	5.438	283103.128	5814661.309			

CONTROL LINE SETOUT - MKCP10


PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283055.386	5814696.153			
IP 2	1.156	283054.383	5814696.885	R = 2.550	2.311	51d55'36.76"
CC	2.311	283054.341	5814698.126			
IP 3	3.874	283054.284	5814699.805	R = -3.450	3.127	51d55'36.76"
IP 4	5.438	283052.927	5814700.795			

CONTROL LINE SETOUT - MKCP11

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283097.226	5814678.852			
IP 2	1.153	283098.226	5814678.122	R = 2.550	2.306	51d48'59.02"
IP 3	2.306	283098.271	5814676.884			
IP 4	3.866	283098.331	5814675.209	R = -3.450	3.120	51d49'01.37"
IP 5	5.426	283099.685	5814674.222			


CONTROL LINE SETOUT - MKCP12

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283055.519	5814706.455			
IP 2	1.560	283056.873	5814705.467	R = -3.450	3.120	51d48'59.17"
IP 3	3.120	283058.486	5814705.921			
IP 4	4.273	283059.679	5814706.256	R = 2.550	2.306	51d49'01.76"
IP 5	5.426	283060.680	5814705.525			



MKCP11 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.



MKCP12 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 5 10 15 20m

1 : 200

0 1 2 3 4m

1 : 40

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON


Title

INTERSECTION DETAIL PLAN
SHEET 3

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com


Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0262	04

Date Plotted: 27 Jul 2023 - 04:15pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0260-Intersection.dwg V1



GYMBOWEN AVENUE INDENTED PARKING DETAIL - CH 208.974


SCALE 1:200



Vertical Curve Length (m) / Vertical Curve Radius (m)										
DESIGN LEVELS ON KERB LIP LINE	101.295	101.301		101.313	101.323	101.324	101.346	101.346	101.370	101.376	101.381	101.387
EXISTING SURFACE ON KERB LIP LINE		100.455		100.469	100.476	100.476	100.483	100.483	100.488	100.490	100.492	
PEGGED CHAINAGE	-1.000	0.000		2.300	3.084	3.127	3.869	3.869	4.653	5.000	5.438	6.438

MKCP13 LONGITUDINAL SECTION


SCALE 1:200 HORI.
1:40 VERT.



Vertical Curve Length (m) / Vertical Curve Radius (m)										
DESIGN LEVELS ON KERB LIP LINE	101.606	101.606		101.606	101.600	101.580	101.580	101.561	101.560	101.545	101.544	101.539
EXISTING SURFACE ON KERB LIP LINE		100.695		100.695	100.694	100.694	100.693	100.693	100.692	100.688	100.687	
PEGGED CHAINAGE	-1.000	0.000		0.784	1.569	1.569	2.311	2.353	3.138	5.000	5.438	6.438

MKCP14 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.



Vertical Curve Length (m) / Vertical Curve Radius (m)										
DESIGN LEVELS ON KERB LIP LINE	101.508	101.502	101.491	101.467	101.444	101.443	101.433	101.424	101.422	101.416
EXISTING SURFACE ON KERB LIP LINE		100.474	100.470	100.469	100.470	100.470	100.472	100.467		
PEGGED CHAINAGE	-1.000	0.000	0.784	1.569	2.311	2.353	3.138	5.000	5.438	6.438

MKCP15 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

LEGEND

- PROPOSED SURFACE CONTOURS
- EXISTING SURFACE CONTOURS
- PROPOSED KERB & CHANNEL
- PROPOSED STORMWATER DRAINAGE
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- FUTS — FUTURE SEWER RETICULATION
- FUTW — FUTURE WATER RETICULATION
- FUTR — FUTURE RECYCLED WATER RETICULATION
- FUTC — FUTURE COMMUNICATIONS
- FUTE — FUTURE ELECTRICAL UNDER GROUND
- FUTG — FUTURE GAS RETICULATION

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. ALL KERB SETOUT DATA AND LONG SECTION PROFILE SHOWN ON THE LIP OF KERB UNLESS NOTED OTHERWISE.

CONTROL LINE SETOUT - MKCP13


PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283044.557	5814706.904			
IP 2	1.563	283043.200	5814707.894	R = -3.450	3.127	51°55'33.08"
IP 3	3.127	283041.584	5814707.437			
IP 4	4.282	283040.389	5814707.099	R = 2.550	2.311	51°55'36.76"
IP 5	5.438	283039.386	5814707.831			

CONTROL LINE SETOUT - MKCP14

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283006.435	5814731.880			
IP 2	1.156	283005.432	5814732.612	R = 2.550	2.311	51°55'36.76"
CC	2.311	283005.390	5814733.853			
IP 3	3.874	283005.333	5814735.532	R = -3.450	3.127	51°55'36.76"
IP 4	5.438	283003.976	5814736.522			


CONTROL LINE SETOUT - MKCP15

PT	CHAINAGE	EASTING	NORTHING	RAD/SPIRAL	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283029.384	5814728.377			
IP 2	1.155	283030.387	5814727.645	R = 2.550	2.311	51°55'28.19"
IP 3	2.311	283030.429	5814726.405			
IP 4	3.874	283030.486	5814724.726	R = -3.450	3.127	51°55'34.83"
IP 5	5.438	283031.843	5814723.735			



CHERRYPOOL CRESCENT BEND DETAIL

SCALE 1:200



Vertical Curve Length (m) / Vertical Curve Radius (m)												
DESIGN LEVELS ON KERB LIP LINE	98.602	98.597		98.576	98.565	98.548	98.546	98.523	98.516		98.496	98.492	98.491
EXISTING SURFACE ON KERB LIP LINE		98.361		98.352	98.356	98.370	98.371	98.405	98.415		98.468		
PEGGED CHAINAGE	-1.000	0.000		3.500	5.000	7.000	7.194	10.000	10.694		14.194	15.000	15.194

MK19 LONGITUDINAL SECTION

SCALE 1:200 HORI.
1:40 VERT.

CONTROL LINE SETOUT - MK19

PT	CHAINAGE	EASTING	NORTHING	RADIUS	A.LENGTH	DEFL.ANGLE
IP 1	0.000	283151.193	5814905.326			
IP 2	7.097	283151.828	5814914.331	-9.050	14.194	89°51'36.65"
IP 3	14.194	283142.824	5814914.988			

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 5 10 15 20m

1 : 200

0 1 2 3 4m

1 : 40

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

INTERSECTION DETAIL PLAN
SHEET 4

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0263	04

100mm on Original

DRAWING REMOVED FROM SET

Issue	Description	DR	CH	VE	Date
03	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 5 10 15 20m

1 : 200

0 1 2 3 4m

1 : 40

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

INTERSECTION DETAIL PLAN
SHEET 5

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0264	03


100mm on Original

Date Plotted: 10 Jul 2023 - 08:58pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0260-Intersection.dwg V1

DRAWING REMOVED FROM SET

Issue	Description	DR	CH	VE	Date
03	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales



Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title


INTERSECTION DETAIL PLAN
SHEET 6

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0265	03


100mm on Original

Date Plotted: 10 Jul 2023 - 08:58pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0260-Intersection.dwg V1




FILL BATTER TO FUTURE STAGE TYPICAL SECTION

NOT TO SCALE




PIT SETOUT DETAIL

NOT TO SCALE



TYPICAL TEMPORARY TURN AREA DETAIL

NOT TO SCALE



SINGLE PIPE


ELEVATION

nb. DUAL PIPE SIMILAR

STANDARD PIPE OUTLET DETAIL


NOT TO SCALE

nb. DUAL PIPE SIMILAR




B2 (600mm) KERB DETAIL

1:10



B3 (600mm) KERB DETAIL


1:10



INVERT CHANNEL (IC)


1:10

(TO INTERSECT WITH 600-WIDTH BARRIER KERB & CHANNEL)




TYPICAL SWALE DRAIN DETAIL

NOT TO SCALE




LINE MARKING FOR RAISED PAVEMENTS PLAN

SCALE 1:200




FLAT TOP RAISED PAVEMENT SECTION A

NOT TO SCALE



FLAT TOP RAISED PAVEMENT SECTION B

NOT TO SCALE



LINE MARKING FOR RAISED PAVEMENTS

NOT TO SCALE

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 5 10 15 20m

1 : 200

0 100 200 400 600 800 1000mm

1 : 10

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

TYPICAL DETAILS

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0280	04

PAVEMENT COMPOSITION TYPE 1
GOROKE STREET

LAYER	THICKNESS (mm)	MATERIAL
WEARING COURSE	20	SIZE 7 TYPE L ASPHALT (CLASS 320 BINDER)
BASE COURSE	30	SIZE 10 TYPE N ASPHALT (CLASS 320 BINDER)
INTERLAYER	5	S45R 10mm SAMI TREATMENT
WATER PROOFING	-	PRIME (OR 7mm PRIMER SEAL)
BASE	140	SIZE 20mm CLASS 2 CRUSHED ROCK COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 100% (MODIFIED) MAXIMUM DRY DENSITY AS1289, 5.2.1
SUBBASE	100	SIZE 20mm CLASS 3 CRUSHED ROCK COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (MODIFIED) MAXIMUM DRY DENSITY AS1289,5.2.1
CAPPING LAYER	150	TYPE A MATERIAL COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES: CBR ℏ 8%, SWELL ℍ1.5%, PERMEABILITY K ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
CONSTRUCTION LAYER	150 (MINIMUM)	CONSTRUCTION LAYER COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES : CBR ℏ 8%, SWELL ℍ1.5% AND PERMEABILITY ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
TOTAL	595	MINIMUM THICKNESS AS PER 2019 EDCM GUIDELINES
SUBGRADE	-	(CLAY) TOP 200mm COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1

PAVEMENT COMPOSITION TYPE 2
CHERRYPOOL CRESCENT


LAYER	THICKNESS (mm)	MATERIAL
WEARING COURSE 1	30	SIZE 10 TYPE L ASPHALT (CLASS 320 BINDER)
WEARING COURSE 2	30	SIZE 10 TYPE N ASPHALT (CLASS 320 BINDER)
INTERLAYER	5	S45R 10mm SAMI TREATMENT
WATERPROOFING	-	PRIME (OR 7mm PRIMER SEAL)
BASE	130	SIZE 20mm CLASS 2 CRUSHED ROCK COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 100% (MODIFIED) MAXIMUM DRY DENSITY AS1289, 5.2.1
UPPER SUBBASE	100	SIZE 20mm CLASS 3 CRUSHED ROCK COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (MODIFIED) MAXIMUM DRY DENSITY AS1289,5.2.1
LOWER SUBBASE	100	SIZE 20mm CLASS 4 CRUSHED ROCK COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (MODIFIED) MAXIMUM DRY DENSITY AS1289,5.2.1
CAPPING LAYER	150	TYPE A MATERIAL COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES: CBR ℏ 8%, SWELL ℍ1.5%, PERMEABILITY K ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
CONSTRUCTION LAYER	150 (MINIMUM)	CONSTRUCTION LAYER COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES : CBR ℏ 8%, SWELL ℍ1.5% AND PERMEABILITY ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
TOTAL	695	
SUBGRADE	-	(CLAY) TOP 200mm COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1

PAVEMENT COMPOSITION TYPE 3
GYMBOWEN AVENUE

LAYER	THICKNESS (mm)	MATERIAL
WEARING COURSE	40	SIZE 14 TYPE H ASPHALT (CLASS 320 BINDER)
INTERMEDIATE COURSE	75	SIZE 20 TYPE SI ASPHALT (CLASS 320 BINDER)
BASE COURSE	75	SIZE 20 TYPE SF ASPHALT (CLASS 320 BINDER)
SUBBASE	100	SIZE 20mm CLASS 3 CEMENT TREATED CRUSHED ROCK (3% CEMENT) E ℏ 500 MPa COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 96% (MODIFIED) MAXIMUM DRY DENSITY AS1289, 5.2.1
CAPPING LAYER	150	TYPE A MATERIAL COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES: CBR ℏ 8%, SWELL ℍ1.5%, PERMEABILITY K ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
CONSTRUCTION LAYER	170 (MINIMUM)	CONSTRUCTION LAYER COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES : CBR ℏ 8%, SWELL ℍ1.5% AND PERMEABILITY ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
TOTAL	610	MINIMUM COVER IN ACCORDANCE WITH VICROADS RC500.22 FIGURE 5.1
SUBGRADE	-	(CLAY) TOP 200mm COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1

PAVEMENT COMPOSITION TYPE 4
KARNAK LANE, OZENKADNOOK WAY


LAYER	THICKNESS (mm)	MATERIAL
WEARING COURSE	-	EXPOSED AGGREGATE FINISH
BASE COURSE	200	CONCRETE 32MPa WITH TWO SHEETS OF SL82 MESH REINFORCEMENT WITH 50mm TOP COVER AS PER STANDARD DRAWING MCC 504
SUBBASE	100	SIZE 20mm CLASS 3 CRUSHED ROCK COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (MODIFIED) MAXIMUM DRY DENSITY AS1289,5.2.1
CAPPING LAYER	150	TYPE A MATERIAL COMPLYING WITH THE FOLLOWING MATERIAL PROPERTIES: CBR ℏ 8%, SWELL ℍ1.5%, PERMEABILITY K ℍ5 x 10^{-9} m/s. COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1
TOTAL	450	
SUBGRADE	-	(CLAY) TOP 200mm COMPACTED TO A MINIMUM CHARACTERISTIC DENSITY RATIO OF 98% (STANDARD) MAXIMUM DRY DENSITY AS1289, 5.1.1



PAVEMENT COMPOSITION TYPE 1

NOT TO SCALE

(TO BE CONSTRUCTED AS PER EDCM 202A)



PLAN

SCALE 1 : 750

LEGEND

- STAGE BOUNDARY
- PROPOSED KERB & CHANNEL
- PROPOSED ROAD PAVEMENT TYPE 1
- PROPOSED ROAD PAVEMENT TYPE 2
- PROPOSED ROAD PAVEMENT TYPE 3
- PROPOSED ROAD PAVEMENT TYPE 4
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- MUNICIPAL BOUNDARY

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 15 30 45 60 75m

1 : 750

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL

NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP

STAGE 22A

CITY OF MELTON

Title

PAVEMENT PLAN


SHEET 1

ARCADIS


Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0281	04


Date Plotted: 27 Jul 2023 - 04:24pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0280-TypicalDetails.dwg V1




PLAN
SCALE 1 : 500




PAVEMENT COMPOSITION TYPE 2
NOT TO SCALE
(TO BE CONSTRUCTED AS PER EDCM 202A)



PAVEMENT COMPOSITION TYPE 3
NOT TO SCALE
(TO BE CONSTRUCTED AS PER EDCM 202A)



PAVEMENT COMPOSITION TYPE 4
NOT TO SCALE



PAVEMENT COMPOSITION TYPE 3 WITH PARKING BAYS
NOT TO SCALE

NOTE:
REFER TO EDCM 202A FOR STANDARD SUBSURFACE DRAIN DETAIL FOR EXPANSIVE SUBGRADE.

LEGEND

- STAGE BOUNDARY
- PROPOSED KERB & CHANNEL
- PROPOSED ROAD PAVEMENT TYPE 1
- PROPOSED ROAD PAVEMENT TYPE 2
- PROPOSED ROAD PAVEMENT TYPE 3
- PROPOSED ROAD PAVEMENT TYPE 4
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- LONGITUDINAL TIED JOINT (LJ)
- ISOLATION JOINT (IJ)
- TRANSVERSE JOINT (TJ)
- TIED CONSTRUCTION JOINT (CJ)

NOTES:

1. DOWEL BAR DIAMETER, LENGTH AND SPACING SHALL BE AS SPECIFIED IN THE SCHEDULE OF DETAILS.
   a) TRANSVERSE CONTRACTION JOINTS SPACED AT 8-12m (N28 450mm LONG DOWEL BARS SPACED AT 300mm CENTRES)
   b) LONGITUDINAL TIE BARS SPACED AT 3-4.5m (N12 DEFORMED STEEL BARS 1m LONG)
   c) ISOLATION JOINTS AT PITS & INTERSECTING ROAD PAVEMENTS
2. JOINTS INTO VEHICLE CROSSOVERS TO BE TIED CONSTRUCTION JOINTS
3. DOWELS SHALL BE:
   - SECURELY POSITIONED PARALLEL TO PAVEMENT CENTERLINE AND FINISHED SURFACE
   - PART COATED AS SHOWN WITH APPROVED BOND BREAKING MATERIAL
4. TIE BARS SHALL BE SECURELY POSITIONED PARALLEL TO PAVEMENT CENTERLINE AND FINISHED SURFACE.
5. STEEL FABRIC SHALL BE LOCATED IN THE TOP THIRD OF THE BASE AND SHALL HAVE A MINIMUM COVER OF 50mm. REFER TO SPECIFICATIONS FOR DETAILS OD STEEL FABRIC.
6. SUBBASE AND BASE TRANSVERSE JOINTS SHALL BE OFFSET BY A MINIMUM OF 500mm.
7. TIED CONSTRUCTION JOINTS SHALL BE LOCATED IN THE MIDDLE THIRD OF THE SLAB LENGTH AND AT LEAST 1.5m FROM TRANSVERSE CONTRACTION JOINTS.
8. DOWEL CAP MAY BE OMITTED FOR SHORT SLAB (<5m) CONTRACTION JOINTS.
9. SFRC IS STEEL FIBRE REINFORCE CONCRETE.
10. TIE BAR SHALL NOT BE PLACE WITHIN 500mm OF A TRANSVERSE CONTRACTION JOINT.
11. REINFORCEMENT FOR JOINTED AND CONTINUOUSLY REINFORCED PAVEMENTS IS NOT SHOWN REFER TO SCHEDULE OF DETAILS.
12. SUBBASE AND BASE LONGITUDINAL JOINTS SHALL BE OFFSET BY NOT LESS THAN 250mm BUT NOT MORE THAN 300mm.
13. SAME DIMENSIONS FOR STEEL FIBRE REINFORCED CONCRETE.
14. KERN AND CHANNEL TIED JOINT:
    IF KERB AND CHANNEL AND BASE ARE CAST SIMULTANEOUSLY, TIE BARS ARE NOT REQUIRED BETWEEN THEM. THE PAVEMENT REINFORCEMENT SHALL BE EXTENDED INTO THE KERB AND CHANNEL AND THE BACK OF KERB IS THE EDGE OF PAVEMENT.
15. BACKING ROD SHALL BE MADE OF POLYETHELENE FOAM OR APPROVED EQUIVALENT. ALTERNATIVE MATERIAL AND SHAPE MAY BE APPROVED.
16. AN APPROVED NEOPRENE COMPRESSION SEAL CONFORMING TO ASTM D2628 MAY BE USED INSTEAD OF A FIELD MOULDED SEALANT AND BACKING ROD.
17. AN APPROVED SEALANT SHALL BE INSTALLED ALONG THE TOP AND DOWN THE VERTICAL EDGES OF THE EXPANSION JOINT.
18. REINFORCEMENT SHALL BE LOCATED IN THE TOP THIRD OF THE BASE AND SHALL HAVE A MINIMUM COVER OF 50mm.
19. RECTANGULAR MESH SHALL BE ALIGNED WITH THE CLOSER SPACED WIRES PARALLEL TO THE PAVEMENT CENTERLINE.
20. ALL PAVEMENT DESIGNS HAVE BEEN PROVIDED BY TONKIN AND TAYLOR. ARCADIS ARE NOT RESPONSIBLE FOR THE DESIGN OF THE PAVEMENTS WITHIN THIS STAGE OF WORKS. THE PAVEMENT COMPOSITIONS HAVE BEEN EXTRACTED FROM THE PAVEMENT REPORT FOR THIS STAGE OF WORKS. THE CONTRACTOR SHOULD REVIEW THIS DOCUMENT IN CONJUNCTION WITH THE GEOTECHNICAL AND PAVEMENT REPORTS PROVIDED BY TONKIN AND TAYLOR.
21. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales
0 10 20 30 40 50m
1 : 500

Planner
RobertsDay planning·design·place

Client
RESIMAX GROUP

Status
FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		


Project
EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title
PAVEMENT PLAN
SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone / Stage / Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0282	04

REFER TO DRAWING DRG-0291 FOR CONTINUATION



LEGEND

- CONTINUOUS LANE LINE (LL) — 100
- CONTINUITY LINE (CL) — 1000, 3000 — 200
- GIVE WAY LINE (GL) — 600, 600 — 300
- RAISED REFLECTIVE PAVEMENT MARKER
- SIGN POST
- CHEVRON — 100, 100, 100, 100 — 5000 — 1000

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-002.

Issue	Description	DR	CH	VE	Date
03	RESPONSE TO COUNCIL RFI	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON


Title

SIGNAGE AND LINEMARKING
PLAN SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0290	03

Date Plotted: 27 Jul 2023 - 04:37pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0290-Sign&Linemarking.dwg V1



LEGEND

- 100 — CONTINUOUS LANE LINE (LL)
- 1000 / 3000 — 200 — CONTINUITY LINE (CL)
- 600 / 600 — 300 — GIVE WAY LINE (GL)
- RAISED REFLECTIVE PAVEMENT MARKER
- SIGN POST
- 100 / 100 — CHEVRON
- 100 / 100
- 5000 / 1000

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-002.

REFER TO DRAWING DRG-0290 FOR CONTINUATION

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

N

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

SIGNAGE AND LINEMARKING
PLAN SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0291	04


Date Plotted: 27 Jul 2023 - 05:05pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0290-Sign&Linemarking.dwg V1

NOTES:

1. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.
2. PIPE TRENCHES WITHIN THE ROAD RESERVE MUST BE BACKFILLED WITH 20mm CLASS 3 CRUSHED ROCK TO BE COMPACTED TO A DRY DENTSITY NOT LESS THAN 97% OF MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING:
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE PAVEMENT OF CROSSOVER
   - ADJACENT TO KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE
3. ALL DRAINAGE PIPES TO BE RUBBER RING BELLED SOCKET JOINT TYPE (RRJ) UNLESS NOTED OTHERWISE.
4. ALL DRAINAGE PIPES SHALL BE CLASS 2 RCP, UNLESS OTHERWISE NOTED.
5. WHERE PITS DROP LESS THAN 50mm THE PIT FLOOR MUST BE SHAPED TO MATCH THE LOWER HALF OF THE PIPE.
6. ELECTRICITY LV, GAS AND TELECOMMUNICATION SERVICES CROSSINGS ARE NOT SHOWN FOR CLARITY. REFER RELEVANT DESIGN PACKAGE FOR CROSSING LOCATIONS, MINIMUM CLEARANCES AND COVER REQUIREMENTS.

LEGEND

CRUSHED ROCK BACKFILL



LINE AZ


| | | |

NOTES:

1. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.
2. PIPE TRENCHES WITHIN THE ROAD RESERVE MUST BE BACKFILLED WITH 20mm CLASS 3 CRUSHED ROCK TO BE COMPACTED TO A DRY DENTSITY NOT LESS THAN 97% OF MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING:
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE PAVEMENT OF CROSSOVER
   - ADJACENT TO KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE
3. ALL DRAINAGE PIPES TO BE RUBBER RING BELLED SOCKET JOINT TYPE (RRJ) UNLESS NOTED OTHERWISE.
4. ALL DRAINAGE PIPES SHALL BE CLASS 2 RCP, UNLESS OTHERWISE NOTED.
5. WHERE PITS DROP LESS THAN 50mm THE PIT FLOOR MUST BE SHAPED TO MATCH THE LOWER HALF OF THE PIPE.
6. ELECTRICITY LV, GAS AND TELECOMMUNICATION SERVICES CROSSINGS ARE NOT SHOWN FOR CLARITY. REFER RELEVANT DESIGN PACKAGE FOR CROSSING LOCATIONS, MINIMUM CLEARANCES AND COVER REQUIREMENTS.

LEGEND

CRUSHED ROCK BACKFILL




| | | |

NOTES:

1. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.
2. PIPE TRENCHES WITHIN THE ROAD RESERVE MUST BE BACKFILLED WITH 20mm CLASS 3 CRUSHED ROCK TO BE COMPACTED TO A DRY DENTSITY NOT LESS THAN 97% OF MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING:
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE PAVEMENT OF CROSSOVER
   - ADJACENT TO KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE
3. ALL DRAINAGE PIPES TO BE RUBBER RING BELLED SOCKET JOINT TYPE (RRJ) UNLESS NOTED OTHERWISE.
4. ALL DRAINAGE PIPES SHALL BE CLASS 2 RCP, UNLESS OTHERWISE NOTED.
5. WHERE PITS DROP LESS THAN 50mm THE PIT FLOOR MUST BE SHAPED TO MATCH THE LOWER HALF OF THE PIPE.
6. ELECTRICITY LV, GAS AND TELECOMMUNICATION SERVICES CROSSINGS ARE NOT SHOWN FOR CLARITY. REFER RELEVANT DESIGN PACKAGE FOR CROSSING LOCATIONS, MINIMUM CLEARANCES AND COVER REQUIREMENTS.

LEGEND

CRUSHED ROCK BACKFILL




| | | |

NOTES:

1. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.
2. PIPE TRENCHES WITHIN THE ROAD RESERVE MUST BE BACKFILLED WITH 20mm CLASS 3 CRUSHED ROCK TO BE COMPACTED TO A DRY DENTSITY NOT LESS THAN 97% OF MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING:
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE PAVEMENT OF CROSSOVER
   - ADJACENT TO KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE
3. ALL DRAINAGE PIPES TO BE RUBBER RING BELLED SOCKET JOINT TYPE (RRJ) UNLESS NOTED OTHERWISE.
4. ALL DRAINAGE PIPES SHALL BE CLASS 2 RCP, UNLESS OTHERWISE NOTED.
5. WHERE PITS DROP LESS THAN 50mm THE PIT FLOOR MUST BE SHAPED TO MATCH THE LOWER HALF OF THE PIPE.
6. ELECTRICITY LV, GAS AND TELECOMMUNICATION SERVICES CROSSINGS ARE NOT SHOWN FOR CLARITY. REFER RELEVANT DESIGN PACKAGE FOR CROSSING LOCATIONS, MINIMUM CLEARANCES AND COVER REQUIREMENTS.

LEGEND

CRUSHED ROCK BACKFILL




| | | |

NOTES:

1. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.
2. PIPE TRENCHES WITHIN THE ROAD RESERVE MUST BE BACKFILLED WITH 20mm CLASS 3 CRUSHED ROCK TO BE COMPACTED TO A DRY DENTSITY NOT LESS THAN 97% OF MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING:
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE PAVEMENT OF CROSSOVER
   - ADJACENT TO KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE
3. ALL DRAINAGE PIPES TO BE RUBBER RING BELLED SOCKET JOINT TYPE (RRJ) UNLESS NOTED OTHERWISE.
4. ALL DRAINAGE PIPES SHALL BE CLASS 2 RCP, UNLESS OTHERWISE NOTED.
5. WHERE PITS DROP LESS THAN 50mm THE PIT FLOOR MUST BE SHAPED TO MATCH THE LOWER HALF OF THE PIPE.
6. ELECTRICITY LV, GAS AND TELECOMMUNICATION SERVICES CROSSINGS ARE NOT SHOWN FOR CLARITY. REFER RELEVANT DESIGN PACKAGE FOR CROSSING LOCATIONS, MINIMUM CLEARANCES AND COVER REQUIREMENTS.

LEGEND

CRUSHED ROCK BACKFILL




| | | |

NOTES:

1. REFER TO SHEET DRG-0002 FOR GENERAL NOTES.
2. PIPE TRENCHES WITHIN THE ROAD RESERVE MUST BE BACKFILLED WITH 20mm CLASS 3 CRUSHED ROCK TO BE COMPACTED TO A DRY DENTSITY NOT LESS THAN 97% OF MAXIMUM FOUND IN THE STANDARD COMPACTION TEST FOR THE FOLLOWING:
   - BENEATH THE ROAD PAVEMENT OR DRIVEWAY CROSSOVER TO THE UNDERSIDE OF THE PAVEMENT OF CROSSOVER
   - ADJACENT TO KERBING OR CONCRETE WORKS TO A LEVEL THAT IS NOT AFFECTED BY A 45 DEGREE ANGLE OR REPOSE FROM NEAR THE LOWER EDGE
3. ALL DRAINAGE PIPES TO BE RUBBER RING BELLED SOCKET JOINT TYPE (RRJ) UNLESS NOTED OTHERWISE.
4. ALL DRAINAGE PIPES SHALL BE CLASS 2 RCP, UNLESS OTHERWISE NOTED.
5. WHERE PITS DROP LESS THAN 50mm THE PIT FLOOR MUST BE SHAPED TO MATCH THE LOWER HALF OF THE PIPE.
6. ELECTRICITY LV, GAS AND TELECOMMUNICATION SERVICES CROSSINGS ARE NOT SHOWN FOR CLARITY. REFER RELEVANT DESIGN PACKAGE FOR CROSSING LOCATIONS, MINIMUM CLEARANCES AND COVER REQUIREMENTS.

LEGEND

CRUSHED ROCK BACKFILL



| | | |

PIT SCHEDULE

Pit		INTERNAL		INLET		OUTLET		PIT		Standard Drawing	REMARKS
Name	TYPE	WD	LEN	DIA	INV LEV	DIA	INV LEV	SETOUT RL	DEPTH		
AA01	HEADWALL						94.600	95.800	1.200	REFER DRAWING DRG-280 FOR OUTLET DETAIL	TWIN DIA 1200mm HEADWALL
AY02	JUNCTION PIT HAUNCHED	1.05	2.4	825	95.214	(2x)600	95.164	98.917	3.754	EDCM 607	
AY03	GRATED PIT	0.9	0.9	825	95.351	825	95.301	98.119	2.817	IDM SD 455	CLASS D HEAVY DUTY V GRATE
				375	96.932						
AY04	GRATED PIT	0.9	0.9	825	95.468	825	95.418	97.933	2.515	IDM SD 455	CLASS D HEAVY DUTY V GRATE
AZ01	SIDE ENTRY PIT GRATED HAUNCHED	1.8	1.2	1050	94.735	1200	94.685	98.499	3.815	EDCM 601 AND 607	
				750	94.451						
AZ03	JUNCTION PIT HAUNCHED	1.35	1.8	300	97.285	1050	94.901	98.643	3.742	EDCM 607	
				900	94.951						
AZ04	DOUBLE SIDE ENTRY PIT GRATED	0.6	0.9			300	97.371	98.651	1.281	EDCM 602 AND 605	
DA01	SIDE ENTRY PIT GRATED HAUNCHED	0.9	1.35	300	96.932	750	96.503	98.519	2.015	EDCM 601 AND 607	
				750	96.553						
DA02	SIDE ENTRY PIT GRATED HAUNCHED	0.6	1.5	750	96.680	750	96.630	98.738	2.108	EDCM 601 AND 607	
				375	97.105						
DA03	SIDE ENTRY PIT GRATED HAUNCHED	1.05	1.8	750	97.020	750	96.970	98.956	1.985	EDCM 601 AND 607	
DA04	SIDE ENTRY PIT GRATED HAUNCHED	1.05	0.9	750	97.420	750	97.370	99.372	2.003	EDCM 601 AND 607	
DA05	SIDE ENTRY PIT GRATED HAUNCHED	1.05	0.9	750	98.005	750	97.955	99.995	2.040	EDCM 601 AND 607	
DA06	SIDE ENTRY PIT GRATED HAUNCHED	1.05	0.9	750	98.353	750	98.303	100.652	2.348	EDCM 601 AND 607	
DA07	JUNCTION PIT HAUNCHED	1.05	0.9	750	98.513	750	98.463	100.840	2.377	EDCM 607	
DA08	JUNCTION PIT HAUNCHED	1.05	0.9	750	98.617	750	98.567	100.946	2.378	EDCM 607	
DA09	SIDE ENTRY PIT GRATED HAUNCHED	1.05	1.5	750	98.800	750	98.750	101.236	2.485	EDCM 601 AND 607	
				300	99.550						
DA10	DOUBLE SIDE ENTRY PIT GRATED HAUNCHED	0.6	1.8	750	98.917	750	98.867	101.394	2.527	EDCM 602 AND 607	
				300	99.717						
DA12	GRATED PIT HAUNCHED	1.2	0.9	750	99.067	750	99.017	100.961	1.944	EDCM 607	PIT WITH TEMPORARY 900X900 SURFACE INLET GRATE
DA11	DOUBLE SIDE ENTRY PIT GRATED	0.6	0.9			300	99.803	101.395	1.592	EDCM 602 AND 605	
DB01	JUNCTION PIT	0.6	0.6	300	98.820	300	98.770	99.918	1.148	EDCM 605	
DB02	JUNCTION PIT	0.6	0.6	300	99.365	300	99.315	100.500	1.185	EDCM 605	
DB03	JUNCTION PIT	0.6	0.6	225	100.285	300	100.210	101.350	1.140	EDCM 605	
DB04	JUNCTION PIT	0.6	0.6	225	100.356	225	100.306	101.384	1.078	EDCM 605	
				225	100.356						
DB06	JUNCTION PIT	0.6	0.6			225	100.507	101.380	0.873	EDCM 605	
DC01	SIDE ENTRY PIT GRATED	0.6	0.9	300	99.749	300	99.699	101.562	1.863	EDCM 601 AND 605	
DC02	SIDE ENTRY PIT GRATED	0.6	0.9			300	99.871	101.873	2.002	EDCM 601 AND 605	
DD01	SIDE ENTRY PIT GRATED	0.6	0.9	300	97.921	375	97.846	99.378	1.532	EDCM 601 AND 605	
DD02	SIDE ENTRY PIT GRATED	0.6	0.9	300	98.574	300	98.524	100.000	1.476	EDCM 601 AND 605	
DD03	SIDE ENTRY PIT GRATED	0.6	0.9			300	99.172	100.658	1.486	EDCM 601 AND 605	
EA01	DOUBLE SIDE ENTRY PIT GRATED HAUNCHED	1.8	0.9	900	94.993	900	94.993	98.456	3.464	EDCM 602 AND 607	
EA02	SIDE ENTRY PIT GRATED HAUNCHED	1.5	2.7	(2x)600	95.089	1050	95.039	98.720	3.680	EDCM 601 AND 607	
				600	96.664						
EA04	SIDE ENTRY PIT GRATED HAUNCHED	0.9	0.9	600	96.820	600	96.770	98.823	2.053	EDCM 601 AND 607	
				300	97.070						
				300	97.070						
EA05	SIDE ENTRY PIT GRATED HAUNCHED	0.9	0.9	600	97.180	600	97.130	99.210	2.080	EDCM 601 AND 607	
				300	97.430						
EA06	SIDE ENTRY PIT GRATED	0.6	0.9			300	97.513	99.214	1.701	EDCM 601 AND 605	
EA07	SIDE ENTRY PIT GRATED HAUNCHED	0.9	0.9	600	97.440	600	97.390	99.511	2.121	EDCM 601 AND 607	
				300	97.690						
EA08	SIDE ENTRY PIT GRATED	0.6	0.9			300	97.774	99.515	1.741	EDCM 601 AND 605	
EA09	SIDE ENTRY PIT GRATED HAUNCHED	0.9	0.9	600	97.587	600	97.537	99.672	2.135	EDCM 601 AND 607	
EA10	SIDE ENTRY PIT GRATED HAUNCHED	1.2	0.9	525	97.695	600	97.645	99.775	2.130	EDCM 601 AND 607	
EA11	SIDE ENTRY PIT GRATED HAUNCHED	0.9	1.2	525	97.924	525	97.874	99.958	2.084	EDCM 601 AND 607	
				300	98.099						
				300	98.099						
EA12	SIDE ENTRY PIT GRATED HAUNCHED	0.6	1.2	525	98.039	525	97.989	100.250	2.261	EDCM 601 AND 607	
EA13	GRATED PIT HAUNCHED	0.9	1.2	525	98.191	525	98.141	100.382	2.240	EDCM 607	
EA04A	SIDE ENTRY PIT GRATED	0.6	0.9			300	97.243	98.838	1.595	EDCM 601 AND 605	
EB01	JUNCTION PIT	0.6	0.6	300	97.793	300	97.743	99.455	1.711	EDCM 605	
EB02	JUNCTION PIT	0.6	0.6	300	98.852	300	98.802	100.088	1.286	EDCM 605	
EB03	JUNCTION PIT	0.6	0.6	225	99.480	300	99.430	100.699	1.269	EDCM 605	
EB04	JUNCTION PIT	0.6	0.6	225	99.639	225	99.589	101.001	1.412	EDCM 605	
				225	99.639						
EB05	JUNCTION PIT	0.6	0.6			225	100.040	101.251	1.211	EDCM 605	
EB06	JUNCTION PIT	0.6	0.6			225	99.774	100.600	0.826	EDCM 605	
EC03	DOUBLE SIDE ENTRY PIT GRATED	0.6	0.9			300	98.268	100.202	1.934	EDCM 602 AND 605	
FA03	GRATED PIT	0.9	0.9	375	97.017	375	96.967	98.237	1.271	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FA04	GRATED PIT	0.9	0.9	375	97.277	375	97.227	98.458	1.231	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FA05	GRATED PIT	0.6	0.9	300	97.597	375	97.522	98.715	1.193	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FA06	GRATED PIT	0.6	0.9	300	97.850	300	97.800	98.929	1.129	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FA07	GRATED PIT	0.6	0.6			300	98.037	99.125	1.088	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FB01	GRATED PIT	0.6	0.9	300	97.683	300	97.283	99.098	1.816	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FB02	GRATED PIT	0.6	0.9	300	98.037	300	97.987	99.412	1.425	IDM SD 455	CLASS D HEAVY DUTY V GRATE
FB03	JUNCTION PIT	0.6	0.6			300	98.568	99.850	1.283	EDCM 605	
MC05	SIDE ENTRY PIT GRATED	0.6	0.9	300	98.231	300	98.181	99.599	1.418	EDCM 601 AND 605	
MC06	SIDE ENTRY PIT GRATED	0.6	0.9			300	98.313	99.602	1.289	EDCM 601 AND 605	

NOTE:

1. ALL HAUNCHED PIT RISERS TO BE HAUNCHED TO 0.6m x 0.9m COVER AS PER EDCM STANDARD.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

STORMWATER DRAINAGE
PIT SCHEDULE

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0320	04

100mm on Original

Date Plotted: 17 Jul 2023 - 02:23pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0320-SWDPitSchedule.dwg V1

REFER TO DRAWING-0351 FOR CONTINUATION

FUTURE STAGE 22B

STAGE 22A

FUTURE STAGE 26

EXISTING STAGE 18C

EXISTING STAGE 18B

GOROKE STREET

CHERRYPOOL CRESCENT

KARNAK LANE

OZENKADNOOK WAY

GYMBOWEN AVENUE

MT MOUNT MARY ROAD

MURTOA CRESCENT

MOYRISK CLOSE

FUTURE NATURE RESERVE

ZUMSTEINS WALK
RESERVE NO.148

RESERVE NO.145

RESERVE NO. 146

RESERVE NO.147

RESERVE NO.149

RESERVE NO. 114

RESERVE NO. 115

RESERVE NO. 112

SUPERLOT S193

SUPERLOT MA-05
0.1538ha

SUPERLOT S195

TO EX. DRAIN, PART OF EX. MMR-03 WORKS

TO EX. DRAIN, PART OF EX. MMR-03 WORKS

DD-03
0.2360ha

DD-02(2)
0.0475ha

DD-03(2)
0.0412ha

DB-04
0.0421ha

DB-06
0.0888ha

CA-13(2)
0.0345ha

CA-14(2)
0.0835ha

DC-02(2)
0.0261ha

DC-01(2)
0.0149ha

DA-09(2)
0.0182ha

DA-11(2)
0.0748ha

DA-10(2)
0.0206ha

EC-02(2)
0.0340ha

EC-03(2)
0.0829ha

EC-01(2)
0.0169ha

DA-05(2)
0.0477ha

DA-06(2)
0.0435ha

EB-02
0.2666ha

EB-03
0.2380ha

EB-04
0.0351ha

EB-05
0.0724ha

EB-06
0.0752ha

EA-07
0.1932ha

EA-05(2)
0.0489ha

EA-06(2)
0.0540ha

EA-07(2)
0.0262ha

EA09
0.1462ha

EA-08(2)
0.0484ha

EA-09(2)
0.0377ha

EA-10(2)
0.0240ha

EA-11(2)
0.0164ha

EA-12(2)
0.0191ha

FA-04(2)
0.0455ha

FA-05
0.1404ha

FA-05(2)
0.0639ha

FA-06
0.1052ha

FA-06(2)
0.0387ha

FA-07
0.1321ha

FA-07(2)
0.0229ha

FB-02(2)
0.0288ha

FB-03
0.0981ha

FB-01(2)
0.0200ha

FB-02
0.1221ha

MA-04(3)
0.0280ha

MA-04
0.1848ha

MA-04(3)
0.0280ha

MA-07(3)
0.2038ha

MC-05(2)
0.0595ha

MC-06(2)
0.0628ha

CATCHMENT D201-D2(4)
LOT = 4.82 ha
ROAD = 2.6 ha
RESERVE = 0.55 ha
tc = 16min
ASSUMED AVERAGE C = 0.624
20% AEP FLOW = 0.687 m3/s

CATCHMENT E201-E2(4)
LOT = 1.88 ha
ROAD = 1.01 ha
RESERVE = 0 ha
tc = 11min
ASSUMED AVERAGE C = 0.647
20% AEP FLOW = 0.301 m3/s

LEGEND

- EXISTING SURFACE CONTOURS
- PROPOSED SURFACE CONTOURS
- PROPOSED STORMWATER DRAINAGE
- A-20 PROPOSED PIT LABEL
- EXISTING STORMWATER DRAINAGE
- FUTSWD FUTURE STORMWATER DRAINAGE
- PROPOSED CATCHMENT BOUNDARY
- PROPOSED RIDGE LINE
- A-20(2) 0.0519ha CATCHMENT LABEL AND AREA

NOTE:

FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.

AVERAGE CATCHMENT COEFFICIENTS OF RUNOFF STAGE 22A & 22B - 20% AEP

ROAD RESERVE	0.602
LOTS	0.751
OPEN SPACE RESERVE	0.304

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	HA	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	KR	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

100mm on Original

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: STORMWATER DRAINAGE 20% AEP CATCHMENT PLAN
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0350	04

Date Plotted: 18 Jul 2023 - 10:18am File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0350-Q5Catchment.dwg V1

INSET - A

FUTURE STAGE 22E

FUTURE WETLAND RESERVE

FUTURE STAGE 22B

EXISTING STAGE 18D

BUNGALALLY WALK

CHERRYPOOL CRESCENT

GOROKE STREET

KARNAK LANE

MOUNT MARY ROAD

CALLAWADDA DRIVE

EXTENDED DRIVEWAY

BALQUHIDDER

STREET

TO EX. DRAIN, PART OF EX. MMR-03 WORKS

RESERVE NO. 117

RESERVE NO. 114

SUPERLOT S196

SUPERLOT S193

RESERVE NO.151

EA-01(2) 0.0436ha

EA-02(2) 0.0160ha

EB-02 0.2666ha

DA-04(2) 0.0431ha

DD-01(2) 0.0414ha

EA-05 0.1486ha

EA-04(2) 0.0626ha

EA-04A(2) 0.0596ha

AZ-04(2) 0.0570ha

AY-03 0.0964ha

AY-04 0.0944ha

AY-03(2) 0.0331ha

AY-04(2) 0.0222ha

FA-03 0.0348ha

FA-04 0.1408ha

FA-03(2) 0.0414ha

FA-04(2) 0.0455ha

MA-03 0.1846ha

REFER INSET - A

REFER TO DRAWING-0350 FOR CONTINUATION

LEGEND

- EXISTING SURFACE CONTOURS
- PROPOSED SURFACE CONTOURS
- PROPOSED STORMWATER DRAINAGE
- PROPOSED PIT LABEL
- EXISTING STORMWATER DRAINAGE
- FUTURE STORMWATER DRAINAGE
- PROPOSED CATCHMENT BOUNDARY
- PROPOSED RIDGE LINE
- A-20(2) 0.0519ha — CATCHMENT LABEL AND AREA

NOTE:

FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.

AVERAGE CATCHMENT COEFFICIENTS OF RUNOFF STAGE 22A & 22B - 20% AEP

ROAD RESERVE	0.602
LOTS	0.751
OPEN SPACE RESERVE	0.304

Issue	Description	DR	CH	VE	Date
03	RESPONSE TO COUNCIL RFI	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

100mm on Original

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: STORMWATER DRAINAGE 20% AEP CATCHMENT PLAN SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0351	03

Date Plotted: 18 Jul 2023 - 10:33am File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0350-Q5Catchment.dwg V1

REFER TO DRAWING-0353 FOR CONTINUATION

FUTURE STAGE 22B

STAGE 22A

FUTURE STAGE 26

EXISTING STAGE 18C

EXISTING STAGE 18B

CATCHMENT D1
LOT: 1.700ha
ROAD: 1.200ha
RESERVE: 0.000ha

CATCHMENT E1
LOT: 1.170ha
ROAD: 0.540ha
RESERVE: 0.000ha

CATCHMENT F1
LOT: 0.540ha
ROAD: 0.280ha
MISC: 0.000ha

CATCHMENT F3
LOT: 0.243ha
ROAD: 0.040ha
MISC: 0.000ha

CATCHMENT MMR3 (WEST)
LOT: 0.550ha
ROAD: 1.240ha
MISC: 0.210ha

CATCHMENT MMR3 (EAST)
LOT: 0.000ha
ROAD: 1.756ha
MISC: 0.000ha

EXTERNAL CATCHMENT D2
LOT: 5.065ha
ROAD: 2.150ha
MISC: 0.588ha

EXTERNAL CATCHMENT E2
LOT: 2.140ha
ROAD: 0.669ha
MISC: 0.081ha

EXTERNAL CATCHMENT G1
LOT: 3.473ha
ROAD: 0.999ha
MISC: 1.140ha

GOROKE STREET
CHERRYPOOL CRESCENT
OZENKADNOOK WAY
KARNAK LANE
GYMBOWEN AVENUE
ZUMSTEINS WALK
MOUNT MARY ROAD
MOYREISK CLOSE
MURTOA CRESCENT

SUPERLOT S193
SUPERLOT S194
SUPERLOT S195

RESERVE NO.145
RESERVE NO. 146
RESERVE NO.147
RESERVE NO.148
RESERVE NO.149
RESERVE NO. 114
RESERVE NO. 115
RESERVE NO. 112

FUTURE NATURE RESERVE

LEGEND

- STAGE BOUNDARY
- EXISTING SURFACE CONTOURS
- PROPOSED SURFACE CONTOURS
- PROPOSED STORMWATER DRAINAGE
- A-20 PROPOSED PIT LABEL
- EXISTING STORMWATER DRAINAGE
- FUTURE STORMWATER DRAINAGE
- PROPOSED CATCHMENT BOUNDARY
- PROPOSED RIDGE LINE
- CATCHMENT 1 / LOT: 1.0 ha / RR: 1.0 ha / MISC: 0.0 ha — CATCHMENT LABEL AND AREA
- 10 — STORMWATER NODES

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. UPSTREAM CATCHMENT CALCULATION OUTSIDE OF STAGE 22 ARE ASSUMED BASED ON CURRENT CONCEPT MASTER PLAN.

AVERAGE CATCHMENT COEFFICIENTS OF RUNOFF STAGE 22A & 22B - 1% AEP

ROAD RESERVE	0.602
LOTS	0.751
OPEN SPACE RESERVES	0.304

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

100mm on Original

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: STORMWATER DRAINAGE 1% AEP CATCHMENT PLAN
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone	Stage	Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD			CV	DRG	0352	04

Date Plotted: 18 Jul 2023 - 11:24am File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0352-Q100Catchment.dwg V1

INSET - A

FUTURE STAGE 22E

FUTURE WETLAND RESERVE

REFER INSET - A

BUNGALALLY WALK

CHERRYPOOL CRESCENT

CHERRYPOOL CRESCENT

STREET

CATCHMENT E0
LOT: 0.150ha
ROAD: 0.130ha
MISC: 0.000ha

CATCHMENT F2
LOT: 0.200ha
ROAD: 0.000ha
MISC: 0.000ha

SUPERLOT S196

RESERVE NO.15

CATCHMENT D1
LOT: 1.700ha
ROAD: 1.200ha
RESERVE: 0.000ha

KARNAK LANE

MOUNT MARY ROAD

CALLAWADDA DRIVE

EXISTING STAGE 18D

FUTURE STAGE 22B

GOROKE STREET

CATCHMENT E1
LOT: 1.170ha
ROAD: 0.540ha
RESERVE: 0.000ha

KARNAK LANE

CHERRYPOOL CRESCENT

STAGE 22A

CATCHMENT F1
LOT: 0.540ha
ROAD: 0.280ha
MISC: 0.000ha

CATCHMENT MMR3 (EAST)
LOT: 0.000ha
ROAD: 1.756ha
MISC: 0.000ha

CATCHMENT MMR3 (WEST)
LOT: 0.550ha
ROAD: 1.240ha
MISC: 0.210ha

EXTENDED DRIVEWAY

BALQUHIDDER

RESERVE NO. 117

RESERVE NO. 114

SUPERLOT S193

REFER TO DRAWING-0352 FOR CONTINUATION

LEGEND

- STAGE BOUNDARY
- EXISTING SURFACE CONTOURS
- PROPOSED SURFACE CONTOURS
- PROPOSED STORMWATER DRAINAGE
- A-20 PROPOSED PIT LABEL
- EXISTING STORMWATER DRAINAGE
- FUTURE STORMWATER DRAINAGE
- PROPOSED CATCHMENT BOUNDARY
- PROPOSED RIDGE LINE
- CATCHMENT 1 / LOT: 1.0 ha / RR: 1.0 ha / MISC: 0.0 ha — CATCHMENT LABEL AND AREA
- 10 — STORMWATER NODES

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. UPSTREAM CATCHMENT CALCULATION OUTSIDE OF STAGE 22 ARE ASSUMED BASED ON CURRENT CONCEPT MASTER PLAN.

AVERAGE CATCHMENT COEFFICIENTS OF RUNOFF STAGE 22A & 22B - 1% AEP

ROAD RESERVE	0.602
LOTS	0.751
OPEN SPACE RESERVES	0.304

Issue	Description	DR	CH	VE	Date
03	RESPONSE TO COUNCIL RFI	CM	CS	IOC	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 10 20 30 40 50m

1 : 500

100mm on Original

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

© Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		


Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: STORMWATER DRAINAGE 1% AEP CATCHMENT PLAN
SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone / Stage / Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0353	03

Date Plotted: 18 Jul 2023 - 11:32am File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0352-Q100Catchment.dwg V1



LEGEND

- 5.0 — EXISTING SURFACE CONTOURS
- 5.0 — PROPOSED SURFACE CONTOURS
- SWD — PROPOSED STORMWATER DRAINAGE
- A-20 — PROPOSED PIT LABEL
- SWD — EXISTING STORMWATER DRAINAGE
- FUTSWD — FUTURE STORMWATER DRAINAGE
- PROPOSED CATCHMENT BOUNDARY
- PROPOSED RIDGE LINE
- A-20(2) 0.0519ha — CATCHMENT LABEL AND AREA

NOTE:

FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.

AVERAGE CATCHMENT COEFFICIENTS OF RUNOFF STAGE 22A & 22B - 20% AEP

ROAD RESERVE	0.602
LOTS	0.751
OPEN SPACE RESERVE	0.304

Issue	Description	DR	CH	VE	Date
02	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
01	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23

Scales

0 500 1000 1500 2000m

1 : 20000

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title


STORMWATER DRAINAGE 20% AEP
OVERALL CATCHMENT PLAN

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0354	02

100mm on Original

Date Plotted: 27 Jul 2023 - 04:51pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0354-Q5Overall_Catchment.dwg V1



LEGEND

- STAGE BOUNDARY
- EXISTING SURFACE CONTOURS (5.0)
- PROPOSED SURFACE CONTOURS (5.0)
- PROPOSED STORMWATER DRAINAGE (SWD)
- PROPOSED PIT LABEL (A-20)
- EXISTING STORMWATER DRAINAGE (SWD)
- FUTURE STORMWATER DRAINAGE (FUTSWD)
- PROPOSED CATCHMENT BOUNDARY
- PROPOSED RIDGE LINE
- CATCHMENT LABEL AND AREA (CATCHMENT 1 — LOT: 1.0 ha, RR: 1.0 ha, MISC: 0.0 ha)
- STORMWATER NODES (10)

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. UPSTREAM CATCHMENT CALCULATION OUTSIDE OF STAGE 22 ARE ASSUMED BASED ON CURRENT CONCEPT MASTER PLAN.

AVERAGE CATCHMENT COEFFICIENTS OF RUNOFF STAGE 22A & 22B - 1% AEP

ROAD RESERVE	0.602
LOTS	0.751
OPEN SPACE RESERVES	0.304

Issue	Description	DR	CH	VE	Date
02	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
01	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23

Scales

0 50 100 150 200m

1 : 2000

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: STORMWATER DRAINAGE 1% AEP
OVERALL CATCHMENT PLAN

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0356	02

100mm on Original

Date Plotted: 27 Jul 2023 - 04:46pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0356-Q100Overall_Catchment.dwg V1

20% AEP HYDROLOGICAL DESIGN SHEET

Node Name	Pit Type	Setout RL	Grate RL	Catch ID	Time Tc	Intensity I	Runoff C	Area A	Full CA	Full Sum CA	Full Qc=CIA	Partial CA	Partial Sum CA	Partial Qc=CIA	Approach Flow Qa
(-)	(-)	(m)	(m)	(-)	(min)	(mm/hr)	(-)	(ha)	(ha)	(ha)	(L/s)	(ha)	(ha)	(L/s)	(L/s)
AY02	VIC GAA JP HAUNCHED	98.92	98.92												0
AY03	VIC SURFACE GP 900x900	98.12	98.12	1P	5	76.8	0.75	0.0964	0.0724	0.0923	18.5	0.0724	0.089	19	19
				2P	6	72.3	0.6	0.0331	0.02			0.0166			
AY04	VIC SURFACE GP 900x900	97.93	97.93	1P	5	76.8	0.75	0.0944	0.0709	0.0843	16.9	0.0709	0.0821	17.5	17.5
				2P	6	72.3	0.6	0.0222	0.0134			0.0111			
AA01	HW OUT	95.8	95.8												
AZ01	VIC GAA SEP G HAUNCHED	98.5	98.39	2P	6	72.3	0.6	0.0225	0.0136	0.0136	2.7	0.0136	0.0136	2.7	2.7
AZ03	VIC GAA JP HAUNCHED	98.64	98.53												0
AZ04	VIC GAA DSEP G 600x900	98.65	98.5	2P	6	72.3	0.6	0.057	0.0343	0.0343	6.9	0.0343	0.0343	6.9	6.9
DA01	VIC GAA SEP G HAUNCHED	98.52	98.4	1P	5	76.8	0.75	0.0468	0.0352	0.0596	12	0.0352	0.0555	11.8	12
				2P	6	72.3	0.6	0.0406	0.0245			0.0204			
DA02	VIC GAA SEP G HAUNCHED	98.74	98.62	2P	6	72.3	0.6	0.0198	0.0119	0.0119	2.4	0.0119	0.0119	2.4	2.4
DA03	VIC GAA SEP G HAUNCHED	98.96	98.84	2P	6	72.3	0.6	0.0133	0.008	0.008	1.6	0.008	0.008	1.6	1.6
DA04	VIC GAA SEP G HAUNCHED	99.37	99.26	2P	6	72.3	0.6	0.0431	0.026	0.026	5.2	0.026	0.026	5.2	5.2
DA05	VIC GAA SEP G HAUNCHED	99.99	99.88	2P	6	72.3	0.6	0.0477	0.0287	0.0287	5.8	0.0287	0.0287	5.8	5.8
DA06	VIC GAA SEP G HAUNCHED	100.65	100.54	2P	6	72.3	0.6	0.0435	0.0262	0.0262	5.3	0.0262	0.0262	5.3	5.3
DA07	VIC GAA JP HAUNCHED	100.84	100.72												
DA08	VIC GAA JP HAUNCHED	100.95	100.83												0
DA09	VIC GAA SEP G HAUNCHED	101.24	101.12	2P	6	72.3	0.6	0.0182	0.0109	0.0109	2.2	0.0109	0.0109	2.2	2.2
DA10	VIC GAA DSEP G HAUNCHED	101.39	101.27	2P	6	72.3	0.6	0.0206	0.0124	0.0124	2.5	0.0124	0.0124	2.5	2.5
DA12	VIC SURFACE GP HAUNCHED	100.96	100.6												0
DA13	Stub Connection	100.62	100.62												0
DA11	VIC GAA DSEP G 600x900	101.39	101.27	2P	6	72.3	0.6	0.0748	0.045	0.045	9	0.045	0.045	9	9
DB01	VIC GAA JP 600x600	99.92	99.8												0
DB02	VIC GAA JP 600x600	100.5	100.23	1P	5	76.8	0.75	0.174	0.1307	0.1307	27.9	0.1307	0.1307	27.9	27.9
DB03	VIC GAA JP 600x600	101.35	100.87	1P	5	76.8	0.75	0.1485	0.1115	0.1115	23.8	0.1115	0.1115	23.8	23.8
DB04	VIC GAA JP 600x600	101.38	100.92	1P	5	76.8	0.75	0.0421	0.0316	0.0316	6.7	0.0316	0.0316	6.7	6.7
DB05	VIC GAA JP 600x600	101.38	101.03	1P	5	76.8	0.75	0.0851	0.0639	0.0639	13.6	0.0639	0.0639	13.6	13.6
DB06	VIC GAA JP 600x600	101.38	100.83	1P	5	76.8	0.75	0.0888	0.0667	0.0667	14.2	0.0667	0.0667	14.2	14.2
DC01	VIC GAA SEP G 600x900	101.26	101.12	2P	6	72.3	0.6	0.0149	0.009	0.009	1.8	0.009	0.009	1.8	1.8
DC02	VIC GAA SEP G 600x900	101.53	101.41	2P	6	72.3	0.6	0.0261	0.0157	0.0157	3.2	0.0157	0.0157	3.2	3.2
DD01	VIC GAA SEP G 600x900	99.38	99.26	2P	6	72.3	0.6	0.0414	0.0249	0.0249	5	0.0249	0.0249	5	5
DD02	VIC GAA SEP G 600x900	100	99.88	1P	5	76.8	0.75	0.1276	0.0958	0.1244	25	0.0958	0.1197	25.5	25.5
				2P	6	72.3	0.6	0.0475	0.0286			0.0238			
DD03	VIC GAA SEP G 600x900	100.66	100.54	1P	5	76.8	0.75	0.236	0.1772	0.2021	40.6	0.1772	0.1979	42.2	42.2
				2P	6	72.3	0.6	0.0412	0.0248			0.0207			
EA01	VIC GAA DSEP G HAUNCHED	98.46	98.5	1P	5	76.8	0.75	0.0401	0.0301	0.0564	11.3	0.0301	0.052	11.1	11.3
				2P	6	72.3	0.6	0.0436	0.0263			0.0219			
EA02	VIC GAA SEP G HAUNCHED	98.72	98.61	2P	6	72.3	0.6	0.016	0.0096	0.0096	1.9	0.0096	0.0096	1.9	1.9
EA04	VIC GAA SEP G HAUNCHED	98.82	98.71	2P	6	72.3	0.6	0.0626	0.0377	0.0377	7.6	0.0377	0.0377	7.6	7.6
EA05	VIC GAA SEP G HAUNCHED	99.21	99.09	1P	5	76.8	0.75	0.1486	0.1116	0.141	28.3	0.1116	0.1361	29	29
				2P	6	72.3	0.6	0.0489	0.0294			0.0245			
EA07	VIC GAA SEP G HAUNCHED	99.51	99.39	1P	5	76.8	0.75	0.1932	0.1451	0.1609	32.3	0.1451	0.1583	33.8	33.8
				2P	6	72.3	0.6	0.0262	0.0158			0.0132			
EA09	VIC GAA SEP G HAUNCHED	99.67	99.55	1P	5	76.8	0.75	0.1462	0.1098	0.1325	26.6	0.1098	0.1287	27.5	27.5
				2P	6	72.3	0.6	0.0377	0.0227			0.0189			
EA10	VIC GAA SEP G HAUNCHED	99.78	99.66	2P	6	72.3	0.6	0.024	0.0144	0.0144	2.9	0.0144	0.0144	2.9	2.9
EA11	VIC GAA SEP G HAUNCHED	99.96	99.84	2P	6	72.3	0.6	0.0164	0.0099	0.0099	2	0.0099	0.0099	2	2
EA12	VIC GAA SEP G HAUNCHED	100.25	100.13	2P	6	72.3	0.6	0.0191	0.0115	0.0115	2.3	0.0115	0.0115	2.3	2.3
EA13	VIC SURFACE GP HAUNCHED	100.38	100.38												0
EA14	Stub Connection	100.39	100.39												0
EA04A	VIC GAA SEP G 600x900	98.84	98.72	2P	6	72.3	0.6	0.0596	0.0359	0.0359	7.2	0.0359	0.0359	7.2	7.2
EA08	VIC GAA SEP G 600x900	99.51	99.39	2P	6	72.3	0.6	0.0484	0.0291	0.0291	5.9	0.0291	0.0291	5.9	5.9
EA06	VIC GAA SEP G 600x900	99.21	99.09	2P	6	72.3	0.6	0.054	0.0325	0.0325	6.5	0.0325	0.0325	6.5	6.5
EB01	VIC GAA JP 600x600	99.45	99.45												0
EB02	VIC GAA JP 600x600	100.09	99.92	1P	5	76.8	0.75	0.2666	0.2002	0.2002	42.7	0.2002	0.2002	42.7	42.7
EB03	VIC GAA JP 600x600	100.7	100.39	1P	5	76.8	0.75	0.238	0.1788	0.1788	38.1	0.1788	0.1788	38.1	38.1
EB04	VIC GAA JP 600x600	101	100.59	1P	5	76.8	0.75	0.0351	0.0264	0.0264	5.6	0.0264	0.0264	5.6	5.6
EB05	VIC GAA JP 600x600	101.25	100.65	1P	5	76.8	0.75	0.0724	0.0544	0.0544	11.6	0.0544	0.0544	11.6	11.6
EB06	VIC GAA JP 600x600	100.6	100.41	1P	5	76.8	0.75	0.0752	0.0564	0.0564	12	0.0564	0.0564	12	12
EC01	VIC GAA SEP G 600x900	99.98	99.84	2P	6	72.3	0.6	0.0169	0.0102	0.0102	2	0.0102	0.0102	2	2
EC02	VIC GAA SEP G 600x900	100.53	100.41	2P	6	72.3	0.6	0.034	0.0205	0.0205	4.1	0.0205	0.0205	4.1	4.1
EC03	VIC GAA DSEP G 600x900	100.2	100.08	2P	6	72.3	0.6	0.0829	0.0499	0.0499	10	0.0499	0.0499	10	10
FA03	VIC SURFACE GP 900x900	98.24	98.24	1P	5	76.8	0.75	0.0348	0.0261	0.051	10.3	0.0261	0.0469	10	10.3
				2P	6	72.3	0.6	0.0414	0.0249			0.0208			
FA04	VIC SURFACE GP 900x900	98.46	98.46	1P	5	76.8	0.75	0.1408	0.1057	0.1331	26.7	0.1057	0.1286	27.4	27.4
				2P	6	72.3	0.6	0.0455	0.0274			0.0228			
FA05	VIC SURFACE GP 600x900	98.72	98.72	1P	5	76.8	0.75	0.1404	0.1054	0.1439	28.9	0.1054	0.1375	29.3	29.3
				2P	6	72.3	0.6	0.0639	0.0385			0.0321			
FA06	VIC SURFACE GP 600x900	98.93	98.93	1P	5	76.8	0.75	0.1052	0.079	0.1023	20.6	0.079	0.0984	21	21
				2P	6	72.3	0.6	0.0387	0.0233			0.0194			
FA07	VIC SURFACE GP 600x600	99.12	99.12	1P	5	76.8	0.75	0.1321	0.0992	0.113	22.7	0.0992	0.1107	23.6	23.6
				2P	6	72.3	0.6	0.0229	0.0138			0.0115			
FB01	VIC SURFACE GP 600x900	99.1	99.1	2P	6	72.3	0.6	0.02	0.012	0.012	2.4	0.012	0.012	2.4	2.4
FB02	VIC SURFACE GP 600x900	99.41	99.41	1P	5	76.8	0.75	0.1221	0.0917	0.109	21.9	0.0917	0.1061	22.6	22.6
				2P	6	72.3	0.6	0.0288	0.0174			0.0145			
FB03	VIC GAA JP 600x600	99.85	99.85	1P	5	76.8	0.75	0.0981	0.0737	0.0737	15.7	0.0737	0.0737	15.7	15.7
MA05	VIC GAA SEP G HAUNCHED	98.68	98.56	1P	5	76.8	0.75	0.1538	0.1155	0.1517	30.5	0.1155	0.1456	31.1	31.1
				2P	6	72.3	0.6	0.0601	0.0362			0.0301			
MA06	VIC GAA SEP G HAUNCHED	99	98.87	2P	6	72.3	0.6	0.0124	0.0075	0.0075	1.5	0.0075	0.0075	1.5	1.5

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title

STORMWATER DRAINAGE
CALCULATION TABLES
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0360	04

100mm on Original

20% AEP HYDRAULICS DESIGN SHEET

Pipe ID	Pipe Type	Pipe Length	Pipe Size	Full Pipe Area Af	Pipe Grade	Pipe Grade	Full-area Tct	Full-area I	Full-area Sum CA	Full-area Qc=CIA	Part-area Tct	Part-area I	Part-area Sum CA	Part-area Qc=CIA	Pipe Flow, Q	Capacity Flow Cap	Q/Qcap Ratio	Full Pipe Vel Vf=Q/Af	Norm Depth Vel Vn=Q/An	Critical Depth Vel Vc=Q/Ac	Capacity Vel Vcap=Qcap/Af	US Node Grate RL	Pipe US IL	Pipe DS IL	DS Node Grate RL	Cover Min	Pipe DS Bend	Pipe DS Drop	US Node Ku	US Node Kw	Pipe V'head	P'head Loss (Ku.V'head)	WSE Loss (Kw.V'head)	Pipe T'head Loss	US Node HGL	Pipe US HGL	Pipe DS HGL	DS Node HGL	HGL Grade	HGL Grade	F'board US
(-)	(-)	(m)	(mm)	(sq.m)	(%)	(1 in)	(min)	(mm/hr)	(ha)	(L/s)	(min)	(mm/hr)	(ha)	(L/s)	(L/s)	(L/s)	(-)	(m/s)	(m/s)	(m/s)	(m/s)	(m)	(m)	(m)	(m)	(m)	(deg)	(m)	(-)	(-)	(m)	(m)	(m)	(m)	(m)	(m)	(m)	(%)	(1 in)	(m)
AY02 to EA02	CLASS 2	21.77	(2x)600	0.565	0.34	293.6	16.63	45.33	5.6957	717.1	12.13	53.42	4.8623	721.5	721.5	860.2	0.84	1.28	1.69	1.84	1.52	98.92	95.16	95.09	98.61	2.84	0.8	0.05	1.67	1.78	0.08	0.14	0.15	0.05	96.98	96.83	96.78	96.8	0.24	414.6	1.94
AY03 to AY02	CLASS 2	35.06	825	0.535	0.25	400	16.29	45.81	5.6957	724.8	11.73	54.31	4.8494	731.6	731.6	846.7	0.86	1.37	1.77	2.08	1.58	98.12	95.3	95.21	98.92	1.95	-51.2	0.05	0.92	1.03	0.1	0.09	0.1	0.07	97.14	97.04	96.97	96.98	0.19	533	0.98
AY04 to AY03	CLASS 2	26.8	825	0.535	0.25	400	16.04	46.19	5.0599	649.1	12.59	52.4	4.4348	645.5	649.1	846.7	0.77	1.21	1.73	1.99	1.58	97.93	95.42	95.35	98.12	1.64	0	0.05	0.96	1.07	0.08	0.07	0.08	0.04	97.25	97.16	97.13	97.14	0.15	673.9	0.69
AZ01 to AA01	CLASS 2	33.88	1200	1.131	0.25	400	18.25	42.95	15.4986	1849.3	17.69	43.77	15.3105	1861.3	1861.3	1957.7	0.95	1.65	1.96	2.5	1.73	98.39	94.68	94.6	95.8	-0.18	0		2.23	2.54	0.14	0.31	0.35	0.07	96.22	95.87	95.8	95.8	0.21	476.3	2.17
AZ03 to AZ01	CLASS 2	66.46	1050	0.866	0.25	400	17.07	44.68	8.9632	1112.5	14.53	48.59	8.504	1147.9	1147.9	1365.9	0.84	1.33	1.77	2.21	1.58	98.53	94.9	94.73	98.39	2.49	-28.3	0.05	1.98	2.31	0.09	0.18	0.21	0.12	96.5	96.3	96.18	96.22	0.18	566.4	2.02
AZ04 to AZ03	CLASS 2	9.09	300	0.071	0.94	106.1	6	72.3	0.0343	6.9	6	72.3	0.0343	6.9	6.9	94.3	0.07	0.1	0.78	0.65	1.33	98.5	97.37	97.29	98.53	0.95	0.2	2.384	7		0	0		0.08	97.44	97.43	97.34	96.5	1.02	98	1.06
DA01 to AZ01	CLASS 2	8.05	750	0.442	0.65	153.7	18.19	43.04	6.5219	779.7	8.03	64.6	3.082	553	779.7	898.4	0.87	1.76	2.29	2.26	2.03	98.4	96.5	96.45	98.39	1.06	44.6	1.766	1.82	2.19	0.16	0.29	0.35	0.05	97.4	97.05	96.99	96.22	0.74	134.4	1
DA02 to DA01	CLASS 2	12.5	750	0.442	0.61	163.5	18.1	43.18	6.3665	763.6	7.94	64.93	2.9266	527.8	763.6	870.9	0.88	1.73	2.22	2.23	1.97	98.62	96.63	96.55	98.4	1.17	-26.1	0.05	0.93	1.1	0.15	0.14	0.17	0.06	97.57	97.4	97.34	97.4	0.47	212.8	1.05
DA03 to DA02	CLASS 2	12.45	750	0.442	2.33	42.9	18.04	43.26	5.5988	672.8	7.88	65.13	2.1589	390.6	672.8	1701.1	0.4	1.52	3.62	2.11	3.85	98.84	96.97	96.68	98.62	1.04	3.4	0.05	2	2.34	0.12	0.24	0.28	0.05	97.76	97.48	97.54	97.57	-0.5	-201.4	1.08
DA04 to DA03	CLASS 2	17.48	750	0.442	2	50	17.96	43.39	5.5908	673.8	7.79	65.44	2.1509	391	673.8	1575.1	0.43	1.53	3.43	2.11	3.57	99.26	97.37	97.02	98.84	1.16	39.9	0.05	0.24		0.12	0.03		0.26	97.91	97.88	97.72	97.76	0.93	107.4	1.35
DA05 to DA04	CLASS 2	53.5	750	0.442	1	100	17.62	43.88	5.5648	678.3	7.46	66.65	2.1249	393.4	678.3	1113.7	0.61	1.54	2.64	2.12	2.52	99.88	97.95	97.42	99.26	1.16	0	0.05	0.24		0.12	0.03		0.53	98.49	98.47	97.91	97.91	1.04	95.8	1.39
DA06 to DA05	CLASS 2	59.7	750	0.442	0.5	200	17.12	44.6	5.5361	685.9	6.96	68.45	2.0962	398.6	685.9	787.5	0.87	1.55	2.01	2.13	1.78	100.54	98.3	98	99.88	1.19	0	0.05	0.35	0.38	0.12	0.04	0.05	0.3	98.89	98.84	98.52	98.49	0.55	182.7	1.64
DA07 to DA06	CLASS 2	17.85	750	0.442	0.62	162.4	16.99	44.8	5.5099	685.7	6.83	69	2.07	396.7	685.7	873.9	0.78	1.55	2.19	2.13	1.98	100.72	98.46	98.35	100.54	1.5	1.7	0.05	1.45	1.75	0.12	0.18	0.21	0.11	99.19	98.98	98.89	98.89	0.49	202.7	1.53
DA08 to DA07	CLASS 2	10.87	750	0.442	0.5	200	16.9	44.93	5.5099	687.7	6.74	69.36	2.07	398.8	687.7	787.5	0.87	1.56	2.01	2.13	1.78	100.83	98.57	98.51	100.72	1.43	18.2	0.05	1.04	1.24	0.12	0.13	0.15	0.04	99.34	99.18	99.15	99.19	0.27	374.7	1.49
DA09 to DA08	CLASS 2	26.58	750	0.442	0.5	200	16.68	45.25	5.5099	692.6	6.52	70.24	2.07	403.9	692.6	787.5	0.88	1.57	2.01	2.14	1.78	101.12	98.75	98.62	100.83	1.53	12.2	0.05	2.1	2.42	0.13	0.26	0.3	0.09	99.69	99.38	99.31	99.34	0.27	367.3	1.43
DA10 to DA09	CLASS 2	13.32	750	0.442	0.5	200	16.57	45.41	5.4743	690.6	6.17	71.63	1.9537	388.8	690.6	787.5	0.88	1.56	2.01	2.13	1.78	101.27	98.87	98.8	101.12	1.65	-45.9	0.05	1.13	1.35	0.12	0.14	0.17	0.05	99.87	99.7	99.65	99.69	0.38	260.1	1.41
DA12 to DA10	CLASS 2	20.07	750	0.442	0.5	200	16.4	45.66	5.4169	687	16.4	45.66	5.4169	687	687	787.5	0.87	1.56	2.01	2.13	1.78	100.6	99.02	98.92	101.27	1.25	12.4	0.05	1.89	2.21	0.12	0.23	0.27	0.08	100.19	99.92	99.84	99.87	0.38	262.8	0.41
DA13 to DA12	CLASS 2	2	750	0.442	0.5	200	16.38	45.68	5.4169	687.4	16.38	45.68	5.4169	687.4	687.4	787.6	0.87	1.56	2.01	2.13	1.78	100.62	99.08	99.07	100.6	0.67	33.5	0.05	2		0.12	0.25		0.01	100.4	100.16	100.15	100.19	0.38	262.5	0.21
DA11 to DA10	CLASS 2	8.58	300	0.071	1	100	6	72.3	0.045	9	6	72.3	0.045	9	9	96.7	0.09	0.13	0.86	0.7	1.37	101.27	99.8	99.72	101.27	1.1	46.9	0.85	9.7		0	0.01		0.05	99.88	99.87	99.84	99.87	0.4	247.5	1.39
DB01 to DD01	CLASS 2	33.6	300	0.071	2.53	39.6	6.73	69.39	0.4044	77.9	6.58	69.97	0.4025	78.2	78.2	153.8	0.51	1.11	2.18	1.42	2.18	99.8	98.77	97.92	99.26	0.81	90	0.075	2.08	2.64	0.06	0.13	0.17	0.72	99.15	98.99	98.31	98.34	2.02	49.6	0.65
DB02 to DB01	CLASS 2	49.5	300	0.071	1	100	6.19	71.54	0.4044	80.4	6.04	72.12	0.4025	80.6	80.6	96.7	0.83	1.14	1.53	1.44	1.37	100.23	99.32	98.82	99.8	0.78	-90	0.05	1.55		0.07	0.1		0.46	99.64	99.54	99.12	99.15	0.84	118.4	0.59
DB03 to DB02	CLASS 2	67.56	300	0.071	1.25	80	5.46	74.72	0.2737	56.8	5.32	75.37	0.2718	56.9	56.9	108.2	0.53	0.81	1.55	1.24	1.53	100.87	100.21	99.37	100.23	0.74	0	0.05	1.94	2.19	0.03	0.06	0.07	0.8	100.47	100.4	99.64	99.64	1.12	89.4	0.4
DB04 to DB03	CLASS 2	2.15	225	0.04	1	100	5.43	74.85	0.1622	33.7	5.29	75.5	0.1603	33.6	33.7	44.9	0.75	0.85	1.24	1.16	1.13	100.92	100.31	100.28	100.87	0.82	32	0.075	2.18	2.66	0.04	0.08	0.1	0.02	100.56	100.46	100.46	100.47	0.04	2446.9	0.36
DB05 to DB04	CLASS 2	24.79	225	0.04	0.9	111.1	5	76.8	0.0639	13.6	5	76.8	0.0639	13.6	13.6	42.6	0.32	0.34	0.95	0.84	1.07	101.03	100.58	100.36	100.92	0.55	90.1	0.05	7		0.01	0.04		0.16	100.72	100.68	100.54	100.56	0.54	183.5	0.32
DB06 to DB04	CLASS 2	16.71	225	0.04	0.9	111.1	5	76.8	0.0667	14.2	5	76.8	0.0667	14.2	14.2	42.6	0.33	0.36	0.96	0.85	1.07	100.83	100.51	100.36	100.92	0.62	-89.9	0.05	7		0.01	0.05		0.09	100.65	100.6	100.54	100.56	0.39	258.9	0.18
DC01 to DA09	CLASS 2	8.28	300	0.071	1	100	6.32	71.01	0.0247	4.9	6	72.3	0.0238	4.8	4.9	96.7	0.05	0.07	0.71	0.59	1.37	101.12	99.63	99.55	101.12	1.12	87.8	0.8	1.88	2.48	0	0	0	0.05	99.69	99.69	99.65	99.69	0.45	220.8	1.44
DC02 to DC01	CLASS 2	12.13	300	0.071	1	100	6	72.3	0.0157	3.2	6	72.3	0.0157	3.2	3.2	96.7	0.03	0.04	0.63	0.53	1.37	101.41	99.8	99.68	101.12	1.26	-43.7	0.05	9.7		0	0		0.12	99.85	99.85	99.72	99.69	1.04	96.4	1.56
DD01 to DA02	CLASS 2	26.39	375	0.11	2.81	35.6	7.33	67.1	0.7558	140.9	6.52	70.21	0.7418	144.7	144.7	293.9	0.49	1.31	2.65	1.63	2.66	99.26	97.85	97.1	98.62	1.11	43.3	0.475	2.11	2.43	0.09	0.18	0.21	0.63	98.34	98.13	97.54	97.57	2.22	45	0.92
DD02 to DD01	CLASS 2	53.5	300	0.071	1.13	88.6	6.75	69.29	0.3265	62.8	5.75	73.41	0.3212	65.5	65.5	102.8	0.64	0.93	1.54	1.31	1.45	99.88	98.52	97.92	99.26	1.13	0	0.075	1.7		0.04	0.07		0.46	98.8	98.72	98.31	98.34	0.77	129.6	1.08
DD03 to DD02	CLASS 2	59.72	300	0.071	1	100	6	72.3	0.2021	40.6	5	76.8	0.1979	42.2	42.2	96.7	0.44	0.6	1.32	1.11	1.37	100.54	99.17	98.57	99.88	1.1	0	0.05	7		0.02	0.13		0.57	99.46	99.33	98.8	98.8	0.89	112.3	1.08
EA01 to AZ03	CLASS 2	12.08	1050	0.866	0.34	292.5	16.97	44.83	8.9289	1111.8	14.43	48.78	8.4697	1147.7	1147.7	1597.4	0.72	1.33	2.01	2.21	1.84	98.5	94.99	94.95	98.53	2.34	38.9	0.05	1.01	1.2	0.09	0.09	0.11	0.02	96.6	96.5	96.48	96.5	0.18	566.6	1.89
EA02 to EA01	CLASS 2	14.85	1050	0.866	0.32	317.3	16.84	45.01	8.8725	1109.4	14.3	49.03	8.4133	1145.7	1145.7	1533.8	0.75	1.32	1.94	2.21	1.77	98.61	95.04	94.99	98.5	2.34	11.6	0	1.87	2.13	0.09	0.17	0.19	0.03	96.8	96.61	96.59	96.6	0.18	568.5	1.81
EA04 to EA02	CLASS 2	19.26	600	0.283	0.55	181.8	14.13	49.36	3.1672	434.2	8.84	62.02	2.2223	382.8	434.2	455.6	0.95	1.54	1.83	1.99	1.61	98.71	96.77	96.66	98.61	1.41	40.5	1.625	1.61	1.95	0.12	0.19	0.23	0.11	97.47	97.24	97.1	96.8	0.73	137.4	1.23
EA05 to EA04	CLASS 2	77.3	600	0.283	0.4	250	13.3	50.93	2.5774	364.6	8.01	64.66	1.6325	293.2	364.6	388.5	0.94	1.29	1.56	1.85	1.37	99.09	97.13	96.82	98.71	1.36	-0.9	0.05	0.64	0.67	0.08	0.05	0.06	0.25	97.73	97.67	97.43	97.47	0.31	322.4	1.37
EA07 to EA05	CLASS 2	60.24	600	0.283	0.35	285.7	12.62	52.34	2.4039	349.5	7.33	67.12	1.459	272	349.5	363.4	0.96	1.24	1.46	1.81	1.29	99.39	97.39	97.18	99.09	1.39	0	0.05	0.71	0.74	0.08	0.06	0.06	0.18	97.95	97.89	97.72	97.73	0.28	361.7	1.45
EA09 to EA07	CLASS 2	32.08	600	0.283	0.3	333.3	12.22	53.21	2.2138	327.2	6.93	68.57	1.2689	241.7	327.2	336.5	0.97	1.16	1.36	1.77	1.19	99.55	97.54	97.44	99.39	1.43	0	0.05	1.03	1.19	0.07	0.07	0.08	0.09	98.11	98.03	97.95	97.95	0.27	377.3	1.44
EA10 to EA09	CLASS 2	19.43	600	0.283	0.3	333.3	11.98	53.74	2.0813	310.7	6.69	69.53	1.1364	219.5	310.7	336.5	0.92	1.1	1.35	1.73	1.19	99.66	97.64	97.59	99.55	1.29	-8.6	0.05	2.24	2.37	0.06	0.14	0.15	0.05	98.29	98.15	98.1	98.11	0.22	448.7	1.37
EA11 to EA10	CLASS 2	29.76	525	0.216	0.6	166.7	11.7	54.39	2.0669	312.3	6.41	70.67	1.122	220.2	312.3	333.3	0.94	1.44	1.75	1.87	1.54	99.84	97.87	97.69	99.66	1.51	40.4	0.05	2.08	2.38	0.11	0.22	0.25	0.16	98.69	98.44	98.28	98.29	0.53	189.8	1.15
EA12 to EA11	CLASS 2	13.18	525	0.216	0.5	200	11.56	54.71	1.9764	300.4	6	72.3	0.983	197.4	300.4	304.2	0.99	1.39	1.6	1.83	1.41	100.13	97.99	97.92	99.84	1.48	-46.9	0.05	1.98	2.2	0.1	0.19	0.22	0.06	98.94	98.72	98.66	98.69	0.49	205.2	1.19
EA13 to EA12	CLASS 2	20.41	525	0.216	0.5	200	11.35	55.2	1.9649	301.3	11.35	55.2	1.9649	301.3	301.3	304.2	0.99	1.39	1.6	1.84	1.41	100.38	98.14	98.04	100.13	1.45	47.6	0.05	1.85	1.97	0.1	0.18	0.19	0.1	99.21	99.02	98.92	98.94	0.49	203.9	1.17
EA14 to EA13	CLASS 2	2.14	525	0.216	0.5	200	11.33	55.25	1.9649	301.6	11.33	55.25	1.9649	301.6	301.6	304.2	0.99	1.39	1.6	1.84	1.41	100.39	98.2	98.19	100.38	1.62	-43.7	0.05	2		0.1	0.2		0.01	99.41	99.21	99.2	99.21	0.49	203.6	0.98
EA04A to EA04	CLASS 2	8.65	300	0.071	2	50	6	72.3	0.0359	7.2	6	72.3	0.0359	7.2	7.2	136.8	0.05	0.1	1.02	0.66	1.94	98.72	97.24	97.07	98.71	1.11	-75.2	0.3	9.7		0	0.01		0	97.43	97.43	97.43	97.47	-0.01	-17953	1.28
EA08 to EA07	CLASS 2	8.35	300	0.071	1	100	6	72.3	0.0291	5.9	6	72.3	0.0291	5.9	5.9	96.7	0.06	0.08	0.75	0.62	1.37	99.39	97.77	97.69	99.39	1.25	-90	0.3	9.7		0	0		0	97.95	97.95	97.95	97.95	0	-74358	1.44
EA06 to EA05	CLASS 2	8.35	300	0.071	1	100	6	72.3	0.0325	6.5	6	72.3	0.0325	6.5	6.5	96.7	0.07	0.09	0.78	0.64	1.37	99.09	97.51	97.43	99.09	1.21	-90	0.3	9.7		0	0		0	97.73	97.72	97.72	97.73	0	140719	1.36
EB01 to EA04	CLASS 2	32.05	300	0.071	2.1	47.6	7.32	67.15	0.5162	96.3	6.79	69.12	0.5039	96.8	96.8	140.2	0.69	1.37	2.14	1.59	1.98	99.45	97.74	97.07	98.71	1.38	89.1	0.3	2.06	2.54	0.1	0.2	0.24	0.59	98.23	97.99	97.43	97.47	1.73	57.7	1.23
EB02 to EB01	CLASS 2	76.4	300	0.071	1.32	75.7	6.6	69.88	0.5162	100.2	6.08	71.98	0.5039	100.8	100.8	111.2	0.91	1.43	1.78	1.62	1.57	99.92	98.8	97.79	99.45	0.95	-90	0.05	1.7		0.1	0.18		0.9	99.22	99.05	98.18	98.23	1.13	88.2	0.69
EB03 to EB02	CLASS 2	82.5	300	0.071	0.7	142.9	5.53	74.44	0.316	65.3	5.48	74.63	0.3155	65.4	65.4	80.9	0.81	0.93	1.27	1.31	1.15	100.39	99.43	98.85	99.92	0.91	0	0.05	2.65	2.87	0.04	0.12	0.13	0.45	99.76	99.63	99.22	99.22	0.5	201.5	0.63
EB04 to EB03	CLASS 2	13.58	225	0.04	0.8	125	5.32	75.36	0.1372	28.7	5.28	75.56	0.1367	28.7	28.7	40.2	0.71	0.72	1.1	1.09	1.01	100.59	99.59	99.48	100.39	0.97	32.1	0.05	2.18	2.66	0.03	0.06	0.07	0.05	99.87	99.8	99.75	99.76	0.4	252.6	0.71
EB05 to EB04	CLASS 2	20.09	225	0.04	2	50	5	76.8	0.0544	11.6	5	76.8	0.0544	11.6	11.6	63.5	0.18	0.29	1.22	0.8	1.6	100.65	100.04	99.64	100.59	0.96	90	0.05	7		0	0.03		0.3	100.16	100.13	99.86	99.87	1.33	75.3	0.49
EB06 to EB04	CLASS 2	16.91	225	0.04	0.8	125	5	76.8	0.0564	12	5	76.8	0.0564	12	12	40.2	0.3	0.3	0.88	0.81	1.01	100.41	99.77	99.64	100.59	0.58	-90	0.05	7		0	0.03		0.03	99.9	99.86	99.86	99.87	0.01	9285	0.51
EC01 to EA11	CLASS 2	8.95	300	0.071	1	100	6.21	71.45	0.0307	6.1	6	72.3	0.0299	6	6.1	96.7	0.06	0.09	0.76	0.63	1.37	99.84	98.19	98.1	99.84	1.29	89.3	0.225	1.87	2.4	0	0	0	0	98.66	98.66	98.66	98.69	0	25286	1.18
EC02 to EC01	CLASS 2	12.77	300	0.071	3	33.3	6	72.3	0.0205	4.1	6	72.3	0.0205	4.1	4.1	167.6	0.02	0.06	1	0.57	2.37	100.41	98.62	98.24	99.84	1.42	-42	0.05	9.7		0	0		0.02	98.67	98.67	98.66	98.66	0.06	1700.3	1.74
EC03 to EA11	CLASS 2	16.96	300	0.071	1	100	6	72.3	0.0499	10	6	72.3	0.0499	10	10	96.7	0.1	0.14	0.88	0.72	1.37	100.08	98.27	98.1	99.84	1.38	1.9	0.225	9.7		0	0.01		0	98.67	98.66	98.66	98.69	0.01	9318.8	1.41
FA03 to AY03	CLASS 2	7	375	0.11	0.5	200	8.65	62.64	0.5434	94.6	7.28	67.31	0.5304	99.2	99.2	124	0.8	0.9	1.25	1.39	1.12	98.24	96.97	96.93	98.12	0.79	90	1.63	0.67		0.04	0.03		0.04	97.25	97.22	97.16	97.14	0.79	126.8	0.99
FA04 to FA03	CLASS 2	42	375	0.11	0.5	200	8.08	64.46	0.4924	88.2	6.71	69.48	0.4793	92.5	92.5	124	0.75	0.84	1.23	1.35	1.12	98.46	97.23	97.02	98.24	0.81	0	0.05	1.39		0.04	0.05		0.21	97.52	97.47	97.25	97.25	0.53	188.7	0.94
FA05 to FA04	CLASS 2	49	375	0.11	0.5	200	7.37	66.97	0.3593	66.8	6.37	70.82	0.3558	70	70	124	0.56	0.63	1.16	1.22	1.12	98.72	97.52	97.28	98.46	0.77	0	0.05	1.42		0.02	0.03		0.23	97.75	97.72	97.52	97.52	0.42	238.3	0.96
FA06 to FA05	CLASS 2	40.7	300	0.071	0.5	200	6.71	69.47	0.2153	41.6	5.71	73.62	0.2119	43.3	43.3	68.4	0.63	0.61	1.02	1.12	0.97	98.93	97.8	97.6	98.72	0.79	0	0.075	1.97		0.02	0.04		0.21	98.01	97.97	97.76	97.75	0.53	188.3	0.92
FA07 to FA06	CLASS 2	37.3	300	0.071	0.5	200	6	72.3	0.113	22.7	5	76.8	0.1107	23.6	23.6	68.4	0.35	0.33	0.88	0.92	0.97	99.12	98.04	97.85	98.93	0.75	0	0.05	7		0.01	0.04		0.17	98.2	98.16	98.01	98.01	0.39	253.6	0.93
FB01 to MA05	CLASS 2	11.77	300	0.071	1	100	6.3	71.08	0.1948	38.5	5.94	72.56	0.1936	39	39	96.7	0.4	0.55	1.29	1.08	1.37	99.1	96.92	96.8	98.56	1.56	77.4	0.45	1.51	1.88	0.02	0.02	0.03	0.02	98.11	98.08	98.06	98.06	0.16	614.7	0.99
FB02 to FB01	CLASS 2	25.1	300	0.071	1.21	82.4	6	72.3	0.1827	36.7	5.64	73.93	0.1817	37.3	37.3	106.5	0.35	0.53	1.37	1.07	1.51	99.41	97.99	97.68	99.1	1.09	13.2	0.763	3.23	3.72	0.01	0.05	0.05	0.08	98.19	98.14	98.1	98.11	0.14	700.7	1.22
FB03 to FB02	CLASS 2	41.88	300	0.071	1.27	78.9	5	76.8	0.0737	15.7	5	76.8	0.0737	15.7	15.7	108.9	0.14	0.22	1.1	0.82	1.54	99.85	98.57	98.04	99.41	0.95	27.5	0.05	7		0	0.02		0.5	98.68	98.66	98.18	98.19	1.15	87.1	1.17
MA05 to MA-04	CLASS 2	63.5	750

REFER TO DRAWING DRG-0701 FOR CONTINUATION



LEGEND

- PROPOSED KERB & CHANNEL
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- PROPOSED SHARED PATH
- STREET TREE
- KERB INLET DIVERSION. REFER TO DRAWING DRG-0702 FOR DETAILS
- SWD — PROPOSED STORMWATER DRAINAGE
- S — PROPOSED SEWERAGE RETICULATION
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- STAGE BOUNDARY
- EXISTING TREES TO BE RETAINED
- EXISTING TREES TO BE REMOVE

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. PASSIVE IRRIGATION LOCATIONS ARE SUBJECT TO FINAL LANDSCAPE AND ELECTRICAL DESIGN PLANS.
3. FOR FURTHER DETAILS REFER TO THE LANDSCAPE ARCHITECT DESIGN PLANS.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON


Title

PASSIVE IRRIGATION LAYOUT
SHEET 1

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0700	04

Date Plotted: 27 Jul 2023 - 04:55pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0700-PassiveIrrigation.dwg V1



LEGEND

- PROPOSED KERB & CHANNEL
- PROPOSED ROAD PAVEMENT
- PROPOSED CONCRETE FOOTPATH/DRIVEWAY
- PROPOSED SHARED PATH
- STREET TREE
- KERB INLET DIVERSION. REFER TO DRAWING DRG-0702 FOR DETAILS
- SWD — PROPOSED STORMWATER DRAINAGE
- S — PROPOSED SEWERAGE RETICULATION
- W — PROPOSED WATER RETICULATION
- R — PROPOSED RECYCLED WATER RETICULATION
- E — PROPOSED ELECTRICITY UNDER GROUND
- C — PROPOSED COMMUNICATIONS
- G — PROPOSED GAS RETICULATION
- STAGE BOUNDARY
- EXISTING TREES TO BE RETAINED
- EXISTING TREES TO BE REMOVE

NOTE:

1. FOR GENERAL NOTES, REFER TO DRAWING No. DRG-0002.
2. PASSIVE IRRIGATION LOCATIONS ARE SUBJECT TO FINAL LANDSCAPE AND ELECTRICAL DESIGN PLANS.
3. FOR FURTHER DETAILS REFER TO THE LANDSCAPE ARCHITECT DESIGN PLANS.

Issue	Description	DR	CH	VE	Date
04	DESIGN CO-ORDINATION AMENDMENTS	CM	CS	IOC	18.07.23
03	RESPONSE TO COUNCIL RFI	CM	CS	SE	12.07.23
02	REMOVING KERB PINCH POINTS	CM	KR	IOC	08.05.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

100mm on Original

Scales

0 10 20 30 40 50m

1 : 500

Planner

RobertsDay
planning·design·place

Client

RESIMAX GROUP

Status

FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project

EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON


Title

PASSIVE IRRIGATION LAYOUT
SHEET 2

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone | Stage | Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD	CV	DRG	0701	04

Date Plotted: 27 Jul 2023 - 04:55pm File Name: C:\Users\menezc4027\DC\ACCDocs\Arcadis\A-AU-10029435-Eynesbury Estate\Project Files\01_WORK IN PROGRESS\01_Civil_CV\Stage22A\Drawings\10029435-AAP-AA22ADD-CV-DRG-0700-PassiveIrrigation.dwg V1



PLAN
1:250

GENERAL NOTES:


1. AT HIGHLY CONSTRAINED SITES, GRAVEL TRENCHES CAN BE MODIFIED IN THE FOLLOWING WAYS:
   - REDUCED OFFSET OF 0.75 m FROM TREE CENTRELINE
   - DIMENSION 1.0 mLONG B0.6 mWIDE B0.75 mDEEP
2. KERB INLET DIVERSIONS TO BE INSTALLED BY CIVIL CONTRACTOR. STREET TREES TO BE INSTALLED BY LANDSCAPE CONTRACTOR



TREENET INLET

LEGEND :

- S — SEWER
- G — GAS
- R — RECYCLE WATER
- W — POTABLE WATER
- SWD — STORM WATER DRAIN
- GRAVEL TRENCH - (rail ballast nominal size 50mm)
- BALANCING PIPE - 90mmd (slotted section within gravel trench)
- BALANCING PIPE - 90mmd (Solid pipe section between gravel trenches)



GRAVEL TRENCH (KERB INLET DIVERSION)
1:10
A

Issue	Description	DR	CH	VE	Date
02	UPDATES FOR REGISTRATION OF ENGINEERS	CM	CS	IOC	12.07.23
01	ISSUED TO COUNCIL FOR APPROVAL	CM	HA	IOC	11.11.22

Scales

0 100 200 400 600 800 1000mm
1 : 10

0 5 10 15 20 25m
1 : 250

100mm on Original

Planner: RobertsDay planning·design·place

Client: RESIMAX GROUP

Status: FOR APPROVAL
NOT TO BE USED FOR CONSTRUCTION

ø Copyright reserved

Original Issue Signatures			
Drawn	C.MENEZ	Original Size	A1
Designed	H.ALAM	Height Datum	AHD
Project Manager	S.EISEL	Grid	MGA
Verified	I.O'CONNOR		

Project: EYNESBURY TOWNSHIP
STAGE 22A
CITY OF MELTON

Title: PASSIVE IRRIGATION DETAILS

ARCADIS
Arcadis Australia Pacific Pty Limited
Level 18, Queen & Collins Tower
376-390 Collins Street
Melbourne VIC 3000 Australia
ABN 76 104 485 289
Tel No: +61 3 8623 4000
www.arcadis.com

Project No.	Originator	Zone / Stage	Phase	Discipline	Type	Drawing No.	Issue
10029435	AAP	AA22ADD		CV	DRG	0702	02